



Security cupboards

- In a particularly solid design
- Resistance class I in accordance with EN 1143-1, IMP certified and tested and certified to EN 15659 LFS 30 P

Application: burglary protection / fire protection / value assurance. Fire protection: LFS 30 P according to EN 15659. Burglary protection: class I according to EN 1143-1. Lock type: dual bit high security lock. Number of drill holes: 2. Door thickness: 94 mm. Thickness of body: 65.5 mm. Material: steel, painted. Colour: light grey RAL 7035.

Height	mm	675	1875	1875
Width	mm	495	955	1305
Depth	mm	472	527	527
Fittings		1 shelf	4 shelves	4 shelves
Capacity	l	55	490	701
Number of files	pcs.	4	50	75
Number of doors	pcs.	1	2	2
Weight	kg	106	398	494
	Ref.	615 807 3H	615 813 3H	615 814 3H
	£	979.00	2525.00	2925.00

Electronic locks with mechanical emergency access via DB lock

Lock type: electronic lock with emergency access.

Ref. 123 120 3H £ 109.00

Mechanical combination locks

Type: protruding. Lock type: mechanical combination lock.

Ref. 900 098 3H £ 197.00

Electronic locks, 1 master code and up to 9 user codes

Lock type: electronic lock.

Ref. 615 774 3H £ 171.00

Electronic locks, 1 master code and up to 9 user codes

Lock type: electronic lock.

Ref. 615 815 3H £ 171.00