

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.:	263.Halle	PROline-paint Hallenmarkier-	43227 EN
Print date:	04.08.2015	Revision date: 29.07.2015	Page: 1 / 7
Version:	1.6	Issue date: 29.07.2015	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier)	263.Halle
Identification of the substance or mixture	PROline-paint Hallenmarkier- farbe - alle Farbtöne - seidenmatt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Coating material

1.3.

supplier (manufacturer/importer/downstream user/distributor)

Moravia GmbH	
Rostocker Straße 10	Telephone: +49 (0)611/ 95020
65191 Wiesbaden	Telefax: +49 (0)611/ 9502200
	E-mail service@moravia.de

Dept. responsible for information:

E-mail

service@moravia.de

Emergency telephone number

+49 (0)611/ 95020

Only available during office hours.

1.4.

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 2 / H225	flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Lact. / H362	Reproductive toxicity	May cause harm to breast-fed children.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H362	May cause harm to breast-fed children.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P263	Avoid contact during pregnancy/while nursing.
P370 + P378	In case of fire: Use Extinguishing powder or sand to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.

contains:

alkanes, C14-17, chloro

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 263.Halle PROline-paint Hallenmarkier-
Print date: 04.08.2015 Revision date: 29.07.2015 43227 EN
Version: 1.6 Issue date: 29.07.2015 Page: 2 / 7

ethyl acetate

Supplemental Hazard information (EU):

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

3. Composition / Information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description: Preparation of synthetic binders, pigments and solvents

Hazardous ingredients:

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

EC No.:	REACH No.:	Wt %
CAS No.:	Chemical name:	Remark:
INDEX No.:	classification:	
205-500-4	01-2119475103-46-xxxx	
141-78-6	ethyl acetate	25 - 50
607-022-00-5	Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	
215-535-7	01-2119488216-32-xxxx	
1330-20-7	xylene	2,5 - 5
601-022-00-9	Flam. Liq. 3 H226 / Acute Tox. 4 H332 / Acute Tox. 4 H312 / Skin Irrit. 2 H315	
265-185-4	01-2119458049-33-xxxx	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	2,5 - 5
649-330-00-2	Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H336 / Aquatic Chronic 2 H411	
287-477-0	01-2119519269-33-xxxx	
85535-85-9	alkanes, C14-17, chloro	1 - 2,5
602-095-00-X	Lact. H362 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	
202-849-4		
100-41-4	ethylbenzene	1 - 2,5
601-023-00-4	Flam. Liq. 2 H225 / Acute Tox. 4 H332 / STOT RE 2 H373 / Asp. Tox. 1 H304	

Additional information

Full text of classification: see section 16

4. First-aid measures

4.1. Description of first aid measures:

General information:

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation:

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact:

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion:

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed:

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 263.Halle
Print date: 04.08.2015
Version: 1.6

PROline-paint Hallenmarkier-
Revision date: 29.07.2015
Issue date: 29.07.2015

43227 EN
Page: 3 / 7

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

7. Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.:	263.Halle	PROline-paint Hallenmarkier-	
Print date:	04.08.2015	Revision date: 29.07.2015	43227 EN
Version:	1.6	Issue date: 29.07.2015	Page: 4 / 7

8. Exposure controls / Personal protection

8.1. Control parameters

ethylbenzene

INDEX No.: 601-023-00-4 / EC No.: 202-849-4 / CAS No.: 100-41-4

WEL, TWA: 441 mg/m³; 100 ppm

WEL, STEL: 552 mg/m³; 125 ppm

Remark: (May be absorbed through the skin.)

xylene, mixture of isomers

INDEX No.: 601-022-00-9 / EC No.: 215-535-7 / CAS No.: 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

ethyl acetate

INDEX No.: 607-022-00-5 / EC No.: 205-500-4 / CAS No.: 141-78-6

WEL, TWA: 730 mg/m³; 200 ppm

WEL, STEL: 1460 mg/m³; 400 ppm

Additional information:

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection:

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection:

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection:

Wear closely fitting protective glasses in case of splashes.

Protective clothing:

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures:

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: liquid

Colour: Trade name/designation

Odour: characteristic

Safety relevant basis data

Flash point:

-4 °C

DIN 53213

Ignition temperature in °C:

210 °C

Method Remark

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 263.Halle
Print date: 04.08.2015
Version: 1.6

PROline-paint Hallenmarkier-
Revision date: 29.07.2015
Issue date: 29.07.2015

43227 EN
Page: 5 / 7

Lower explosion limit:	1,6 Vol-%	
Upper explosion limit:	11,5 Vol-%	
Vapour pressure at 20 °C:	33,68 mbar	calculated.
Density at 20 °C:	1,18 g/cm ³	DIN 53217
Water solubility (g/L):	insoluble	
pH at 20 °C:	neutral	
Viscosity at °C	ca. 35 dPa.s	
Solvent separation test (%):	< 3 %	
Solid content (%):	56 Wt %	
solvent content:		
Organic solvents:	44,3 Wt %	
Water:	0,0 Wt %	

9.2. Other information:

10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

11. Toxicological information

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

xylene

oral, LD50, Rat: > 2000 mg/kg

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Naphtha (petroleum), hydrodesulfurized heavy

Aspiration hazard

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties:

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.:	263.Halle	PROline-paint Hallenmarkier-	
Print date:	04.08.2015	Revision date: 29.07.2015	43227 EN
Version:	1.6	Issue date: 29.07.2015	Page: 6 / 7

Remark

There is no information available on the preparation itself .

12. Ecological information

overall evaluation:

Classification according to Regulation (EC) No. 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation:

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111	waste paint and varnish containing organic solvents or other dangerous substances
--------	---

packaging

Recommendation:

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

14. Transport information

14.1. UN number:

1263

14.2. UN proper shipping name

Land transport (ADR/RID):	Paint
Sea transport (IMDG):	PAINT
Air transport (ICAO-TI / IATA-DGR):	Paint

14.3. Transport hazard class(es)

3

14.4. Packing group:

Land transport (ADR/RID):	III
for packages > 450 litres:	II
Sea transport (IMDG):	III
for packages > 30 litres:	II
Air transport (ICAO-TI / IATA-DGR):	III
for packages > 30 litres:	II

14.5. Environmental hazards:

Land transport (ADR/RID)	n.a.
Marine pollutant	n.a.

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.:	263.Halle	PROline-paint Hallenmarkier-	43227 EN
Print date:	04.08.2015	Revision date: 29.07.2015	Page: 7 / 7
Version:	1.6	Issue date: 29.07.2015	

case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Additional information:

Land transport (ADR/RID)

tunnel restriction code	E
for packages > 450 litres:	D/E

Sea transport (IMDG)

EmS-No.	F-E, S-E
---------	----------

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2:	524
VOC-value (in g/L) ASTM D 2369:	524

National regulations

Restrictions of occupation:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

16. Other information

Carbides.:

Flam. Liq. 2 / H225	flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Lact. / H362	Reproductive toxicity	May cause harm to breast-fed children.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic life.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
STOT RE 2 / H373	Specific target organ toxicity (repeated exposure)	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

Additional information:

Classification according to Regulation (EC) No. 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.