

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

818-Q7811-00
Version 12.0

PROline-paint 2K-Industrial floor
Revision date 2 Feb 2026

Print date 2 Feb 2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

263.20.039 PROline-paint 2K-Industrial floor stone grey semi glossy MR 3,9:1,1 VT with hardener
UFI: 9MSJ-30H5-P00Q-WUKJ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

1.3 Details of the supplier of the safety data sheet

Supplier

MORAVIA GmbH
Rostocker Straße 10 Telephone: +49 611 95020
65191 Wiesbaden Telefax: +49 611 9502200
Germany E-mail: service@moravia.de
Website: www.moravia.de

Department responsible for information

E-mail (competent person) sdb@moravia.de

1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-844636
24 hr. emergency phone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

- * Skin Irrit. 2 H315 Causes skin irritation.
- * Skin Sens. 1 H317 May cause an allergic skin reaction.
- * Eye Irrit. 2 H319 Causes serious eye irritation.
- * Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS07 GHS09

Signal word

Warning

Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- * P273 Avoid release to the environment.
- * P280 Wear protective gloves and eye protection/face protection.
- P391 Collect spillage.

Hazard components for labelling

2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine
3-aminomethyl-3,5,5-trimethylcyclohexylamine
m-Xylilendiamine

Supplemental hazard information

not applicable

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

818-Q7811-00
Version 12.0

PROline-paint 2K-Industrial floor
Revision date 2 Feb 2026

Print date 2 Feb 2026

2.3 Other hazards

* **Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

* **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

Preparation of synthetic binders, pigments and water

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
* - -	aliphatic polyamines Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	8,00 < 10,0
* - -	aliphatic polyamine Aquatic Chronic 2 H411 / EUH071	3,00 < 5,00
90530-15-7 292-053-3 -	2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine 01-2120094715-47 Skin Corr. 1B H314 / Skin Sens. 1A H317 / Eye Dam. 1 H318	1,00 < 2,00
1477-55-0 216-032-5 -	m-Xylilendiamine 01-2119480150-50 Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Acute Tox. 4 H332 / Aquatic Chronic 3 H412 / EUH071	0,500 < 1,00
2855-13-2 220-666-8 612-067-00-9	3-aminomethyl-3,5,5-trimethylcyclohexylamine 01-2119514687-32 Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1A H317 / Eye Dam. 1 H318 ATE (dermal): > 2,000 mg/kg ATE (inhalative): > 5.01 mg/L (4 h)	0,300 < 0,500

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

818-Q7811-00
Version 12.0

PROline-paint 2K-Industrial floor
Revision date 2 Feb 2026

Print date 2 Feb 2026

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetRSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class

LGK8B - Non-combustible corrosive substances

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

818-Q7811-00
Version 12.0

PROline-paint 2K-Industrial floor
Revision date 2 Feb 2026

Print date 2 Feb 2026

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No data available

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	Acute - inhalation, local effects	0.073 mg/m ³
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	Long-term – inhalation, local effects	0.073 mg/m ³
1477-55-0	m-Xylilendiamine	Long-term – inhalation, systemic effects	1.2 mg/m ³
1477-55-0	m-Xylilendiamine	Long-term – inhalation, local effects	0.2 mg/m ³
1477-55-0	m-Xylilendiamine	Long-term - dermal, systemic effects	0.33 mg/kg bw/day

DNEL Consumer

CAS No.	Substance name	DNEL type	DNEL value
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	Long-term - oral, systemic effects	0.3 mg/kg bw/day

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
90530-15-7	2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine	aquatic, intermittent release	0.992 mg/L
90530-15-7	2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine	aquatic, marine water	0.001 mg/L
90530-15-7	2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine	sewage treatment plant	4.65 mg/L
90530-15-7	2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine	sediment, freshwater	96.97 mg/kg sediment dw
90530-15-7	2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine	sediment, marine water	9.68 mg/kg sediment dw
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	aquatic, intermittent release	0.23 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	aquatic, marine water	0.006 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	sewage treatment plant	3.18 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	sediment, freshwater	5.784 mg/kg sediment dw
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	sediment, marine water	0.578 mg/kg sediment dw
1477-55-0	m-Xylilendiamine	aquatic, intermittent release	0.152 mg/L
1477-55-0	m-Xylilendiamine	aquatic, marine water	0.009 mg/L
1477-55-0	m-Xylilendiamine	sewage treatment plant	10 mg/L
1477-55-0	m-Xylilendiamine	sediment, freshwater	12.4 mg/kg sediment dw
1477-55-0	m-Xylilendiamine	sediment, marine water	1.24 mg/kg sediment dw

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

818-Q7811-00
Version 12.0

PROline-paint 2K-Industrial floor
Revision date 2 Feb 2026

Print date 2 Feb 2026

Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo.

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Anti-static clothing including shoes are recommended.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	grey
Odour	characteristic
pH at 20 °C	10 - 11
Melting point/freezing point	< -60 °C
Initial boiling point and boiling range	100 °C Source: 2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine
Flash point	not applicable Source: water
flammability	Combustible liquid.
Lower explosion limit at 20°C	not determined
Upper explosion limit at 20°C	not determined
Vapour pressure at 20°C	9.579 mbar
Relative vapour density	not applicable
Density at 20 °C	1.47 kg/l
Water solubility at 20°C	partially soluble
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	> 360 °C Source: 2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine
Decomposition temperature	not determined
Viscosity at 20 °C	< 700 mm ² /s
particle characteristics	not applicable

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

818-Q7811-00
Version 12.0

PROline-paint 2K-Industrial floor
Revision date 2 Feb 2026

Print date 2 Feb 2026

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO₂), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

3-aminomethyl-3,5,5-trimethylcyclohexylamine

LD50: dermal (Rat): > 2,000 mg/kg

LC50: inhalative (Rat): > 5.01 mg/L (4 h)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Acute (short-term) fish toxicity

3-aminomethyl-3,5,5-trimethylcyclohexylamine

LC50: (*Leuciscus idus* (golden orfe)): 110 mg/L (96 h)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

818-Q7811-00
Version 12.0

PROline-paint 2K-Industrial floor
Revision date 2 Feb 2026

Print date 2 Feb 2026

Acute (short-term) toxicity to algae and cyanobacteria

EC50 (Desmodesmus subspicatus): > 50 mg/L (72 h)

EC10: (Desmodesmus subspicatus): 11.2 mg/L (72 h)

* **Toxicity to microorganisms**

EC10: 1120 mg/L (18 h)

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

* Partition coefficient: n-octanol/water = 0.9 (2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine)

Partition coefficient: n-octanol/water = 0.15 (m-Xylilendiamine)

Partition coefficient: n-octanol/water = 1.56 (3-aminomethyl-3,5,5-trimethylcyclohexylamine)

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080112 - waste paint and varnish other than those mentioned in 08 01 11

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number or ID number

UN 2735

14.2 UN proper shipping name

Land transport (ADR/RID)

Amines, liquid, corrosive, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-Xylilendiamine, 2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine)

Sea transport (IMDG)

* Amines, liquid, corrosive, n.o.s. (contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-Xylilendiamine, 2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine)

Air transport (ICAO-TI / IATA-DGR)

* Amines, liquid, corrosive, n.o.s. (contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-Xylilendiamine, 2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine)

14.3 Transport hazard class(es)

Land transport (ADR/RID) 8

Sea transport (IMDG) 8

Air transport (ICAO-TI / IATA-DGR) 8

14.4 Packing group

Land transport (ADR/RID) II

Sea transport (IMDG) II

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

818-Q7811-00
 Version 12.0

PROline-paint 2K-Industrial floor
 Revision date 2 Feb 2026

Print date 2 Feb 2026

Air transport (ICAO-TI / IATA-DGR) II

14.5 Environmental hazards

Land transport (ADR/RID) not applicable
 Sea transport (IMDG) not applicable

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
 Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

Tunnel restriction code: E
 Limited quantity (LQ): 1 ltr
 Hazard identification number (Kemler No.): 80

Sea transport (IMDG)

Segregation group: IMDG-Code segregation group 18 - Alkalis
 EmS-No.: F-A, S-B
 Limited quantity (LQ): 1 ltr

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

* **Authorisations and/or restrictions on use**

* **Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)**

* Use restriction according to REACH annex XVII, no.: 03

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.
 Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 2 g/l

* **Regulation (EU) No. 528/2012 on biocides**

* biocide, active substance: reaction mass of 5-chloro-2-methyl-2<l>H</l>-isothiazol-3-one and 2-methyl-2H</l>-isothiazol-3-one (3:1)

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

E2 Hazardous to the aquatic environment in Category Chronic 2
 Quantity 1: 200t; Quantity 2: 500t

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

REACH No.	Substance name	CAS No. EC No.
01-2120094715-47	2-Propenenitrile, reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine	90530-15-7 292-053-3
01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8
01-2119480150-50	m-Xylilendiamine	1477-55-0 216-032-5

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

818-Q7811-00
Version 12.0

PROline-paint 2K-Industrial floor
Revision date 2 Feb 2026

Print date 2 Feb 2026

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2	Calculation method.
Skin Sens. 1	Calculation method.
Eye Irrit. 2	Calculation method.
Aquatic Chronic 2	Calculation method.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL: Occupational Exposure Limit Value
BLV: Biological limit values
CAS: Chemical Abstracts Service
CLP: Classification, Labelling and Packaging
CMR: Carcinogenic, Mutagenic and Reprotoxic
DIN: German Institute for Standardization / German industrial standard
DNEL: Derived No-Effect Level
EAKV: European Waste Catalogue Directive
EC: Effective Concentration
EC: European Community
EN: European Standard
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code: International Maritime Code for Dangerous Goods
ISO: International Organization for Standardization
LC: Lethal Concentration
LD: Lethal Dose
MAK: Maximum workplace concentration
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD: Organisation for Economic Cooperation and Development
PBT: persistent, bioaccumulative, toxic
PNEC: Predicted No Effect Concentration
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
UN: United Nations
VOC: Volatile Organic Compounds
vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.