according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

according to resignation (=0, 110 100,=0.10

Article No.: 263.2K PROline-paint 2K-Hallenbe-Print date: 04.08.2015 Revision date: 19.06.2015 Version: 1.3 Issue date: 19.06.2015

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier): 263.2K

Identification of the substance or mixture PROline-paint 2K-Hallenbeschichtung alle Farbtöne sdgl.

MV 3,9:1,1 VT mit Härter

43227 EN

Page: 1 / 7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Coating material

1.3.

supplier (manufacturer/importer/downstream user/distributor)

Moravia GmbH

Rostocker Straße 10 Telephone: +49 (0)611/ 95020
65191 Wiesbaden Telefax: +49 (0)611/ 9502200
E-mail service@moravia.de

Dept. responsible for information:

E-mail

service@moravia.de +49 (0)611/ 95020

Emergency telephone number Only available during office hours.

1.4.

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation.

Eye Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation.

Skin Sens. 1 / H317 respiratory or skin sensitisation May cause an allergic skin reaction.

Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Warning

Hazard statements:

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P280 Wear protective gloves and eye/face protection.

contains:

2-Propenenitrile, Reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine

3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-Xylilendiamine

Supplemental Hazard information (EU):

n.a.

2.3. Other hazards

3. Composition / Information on ingredients

3.2. Mixtures

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article No.: 263.2K Print date: 04.08.2015 Version:

PROline-paint 2K-Hallenbe-Revision date: 19.06.2015 Issue date: 19.06.2015

43227 EN Page: 2 / 7

Product description / chemical characterization

Description: Preparation of synthetic binders, pigments and water

Hazardous ingredients:

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

EC No.: CAS No.:	REACH No.: Chemical name:	Wt %	
INDEX No.:	classification:	Remark:	
	aliphatic polyamines	5 - 10	
	Aquatic Acute 1 H400		
	aliphatic polyamine Aquatic Chronic 1 H410	2,5 - 5	
90530-15-7	2-Propenenitrile, Reaction products with 3-amino-1,5,5-trimethylcyclohexanemethanamine Acute Tox. 4 H302 / Acute Tox. 4 H332 / Skin Corr. 1 H314 / Skin Sens. 1 H317	1 - 2,5	
220-666-8 2855-13-2 612-067-00-9	01-2119514687-32-xxxx 3-aminomethyl-3,5,5-trimethylcyclohexylamine Acute Tox. 4 H312 / Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412	0,5 - 1	
216-032-5 1477-55-0			

Additional information

Full text of classification: see section 16

First-aid measures

4.1. Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation:

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact:

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion:

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm.

Most important symptoms and effects, both acute and delayed:

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

5. Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media

The product itself does not burn.Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons:

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

PROline-paint 2K-Hallenbe-Article No.: 263.2K Print date: 04.08.2015 Revision date: 19.06.2015 Version: Issue date: 19.06.2015

strong water iet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Special protective equipment for firefighters:

Provide a conveniently located respiratory protective device.

Additional information

Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

43227 EN

Page: 3 / 7

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

Reference to other sections 6.4.

Observe protective provisions (see chapter 7 and 8).

7. Handling and storage

Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eves and clothes. Avoid respiration of swarf, When using do not eat, drink or smoke, Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Protect against:: Frost

Specific end use(s) 7.3.

Observe technical data sheet. Observe instructions for use.

Exposure controls / Personal protection

8.1. **Control parameters**

n.a.

Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection:

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.: 263.2K PROline-paint 2K-Hallenbe-

 Print date:
 04.08.2015
 Revision date: 19.06.2015
 43227 EN

 Version:
 1.3
 Issue date: 19.06.2015
 Page: 4 / 7

Hand protection:

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection:

Wear closely fitting protective glasses in case of splashes.

Protective clothing:

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures:

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Cafaty relevant basis de

Physical state: liquid

Colour: Trade name/designation

Odour: characteristic

Safety relevant basis data		Unit	Method	Remark
Flash point (°C):	n.a.			
Ignition temperature in °C:	n.a.			
Lower explosion limit:	n.a.			
Upper explosion limit:	n.a.			
Vapour pressure at 20 °C:	10,47	mbar	calculated.	
Density at 20 °C:	1,34	g/cm³	DIN 53217	
Water solubility (g/L):	partially soluble			
pH at 20 °C:	neutral			
Viscosity at 20 °C:	30 s 8 mm		DIN 53211	
Solvent separation test (%):	< 3	%		
Solid content (%):	55	Wt %		
solvent content:				
Organic solvents::	0,2	Wt %		
Water:	44,7	Wt %		

9.2. Other information:

10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

11. Toxicological information

Classification according to Regulation (EC) No. 1272/2008 [CLP]

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

PROline-paint 2K-Hallenbe-263.2K Article No.: Print date: 04.08.2015 Revision date: 19.06.2015

43227 EN Version: Issue date: 19.06.2015 Page: 5 / 7

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Toxicological data are not available.

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatique, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties:

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself.

12. **Ecological information**

overall evaluation:

Classification according to Regulation (EC) No. 1272/2008 [CLP]

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

12.1. Toxicity

No information available.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

PROline-paint 2K-Hallenbe-263.2K Article No.: Print date: 04.08.2015 Revision date: 19.06.2015

43227 EN Version: Issue date: 19.06.2015 Page: 6 / 7

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or

other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

14. Transport information

14.1. **UN number:**

3082

14.2. UN proper shipping name

Land transport (ADR/RID): Environmentally hazardous substance, liquid, n.o.s.

(Aliphatische Polyamine)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Sea transport (IMDG):

(Aliphatische Polyamine)

Air transport (ICAO-TI / IATA-DGR): Environmentally hazardous substance, liquid, n.o.s.

(Aliphatische Polyamine)

14.3. Transport hazard class(es)

9

14.4. Packing group:

Ш

14.5. Environmental hazards:

Land transport (ADR/RID) **UMWELTGEFÄHRDEND** Marine pollutant p / Aliphatische Polyamine

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Additional information:

Land transport (ADR/RID)

Е tunnel restriction code

Sea transport (IMDG)

EmS-No. F-A, S-F

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

Regulatory information 15.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 2 6 VOC-value (in g/L) ASTM D 2369:

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.: 263.2K PROline-paint 2K-Hallenbe-Print date: 04.08.2015 Revision date: 19.06.2015 Version: 1.3 Issue date: 19.06.2015

Revision date: 19.06.2015 43227 EN Issue date: 19.06.2015 Page: 7 / 7

16. Other information

Carbides.:

Aquatic Acute 1 / H400 Hazardous to the aquatic environment Very toxic to aquatic life.

Aquatic Chronic 1 / H410 Hazardous to the aquatic environment Very toxic to aquatic life with long lasting

effects.

Acute Tox. 4 / H302 Acute toxicity (oral) Harmful if swallowed.
Acute Tox. 4 / H332 Acute toxicity (inhalative) Harmful if inhaled.

Skin Corr. 1 / H314 skin corrosion/irritation Causes severe skin burns and eye damage.

Skin Sens. 1 / H317 respiratory or skin sensitisation May cause an allergic skin reaction.

Acute Tox. 4 / H312 Acute toxicity (dermal) Harmful in contact with skin. Skin Corr. 1B / H314 skin corrosion/irritation Causes severe skin burns at

Skin Corr. 1B / H314 skin corrosion/irritation Causes severe skin burns and eye damage.

Aquatic Chronic 3 / H412 Hazardous to the aquatic environment Harmful to aquatic life with long lasting effects.

Additional information

Classification according to Regulation (EC) No. 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.