

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier**
Floor Cleaner STRONG
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
Relevant identified uses
Washing and cleaning products (including solvent based products)
- 1.3 Details of the supplier of the safety data sheet**
Supplier (manufacturer/importer/only representative/downstream user/distributor)
Bio-Circle Surface Technology GmbH
Street : Berensweg 200
Postal code/city : 33334 Gütersloh
Telephone : +49 5241 9443 0
Telefax : +49 5241 9443 44
Information contact : labor@bio-circle.de
- 1.4 Emergency telephone number**
+49 5241 9443 51 during normal office hours

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture**
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.
Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.
- 2.2 Label elements**
Labelling according to Regulation (EC) No. 1272/2008 [CLP]
Hazard pictograms

Corrosion (GHS05)
Signal word
Danger
Hazard components for labelling
DISODIUM METASILICATE ; CAS No. : 6834-92-0
POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3
Hazard statements
H318 Causes serious eye damage.
H315 Causes skin irritation.
Precautionary statements
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/....
P302+P352 IF ON SKIN: Wash with plenty of water/....
P332+P313 If skin irritation occurs: Get medical advice/attention.
- 2.3 Other hazards**
None

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Hazardous ingredients

BUTYL CELLOSOLVE ; REACH registration No. : 01-2119475108-36-XXXX ; EC No. : 203-905-0; CAS No. : 111-76-2

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

POTASSIUM CUMENESULFONATE ; REACH registration No. : 01-2119489427-24-XXXX ; EC No. : 629-764-9; CAS No. : 164524-02-1

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

(1-METHYLETHYL)BENZENESULFONIC ACID, SODIUM SALT ; REACH registration No. : 01-2119489411-37-XXXX ; EC No. : 239-854-6; CAS No. : 15763-76-5

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

DISODIUM METASILICATE ; REACH registration No. : 01-2119449811-37-XXXX ; EC No. : 229-912-9; CAS No. : 6834-92-0

Weight fraction : $\geq 1 - < 2 \%$

Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 STOT SE 3 ; H335

POTASSIUM HYDROXIDE ; REACH registration No. : 01-2119487136-33-XXXX ; EC No. : 215-181-3; CAS No. : 1310-58-3

Weight fraction : $\geq 1 - < 2 \%$

Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302

ALCOHOLS, C10-C12, ETHOXYLATED, PROPOXYLATED ; REACH registration No. : (Polymer) ; CAS No. : 68154-97-2

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

Water Foam Extinguishing powder Carbon dioxide (CO₂) Sand Nitrogen Extinguishing blanket

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon dioxide (CO₂) Carbon monoxide.

5.3 Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed.

7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against Frost

Hints on joint storage

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

BUTYL CELLOSOLVE ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 20 ppm / 98 mg/m³

Peak limitation : 4(II)

Remark : H,Y

Version : 02.04.2014

Limit value type (country of origin) : STEL (EC)

Limit value : 50 ppm / 246 mg/m³

Remark : H

Version : 08.06.2000

Limit value type (country of origin) : TWA (EC)

Limit value : 20 ppm / 98 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

Remark : H
Version : 08.06.2000

Biological limit values

BUTYL CELLOSOLVE ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Butoxy acetic acid / Urine (U) / At long term exposure: after several previous shifts
Limit value : 100 mg/l
Version : 31.03.2004

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL worker (local) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 246 mg/m³
Limit value type : DNEL worker (local) (POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 1 mg/m³
Limit value type : DNEL worker (systemic) (POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 1 mg/m³
Limit value type : DNEL worker (systemic) (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 6,22 mg/m³
Limit value type : DNEL worker (systemic) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 98 mg/m³
Limit value type : DNEL worker (systemic) (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 53,6 mg/m³
Limit value type : DNEL worker (systemic) ((1-METHYLETHYL)BENZENESULFONIC ACID, SODIUM SALT ; CAS No. : 15763-76-5)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 53,6 mg/m³
Limit value type : DNEL worker (systemic) ((1-METHYLETHYL)BENZENESULFONIC ACID, SODIUM SALT ; CAS No. : 15763-76-5)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 7,6 mg/kg
Limit value type : DNEL worker (systemic) (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 7,6 mg/kg
Limit value type : DNEL worker (systemic) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 663 mg/m³
Limit value type : DNEL worker (systemic) (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

Limit value :	1,49 mg/kg
Limit value type :	DNEL worker (systemic) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route :	Dermal
Exposure frequency :	Long-term (repeated)
Limit value :	75 mg/kg
Limit value type :	DNEL worker (systemic) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route :	Dermal
Exposure frequency :	Short-term (acute)
Limit value :	89 mg/kg

8.2 Exposure controls

Personal protection equipment

Eye/face protection



Wear suitable safety goggles in case of splash.

Suitable eye protection
EN 166.

Skin protection

Hand protection



Wear protective gloves in case of longer lasting skin contact.

Suitable gloves type : EN 374.

Suitable material : NBR (Nitrile rubber)

Breakthrough time (maximum wearing time) : 480 min.

Thickness of the glove material : 0.4 mm

Remark : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Combination filtering device (EN 14387)

Type : A

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General health and safety measures

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : green

Odour : characteristic

Safety relevant basis data

Solidifying point :	(1013 hPa)	ca.	0	°C
Initial boiling point and boiling range :	(1013 hPa)	ca.	97	°C
Flash point :			not relevant	
Lower explosion limit :			not relevant	
Upper explosion limit :			not relevant	
Vapour pressure :	(50 °C)		not relevant	
Density :	(20 °C)	ca.	1,03	g/cm ³
pH :		ca.	13	
Maximum VOC content (EC) :			5	Wt %
Maximum VOC content (Switzerland) :			5	Wt %

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Under normal pressure: distillation without decomposition.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Aluminium Zinc

10.6 Hazardous decomposition products

Sulphur oxides Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route :	Oral
Species :	Rat
Effective dose :	1250 - 1490 mg/kg
Method :	OECD 401
Parameter :	LD50 (FATTY ALCOHOL ALCOXYLATE, POLYMER)
Exposure route :	Oral

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

Species : Rat
Effective dose : > 2000 mg/kg
Acute dermal toxicity
Parameter : ATEmix calculated
Exposure route : Dermal
Effective dose : > 2000 mg/kg
Parameter : LD50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Dermal
Species : Rabbit
Effective dose : 841 mg/kg
Method : OECD 402
Acute inhalation toxicity
Parameter : ATEmix calculated
Exposure route : Inhalation
Effective dose : > 20 mg/l
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 2 - 20 mg/l
Exposure time : 4 h

11.2 Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

11.3 Other adverse effects

Has degreasing effect on the skin. Frequently or prolonged contact with skin may cause dermal irritation.

11.4 Additional information

Preparation not tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Species : Cyprinus carpio (Common Carp)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : > 100 mg/l
Exposure time : 96 h
Parameter : LC50 ((1-METHYLETHYL)BENZENESULFONIC ACID, SODIUM SALT ; CAS No. : 15763-76-5)
Species : Cyprinus carpio (Common Carp)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : > 100 mg/kg
Exposure time : 96 h
Parameter : LC50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Species : Fish
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 2320 mg/l
Exposure time : 96 h
Parameter : LC50 (POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3)
Species : Fish
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 80 mg/l
Exposure time : 96 h
Parameter : Acute (short-term) fish toxicity (ALCOHOLS, C10-C12, ETHOXYLATED, PROPOXYLATED ; CAS No. : 68154-97-2)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

Species : Brachydanio rerio (zebra-fish)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : > 1 - 10 mg/l
Exposure time : 96 h
Method : OECD 203
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Species : Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 1474 mg/l
Exposure time : 96 h
Method : OECD 203
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 1815 mg/l
Exposure time : 24 h
Method : DIN 38412 / part 11
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Chronic (long-term) daphnia toxicity
Effective dose : 297 mg/l
Exposure time : 21 d
Method : OECD 211

Acute (short-term) daphnia toxicity

Parameter : EC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : > 100 mg/l
Exposure time : 48 h
Parameter : EC50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 1700 mg/l
Exposure time : 48 h
Method : OECD 202
Parameter : EC50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
Species : Scenedesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : 207 mg/l
Exposure time : 72 h
Method : DIN 38412 / part 9
Parameter : EC50 (ALCOHOLS, C10-C12, ETHOXYLATED, PROPOXYLATED ; CAS No. : 68154-97-2)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : > 1 - 10 mg/l
Exposure time : 48 h
Method : OECD 202

Chronic (long-term) daphnia toxicity

Parameter : NOEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Species : Brachydanio rerio (zebra-fish)
Evaluation parameter : Chronic (long-term) fish toxicity
Effective dose : > 100 mg/l
Exposure time : 21 d
Method : OECD 204
Parameter : NOEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Species : Daphnia magna (Big water flea)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
 Revision date : 21.08.2017
 Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

Evaluation parameter : Chronic (long-term) daphnia toxicity
 Effective dose : 100 mg/l
 Exposure time : 21 d
 Method : OECD 211
 Parameter : NOEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
 Species : Algae
 Effective dose : 286 mg/l
 Exposure time : 72 h
 Method : OECD 201

Acute (short-term) algae toxicity

Parameter : EC50 ((1-METHYLETHYL)BENZENESULFONIC ACID, SODIUM SALT ; CAS No. : 15763-76-5)
 Species : Daphnia magna (Big water flea)
 Evaluation parameter : Acute (short-term) daphnia toxicity
 Effective dose : > 100 mg/l
 Exposure time : 48 h
 Parameter : EC50 ((1-METHYLETHYL)BENZENESULFONIC ACID, SODIUM SALT ; CAS No. : 15763-76-5)
 Species : Desmodesmus subspicatus
 Evaluation parameter : Acute (short-term) algae toxicity
 Effective dose : > 100 mg/l
 Exposure time : 72 h
 Parameter : EC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
 Species : Desmodesmus subspicatus
 Evaluation parameter : Acute (short-term) algae toxicity
 Effective dose : > 100 mg/l
 Exposure time : 72 h
 Parameter : EC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
 Species : Algae
 Effective dose : 1840 mg/l
 Exposure time : 72 h
 Method : OECD 201
 Parameter : ErC50 (ALCOHOLS, C10-C12, ETHOXYLATED, PROPOXYLATED ; CAS No. : 68154-97-2)
 Species : Selenastrum capricornutum
 Evaluation parameter : Acute (short-term) algae toxicity
 Effective dose : > 1 - 10 mg/l
 Exposure time : 72 h

Bacteria toxicity

Parameter : EC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
 Species : Bacteria toxicity
 Effective dose : > 1000 mg/l
 Exposure time : 3 h
 Parameter : EC50 ((1-METHYLETHYL)BENZENESULFONIC ACID, SODIUM SALT ; CAS No. : 15763-76-5)
 Species : Bacteria toxicity
 Effective dose : > 1000 mg/l
 Parameter : EC50 (DISODIUM METASILICATE ; CAS No. : 6834-92-0)
 Species : Bacteria toxicity
 Effective dose : > 100 mg/l
 Exposure time : 3 h

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
 Inoculum : Biodegradation
 Effective dose : 88 %
 Exposure time : 20 d

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

Parameter :	Biodegradation (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Inoculum :	Biodegradation
Evaluation parameter :	Aerobic
Effective dose :	99,8 %
Exposure time :	28 d
Evaluation :	Readily biodegradable (according to OECD criteria).
Method :	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C
Parameter :	Biodegradation ((1-METHYLETHYL)BENZENESULFONIC ACID, SODIUM SALT ; CAS No. : 15763-76-5)
Inoculum :	Biodegradation
Evaluation parameter :	Aerobic
Effective dose :	99,8 %
Exposure time :	28 d
Evaluation :	Readily biodegradable (according to OECD criteria).
Method :	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C
Parameter :	Biodegradation (ALCOHOLS, C10-C12, ETHOXYLATED, PROPOXYLATED ; CAS No. : 68154-97-2)
Inoculum :	Biodegradation
Evaluation parameter :	Aerobic
Effective dose :	> 60 %
Exposure time :	28 d
Evaluation :	Readily biodegradable (according to OECD criteria).
Method :	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

After neutralisation, reduction in toxic effects is observed.

SECTION 13: Disposal considerations

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. List of proposed waste codes/waste designations in accordance with EWC

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

20 01 29* - detergents containing dangerous substances.

Waste code packaging

15 01 02 - plastic packaging.

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

14.1 UN number

No dangerous goods in sense of this transport regulation.

14.2 UN proper shipping name

No dangerous goods in sense of this transport regulation.

14.3 Transport hazard class(es)

No dangerous goods in sense of this transport regulation.

14.4 Packing group

No dangerous goods in sense of this transport regulation.

14.5 Environmental hazards

No dangerous goods in sense of this transport regulation.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

< 5 % non-ionic surfactants

< 5 % anionic surfactants

perfumes

National regulations

AT: Labelling according to Austrian regulations (Chemikaliengesetz/ChemV).

CH: Chemikalienverordnung (ChemV) and Chemikalien-Risikoreduktions-Verordnung (Chem RRV) are complied.

Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to VwVwS

Other regulations, restrictions and prohibition regulations

Betriebssicherheitsverordnung (BetrSichV)

No flammable liquid according to BetrSichV.

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)

AOX: adsorbierbare organisch gebundene Halogene

CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)

CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)

EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung

ECHA: Europäische Chemikalienagentur (European Chemicals Agency)

EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)

GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Floor Cleaner STRONG
Revision date : 21.08.2017
Print date : 12.09.2017

Version (Revision) : 4.0.0 (3.0.0)

IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)
ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)
IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)
RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le transport international ferroviaire de marchandises dangereuses)
TRGS: Technische Regel für den Umgang mit Gefahrstoffen
VbF: Verordnung über brennbare Flüssigkeiten
VOC: flüchtige organische Verbindung (volatile organic compound)
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

16.3 Key literature references and sources for data

DGUV: GESTIS-Stoffdatenbank
ECHA: Classification And Labelling Inventory
ECHA: Pre-registered Substances
ECHA: Registered Substances
EC_Safety Data Sheet of Suppliers
ESIS: European Chemical Substances Information System
GDL: Gefahrstoffdatenbank der Länder
UBA Rigoletto: Wassergefährdende Stoffe
Regulation (EC) No. 1907/2006 of the European Parliament and of the Council
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

16.4 Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.