

according to Regulation (EC) No 1907/2006

Chalk spray all colors

Revision date: 03.03.2021

Product code: SS-SP-KR-...-...

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Chalk spray all colors

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	Elried Markierungssysteme GmbH (Berasit)	
Street: Place:	Grünwalder Weg 28e D-82041 Oberhaching	
Telephone: e-mail:	089-613764-0 info@elried.de	Telefax:089-613764-64
Contact person: e-mail: Internet:	Verena Riedmaier v.riedmaier@elried.de www.elried.de	Telephone:089-613764-12
I.4. Emergency telephone	Poisoning emergency number Berlin, pl	none: +49(0)30/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Flammable gases: Flam. Gas 1A Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Extremely flammable gas. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol Danger

Signal word:

Pictograms:



Hazard statements

H220	Extremely flammable gas.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precautionary statem	ents

cautionary statements	S
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No



according to Regulation (EC) No 1907/2006

Chalk spray all colors

Revision date: 03.03.2021	Product code: SS-SP-KR	Page 2 of 9
	smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe mist/vapours/spray.	
P262	Do not get in eyes, on skin, or on clothing.	
P271	Use only outdoors or in a well-ventilated area.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P403	Store in a well-ventilated place.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P501	Dispose of contents/container to an appropriate recycling or disposal facility.	

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	GHS Classification		-		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	200-661-7	603-117-00-0			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336				
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve			1 - < 5 %	
	203-905-0	603-014-00-0			
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H312 H302 H315 H319				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink 1 glass of of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures



according to Regulation (EC) No 1907/2006

Chalk spray all colors

Revision date: 03.03.2021

Product code: SS-SP-KR-...-...

Page 3 of 9

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Extremely flammable gas. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

The product is intended for professional use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

Chalk spray all colors

Revision date: 03.03.2021

Product code: SS-SP-KR-...-...

Page 4 of 9

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol		Post shift

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	gaseous
pH-Value:	

not determined

Changes in the physical state



according to Regulation (EC) No 1907/2006

Product code: SS-SP-KR	Page 5 of 9
not determined	
not determined	
not applicable	
not applicable	
not determined	
not determined	
not determined	
not applicable	
not determined	
not determined	
not determined	
The study does not need to be conducted because the substance is known to be insoluble in water.	
not determined	
not determined	
not determined	
not determined	
	not determined not applicable not determined not determined not determined not determined not determined not determined the study does not need to be conducted because the substance is known to be insoluble in water.

10.1. Reactivity

Extremely flammable gas.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information



according to Regulation (EC) No 1907/2006

Chalk spray all colors

Revision date: 03.03.2021

Product code: SS-SP-KR-...-...

Page 6 of 9

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
111-76-2	2-butoxyethanol; ethylene	eglycol monobutyl ether;	butyl cellosolve			
	oral	LD50 470 mg/kg	Rat			
	dermal	ATE 1100 mg/kg				
	inhalation gas	ATE 4500 ppm				

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d] Species	Source	Method	
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve					
	Acute fish toxicity	LC50 1490 mg/l	96 h Lepomis macrochirus			

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	0,81 (25°C)

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.



according to Regulation (EC) No 1907/2006

Chalk spray all colors

Revision date: 03.03.2021

Product code: SS-SP-KR-...-...

Page 7 of 9

SECTION 14: Transport information

Land transport (ADR/RID)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
14.3. Transport hazard class(es):	2	
14.4. Packing group:	-	
Hazard label:	2.1	
Classification code:	5F	
Special Provisions:	190 327 344 625	
Limited quantity:	1L	
Excepted quantity:	E0 2	
Transport category: Tunnel restriction code:	D	
Inland waterways transport (ADN)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
14.3. Transport hazard class(es):	2	
14.4. Packing group:	-	
Hazard label:	2.1	
Classification code:	5F	
Special Provisions:	190 327 344 625 1 L	
Limited quantity: Excepted quantity:	EO	
Marine transport (IMDG)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
Special Provisions:	63, 190, 277, 327, 344, 381, 959	
Limited quantity:	1000 mL	
Excepted quantity: EmS:	E0 F-D, S-U	
Air transport (ICAO-TI/IATA-DGR)	. 2, 5-0	
<u>14.1. UN number:</u>	UN 1950	
<u>14.2. UN proper shipping name:</u>	AEROSOLS, FLAMMABLE	
<u>14.3. Transport hazard class(es):</u>	2.1	
<u></u>		

BERASIT	Safety D	ata Sheet			
part of eiried group	according to Regulati	on (EC) No 1907/2006			
Chalk spray all colors					
Revision date: 03.03.2021		, SS-SP-KR	Page 8 of 9		
14.4. Packing group:	-				
Hazard label:	2.1				
Special Provisions: Limited quantity Passenger:	A145 A167 A802 30 kg G				
Passenger LQ:	Y203				
Excepted quantity:	E0				
IATA-packing instructions - Passenger:		203			
IATA-max. quantity - Passenger:		75 kg			
IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:		203 150 kg			
14.6. Special precautions for user		150 Kg			
Warning: Flammable gases.					
14.7. Transport in bulk according to Annex I	l of Marpol and the II	<u> 3C Code</u>			
not applicable					
SECTION 15: Regulatory information					
15.1. Safety, health and environmental regul	ations/legislation sp	ecific for the substance or	mixture		
EU regulatory information					
Restrictions on use (REACH, annex XVII): Entry 28					
2010/75/EU (VOC):	47 %				
2004/42/EC (VOC):	47 %				
Information according to 2012/18/EU (SEVESO III):	P2 FLAMMABLE G	ASES			

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). 1 - slightly hazardous to water

15.2. Chemical safety assessment

Water hazard class (D):

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals UN: United Nations CAS: Chemical Abstracts Service DNEL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LC50: Lethal concentration, 50% LD50: Lethal loading, 50% EL50: Effect loading, 50%



according to Regulation (EC) No 1907/2006

Chalk spray all colors

Revision date: 03.03.2021

Product code: SS-SP-KR-...-...

Page 9 of 9

EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) IMDG: International Maritime Code for Dangerous Goods EmS: Emergency Schedules MFAG: Medical First Aid Guide IATA: International Air Transport Association ICAO: International Civil Aviation Organization MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Gas 1A; H220	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

	· · · · · · · · · · · · · · · · · · ·
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)