

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

FT 400

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**

**Sectors of use [SU]**

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
Industrial uses

**Products Category [PC]**

PC-CLN-2 - All-purpose (or multi-purpose) non-abrasive cleaners

### 1.3 Details of the supplier of the safety data sheet

**Supplier**

Bio-Circle Surface Technology GmbH

**Street :** Berensweg 200

**Postal code/City :** 33334 Gütersloh

**Telephone :** +49 5241 9443 0

**Telefax :** +49 5241 9443 44

**Information contact :** labor@bio-circle.de

### 1.4 Emergency telephone number

+49 5241 9443 51 during normal office hours  
(Monday to Thursday from 8 am to 4 pm and Friday from 8 am to 3 pm)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

None

### 2.2 Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Special rules for supplemental label elements for certain mixtures**

EUH210 Safety data sheet available on request.

### 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Hazardous ingredients**

1-METHOXY-2-PROPANOL ; REACH No. : 01-2119457435-35-XXXX ; EC No. : 203-539-1; CAS No. : 107-98-2

Weight fraction :  $\geq 10 - < 20$  %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336  
Substance with a common (EC) occupational exposure limit value.

ETHANOL ; REACH No. : 01-2119457610-43-XXXX ; EC No. : 200-578-6; CAS No. : 64-17-5

Weight fraction :  $\geq 5 - < 10$  %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319

Specific Conc. Limits : Eye Irrit. 2 ; H319: C  $\geq 50$  %

1-PROPOXY-2-PROPANOL ; REACH No. : 01-2119474443-37-XXXX ; EC No. : 216-372-4; CAS No. : 1569-01-3

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

Weight fraction :  $\geq 4 - < 5,5 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Eye Irrit. 2 ; H319

#### Further ingredients

3-METHOXYBUTAN-1-OL ; REACH No. : 01-2119548352-41-XXXX ; EC No. : 219-741-8; CAS No. : 2517-43-3

Weight fraction :  $\geq 1 - < 5 \%$

#### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

When in doubt or if symptoms are observed, get medical advice.

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest.

#### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

#### After eye contact

Protect uninjured eye. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

#### Following ingestion

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Extinguishing powder Carbon dioxide (CO<sub>2</sub>) Sand Nitrogen Extinguishing blanket

#### Unsuitable extinguishing media

Full water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO<sub>2</sub>) , Nitrogen oxides (NO<sub>x</sub>)

### 5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### 5.4 Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

Special danger of slipping by leaking/spilling product. Use personal protection equipment.

## 6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## 6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

## 6.4 Reference to other sections

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Keep container tightly closed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against : Frost .

#### Hints on joint storage

Storage class (TRGS 510) : 10

### 7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 100 ppm / 370 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 23.06.2022

Limit value type (country of origin) : STEL ( EC )  
Limit value : 150 ppm / 568 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 375 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

ETHANOL ; CAS No. : 64-17-5

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 380 mg/m<sup>3</sup>  
Peak limitation : 4(II)  
Remark : Y  
Version : 23.06.2022

#### Biological limit values

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : 1-methoxypropan-2-ol / Urine (U) / End of exposure or end of shift  
Limit value : 15 mg/l  
Version : 25.02.2022

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

## DNEL-/PNEC-values

### DNEL/DMEL

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	78 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	43,9 mg/m <sup>3</sup>
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	33 mg/kg bw/day
Limit value type :	DNEL worker (local and systemic)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	553,5 mg/m <sup>3</sup>
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	369 mg/m <sup>3</sup>
Limit value type :	DNEL worker (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	183 mg/kg bw/day

ETHANOL ; CAS No. : 64-17-5

Limit value type :	DNEL Consumer (local)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	950 mg/m <sup>3</sup>
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	87 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	206 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	114 mg/m <sup>3</sup>
Limit value type :	DNEL worker (local)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	1900 mg/m <sup>3</sup>
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	380 mg/m <sup>3</sup>
Limit value type :	DNEL worker (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	343 mg/kg bw/day

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 11 mg/kg bw/day  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 36 mg/kg bw/day  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 38 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 263 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 82,5 mg/kg bw/day

**PNEC**

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2  
Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 10 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 100 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 1 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Limit value : 52,3 mg/kg dw  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 5,2 mg/kg dw  
Limit value type : PNEC (Soil)  
Limit value : 4,59 mg/kg dw  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 100 mg/l  
1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3  
Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,1 mg/l

**ETHANOL ; CAS No. : 64-17-5**

Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,96 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 2,75 mg/l

**1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3**

Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 1 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,01 mg/l

**ETHANOL ; CAS No. : 64-17-5**

Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,79 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Limit value : 3,6 mg/kg dw

**1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

Limit value type : PNEC (Sediment, freshwater)  
Limit value : 0,386 mg/kg dw  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 0,0386 mg/kg dw  
ETHANOL ; CAS No. : 64-17-5  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 2,9 mg/kg dw  
Limit value type : PNEC (Soil)  
Limit value : 0,63 mg/kg dw  
1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3  
Limit value type : PNEC (Soil)  
Limit value : 0,0185 mg/kg dw  
ETHANOL ; CAS No. : 64-17-5  
Limit value type : PNEC (Secondary poisoning)  
Limit value : 380 - 720 mg/kg food  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 580 mg/l  
1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 4 mg/l

## 8.2 Exposure controls

### Personal protection equipment

#### Eye/face protection



Wear suitable safety goggles in case of splash.

#### Suitable eye protection

EN 166.

#### Skin protection

##### Hand protection



**Suitable gloves type** : EN 374.

**Suitable material** : NBR (Nitrile rubber)

**Breakthrough time** : 480 min.

**Thickness of the glove material** : 0.4 mm

**Remark** : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

#### Suitable respiratory protection apparatus

Combination filtering device

Type : A

#### Remark

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

## General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

## 8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state : Liquid

Colour : colourless

#### Odour

like: Ether

#### Safety characteristics

Solidifying point :	( 1013 hPa )		-25,5	°C	
Initial boiling point and boiling range :	( 1013 hPa )		80	°C	
Flash point :		approx.	49	°C	DIN EN ISO 13736
Auto-ignition temperature :	( ETHANOL )		363	°C	Literature value
Flammability :			flammable		
Lower explosion limit :	( ETHANOL )		3,5	Vol-%	Literature value
Upper explosion limit :	( ETHANOL )		15	Vol-%	Literature value
Vapour pressure :	( 20 °C )	<	30	hPa	Calculated
Density :	( 20 °C )	approx.	0,98	g/cm <sup>3</sup>	
Solvent separation test :	( 20 °C )		not applicable		
Water solubility :	( 20 °C )		completely miscible		
pH :	( 20 °C )		11,4		
Relative vapour density :	( 20 °C )		not determined		
Maximum VOC content (EC) :			32,8	Weight-%	
Maximum VOC content (Switzerland) :			33,1	Weight-%	
Taxable VOC content (Switzerland) :			25,9	Weight-%	

### 9.2 Other information

Not sustaining combustion. UN Test L.2: Sustained combustibility test

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non-reactive under normal use conditions.

### 10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Do not spray on naked flames or any incandescent material.

### 10.5 Incompatible materials

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

No information available.

## 10.6 Hazardous decomposition products

No known hazardous decomposition products.  
Decomposition products in case of fire: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Acute oral toxicity

Parameter : ATEmix  
Exposure route : Oral  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 3739 - 4277 mg/kg  
Parameter : LD50 ( ETHANOL ; CAS No. : 64-17-5 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 10470 mg/kg  
Method : OECD 401  
Parameter : LD50 ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 2490 - 4330 mg/kg  
Method : OECD 401

##### Acute dermal toxicity

Parameter : ATEmix  
Exposure route : Dermal  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg  
Method : Regulation (EC) No. 440/2008, Annex B.3  
Parameter : LD50 ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 3775 - 4330 mg/kg  
Method : OECD 402

##### Acute inhalation toxicity

Parameter : ATEmix  
Exposure route : Inhalation  
Effective dose : > 20 mg/m<sup>3</sup>  
Parameter : LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Inhalation  
Species : Mouse  
Effective dose : 6000 - 7000 ppm  
Exposure time : 6 h  
Method : OECD 403  
Parameter : LC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 115,9 - 133,8 mg/l

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

Exposure time : 4 h  
Method : OECD 403  
Parameter : LC50 ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 1725 ppm  
Exposure time : 6 h  
Method : OECD 403

## Corrosion

### Skin corrosion/irritation

No further relevant information available.

### Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Rabbit  
Result : Causes serious eye irritation  
Method : OECD 405  
Parameter : Serious eye damage/eye irritation ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )  
Species : Rabbit  
Method : OECD 405

### Assessment/classification

Based on available data, the classification criteria are not met.

## Respiratory or skin sensitisation

### Skin sensitisation

No further relevant information available.

### Sensitisation to the respiratory tract

No further relevant information available.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

### Carcinogenicity

No further relevant information available.

### Germ cell mutagenicity

No further relevant information available.

### Reproductive toxicity

No further relevant information available.

## STOT-single exposure

### STOT SE 3

Parameter : STOT SE 3 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Inhalative  
Result : May cause drowsiness or dizziness.

### Narcotic effects

#### Assessment/classification

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

No further relevant information available.

## Aspiration hazard

No further relevant information available.

## 11.2 Information on other hazards

### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

### Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

### Other adverse effects

May be absorbed through the skin. Frequently or prolonged contact with skin may cause dermal irritation.

### Additional information

Preparation not tested. The statement is derived from the properties of the single components.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter : LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )

Species : Pimephales promelas (fathead minnow)

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 20800 mg/l

Exposure time : 96 h

Parameter : LC50 ( ETHANOL ; CAS No. : 64-17-5 )

Species : Pimephales promelas (fathead minnow)

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 14,2 g/l

Exposure time : 96 h

Parameter : LC50 ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )

Species : Oncorhynchus mykiss (Rainbow trout)

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : > 100 mg/l

Exposure time : 96 h

Parameter : LC50 ( 3-METHOXYBUTAN-1-OL ; CAS No. : 2517-43-3 )

Species : Oncorhynchus mykiss (Rainbow trout)

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : > 100 mg/l

Exposure time : 96 h

Method : OECD 203

##### Chronic (long-term) fish toxicity

Parameter : NOEC ( ETHANOL ; CAS No. : 64-17-5 )

Species : Danio rerio (zebrafish)

Evaluation parameter : Chronic (long-term) fish toxicity

Effective dose : 250 mg/l

Exposure time : 120 h

Method : OECD 212

##### Acute (short-term) toxicity to crustacea

Parameter : EC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )

Species : Daphnia magna (Big water flea)

Evaluation parameter : Acute (short-term) daphnia toxicity

Effective dose : 21100 - 25900 mg/l

Exposure time : 48 h

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )

Species : Daphnia

Evaluation parameter : Acute (short-term) toxicity to crustacea

Effective dose : 5012 mg/l

Exposure time : 48 h

Parameter : EC50 ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )

Species : Daphnia magna (Big water flea)

Evaluation parameter : Acute (short-term) daphnia toxicity

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

Effective dose : > 100 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( 3-METHOXYBUTAN-1-OL ; CAS No. : 2517-43-3 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : > 100 mg/l  
Exposure time : 48 h  
Method : OECD 202

**Chronic (long-term) toxicity to aquatic invertebrate**

Parameter : NOEC ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Daphnia  
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate  
Effective dose : 9,6 mg/l  
Exposure time : 10 D

**Acute (short-term) toxicity to algae and cyanobacteria**

Parameter : EC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Acute (short-term) algae toxicity  
Effective dose : > 1000 mg/l  
Exposure time : 7 D

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Chlorella vulgaris  
Evaluation parameter : Inhibition of growth rate  
Effective dose : 675 mg/l  
Exposure time : 4 D  
Method : OECD 201

Parameter : EC50 ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Acute (short-term) algae toxicity  
Effective dose : 5583 mg/l  
Exposure time : 48 h

Parameter : EC50 ( 3-METHOXYBUTAN-1-OL ; CAS No. : 2517-43-3 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : > 100 mg/l  
Exposure time : 72 h  
Method : OECD 201

**Toxicity to microorganisms**

Parameter : EC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Pseudomonas putida  
Evaluation parameter : Bacteria toxicity  
Effective dose : > 10000 mg/l  
Exposure time : 17 h  
Method : DIN 38412 / part 8

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Bacteria toxicity  
Effective dose : 5,8 g/l  
Exposure time : 4 h

Parameter : EC50 ( 3-METHOXYBUTAN-1-OL ; CAS No. : 2517-43-3 )  
Species : Toxicity to microorganisms  
Effective dose : > 1000 mg/l  
Exposure time : 3 h  
Method : OECD 209

Parameter : EC10 ( 3-METHOXYBUTAN-1-OL ; CAS No. : 2517-43-3 )  
Species : Toxicity to microorganisms  
Effective dose : 155 mg/l

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

Exposure time : 3 h  
Method : OECD 209

## 12.2 Persistence and degradability

According to the recipe, contains no AOX. The surfactant contained in this mixture complies with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

### Abiotic degradation

#### Abiotic degradation (Air)

Parameter : Half-life time ( ETHANOL ; CAS No. : 64-17-5 )  
Degradation rate : 38 h

### Biodegradation

Parameter : DOC reduction ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )

Inoculum : Biodegradation

Evaluation parameter : Aerobic

Degradation rate : 96 %

Test duration : 28 D

Evaluation : Readily biodegradable (according to OECD criteria).

Method : OECD 301E

Parameter : Biodegradation ( ETHANOL ; CAS No. : 64-17-5 )

Inoculum : Biodegradation

Evaluation parameter : Aerobic

Degradation rate : approx. 84 %

Test duration : 20 D

Evaluation : Readily biodegradable (according to OECD criteria).

Parameter : DOC reduction ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )

Inoculum : Biodegradation

Evaluation parameter : Aerobic

Degradation rate : 91,5 %

Test duration : 28 D

Evaluation : Readily biodegradable (according to OECD criteria).

Method : OECD 301A

Parameter : BOD (% of COD) ( 3-METHOXYBUTAN-1-OL ; CAS No. : 2517-43-3 )

Inoculum : Degree of elimination

Evaluation parameter : Aerobic

Degradation rate : 80 %

Test duration : 28 D

Method : OECD 301F

## 12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )

Value : 3,16 L/kg

Parameter : Partition coefficient n-octanol/water (log value) ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )

Value : 0,37

20 °C

Parameter : Log KOW ( 1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3 )

Value : 0,621

20 °C

Parameter : Log KOW ( ETHANOL ; CAS No. : 64-17-5 )

Value : -0,77 - -0,3

20 °C

No indication of bioaccumulation potential.

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

## 12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7 Other adverse effects

No information available.

## 12.8 Additional ecotoxicological information

After neutralisation, reduction in toxic effects is observed.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Directive 2008/98/EC (Waste Framework Directive)

##### Before intended use

##### Waste codes/waste designations according to EWC/AVV

20 01 30 (Detergents other than those mentioned in 20 01 29)

##### Other disposal recommendations

Dispose of waste according to applicable legislation. Dispose of contents/container to an appropriate recycling or disposal facility. Contaminated packages must be completely emptied and can be re-used following proper cleaning (Water (with cleaning agent)). Handle contaminated packages in the same way as the substance itself.

### 13.2 Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## SECTION 14: Transport information

### 14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

### 14.4 Packing group

No dangerous good in sense of these transport regulations.

### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

### 14.6 Special precautions for user

None

### 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

Use restriction according to REACH annex XVII, no. : 30, 40, 55, 75

##### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

mothers.

## Other regulations (EU)

### Labelling for contents according to regulation (EC) No. 648/2004

< 5 % non-ionic surfactants

## National regulations

### Störfallverordnung (12. BlmschV)

Category : P5b FLAMMABLE LIQUIDS

### Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

Weight fraction (Number 5.2.4. III) : < 1 %

### Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

## 15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

01. Unique Formula Identifier · 01. Relevant identified uses · 12. Bioaccumulative potential

### 16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)

AOX: adsorbierbare organisch gebundene Halogene

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)

CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)

EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung

ECHA: Europäische Chemikalienagentur (European Chemicals Agency)

EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)

GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)

IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)

ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)

IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)

RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le transport international ferroviaire de marchandises dangereuses)

TRGS: Technische Regel für den Umgang mit Gefahrstoffen

VbF: Verordnung über brennbare Flüssigkeiten

VOC: flüchtige organische Verbindung (volatile organic compound)

VVEA: Verordnung über die Vermeidung und die Entsorgung von Abfällen

VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe

WGK: Wassergefährdungsklasse

### 16.3 Key literature references and sources for data

DGUV: GESTIS-Stoffdatenbank

ECHA: Classification And Labelling Inventory

ECHA: Pre-registered Substances

ECHA: Registered Substances

EC\_Safety Data Sheet of Suppliers

ESIS: European Chemical Substances Information System

GDL: Gefahrstoffdatenbank der Länder

UBA Rigoletto: Wassergefährdende Stoffe

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council

|-> COMMISSION REGULATION (EU) 2020/878 of 18 June 2020

Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FT 400  
Revision date : 02.10.2025  
Print date : 02.10.2025

Version (Revision) : 3.0.2 (3.0.1)

---

**16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

**16.5 Relevant H- and EUH-phrases (Number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**16.6 Training advice**

None

**16.7 Additional information**

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---