

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT
 Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015,
 6301952015, 6301953015, 6301954015, 6301957015




Version: 5 Revision: 08/10/2021




Previous revision: 08/07/2021

Date of printing: 08/10/2021

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING


1.1	PRODUCT IDENTIFIER: UFI: TRR5-80RJ-U00J-DS86	AMPERE - TRAFFIC ANTISLIP FLOOR PAINT Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015
1.2	RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: <u>Intended uses (main technical functions):</u> One-pack performance coating, solvent-borne. <u>Uses advised against:</u> This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as 'Intended or identified uses'. <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Not restricted.	[X] Industrial [X] Professional [] Consumers
1.3	DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: A.M.P.E.R.E. SYSTEM 3 rue Antoine Balard - Z.I. du Vert Galant 95310 Saint-Ouen-l'Aumône – France Tél: + 33 1 34 64 72 72 / Fax: +33 1 30 37 55 17 <u>E-mail address of the person responsible for the Safety Data Sheet:</u> e-mail : fds@ampersystem.com	
1.4	EMERGENCY TELEPHONE NUMBER: 0344 892 0111  National Poisons Information Service (NPIS) - In England, Wales or Scotland: dial 111 - In N Ireland: contact your local GP or pharmacist during normal hours.	

SECTION 2 : HAZARDS IDENTIFICATION

2.1	CLASSIFICATION OF THE SUBSTANCE OR MIXTURE : Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture. <u>Classification in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP):</u> WARNING: Flam. Liq. 3:H226 Eye Irrit. 2:H319 Lact.:H362 STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 Aquatic Acute 1:H400 Aquatic Chronic 1:H410 EUH066					
	Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects
	<u>Physicochemical:</u> 	Flam. Liq. 3:H226 Eye Irrit. 2:H319 Lact.:H362	c) c) c)	Cat.3 Cat.2 -	- Eyes -	- Irritation -
	<u>Human health:</u> 	STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 Aquatic Acute 1:H400 Aquatic Chronic 1:H410	c) c) c) c)	Cat.3 Cat.3 Cat.1 -	Inhalation Inhalation CNS -	Irritation Narcosis -
	<u>Environment:</u> 	EUH066	c)	-	Skin	Dryness, Cracking

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

2.2	LABEL ELEMENTS:  <u>Hazard statements:</u> H226 H362 H319 H335 H336 H410 EUH066 <u>Precautionary statements:</u> P102 P210 P337+P313 P280F	This product is labelled with the signal word WARNING in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP) Flammable liquid and vapour. May cause harm to breast-fed children. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Very toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. If eye irritation persists: Get medical attention. Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection.
-----	--	--

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT

Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015







P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P273-P391-P501a Avoid release to the environment. Collect spillage. Dispose of contents/container in accordance with local regulations.
[Supplementary statements:](#)
 EUH208 Contains tall-oil fatty acids oleylamide. May produce an allergic reaction.
 EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
[Substances that contribute to classification:](#)
 Hydrocarbons C9 aromatics
 Xylene (mixture of isomers)

- 2.3 [OTHER HAZARDS:](#)
 Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:
[Other physicochemical hazards:](#) Vapours may form with air a mixture potentially flammable or explosive.
[Other adverse human health effects:](#) No other relevant adverse effects are known.
[Other negative environmental effects:](#) Does not contain substances that fulfil the PBT/vPvB criteria.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 [SUBSTANCES:](#)
 Not applicable (mixture).

- 3.2 [MIXTURES:](#)
 This product is a mixture.
[Chemical description:](#)
 Mixture of pigments, resins and additives in organic solvents.
[HAZARDOUS INGREDIENTS:](#)
 Substances taking part in a percentage higher than the exemption limit:

30 < 40 %		Hydrocarbons C9 aromatics (CAS: 64742-95-6) , List No. 918-668-5 REACH: 01-2119455851-35 CLP: Danger: Flam. Liq. 3:H226 STOT SE (irrit.) 3:H335 STOT SE (narco sis) 3:H336 Asp. Tox. 1:H304 Aquatic Chronic 2:H411 EUH066	Autoclassified < REACH
5 < 10 %		Reaction mass of ethylbenzene and m-xylene and p-xylene List No. 905-562-9 REACH: 01-2119488216-32 CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (inh.) 4:H332 Acute Tox. (skin) 4:H312 Skin Irrit. 2:H315 Eye Irrit. 2:H319 STOT SE (irrit.) 3:H335 STOTRE 2 H373i Asp. Tox. 1:H304	Autoclassified < REACH
2,5 < 5 %		Chlorinated paraffins C14-C17 CAS: 85535-85-9 , EC: 287-477-0 CLP: Warning: Lact.:H362 Aquatic Acute 1:H400 (M=100) Aquatic Chronic 1:H410 (M=10) EUH066	Index No. 602-095-00-X < ATP01
< 0,025 %		Tall-oil fatty acids oleylamide CAS: 85711-55-3 , EC: 288-315-1 CLP: Danger: Eye Dam. 1:H318 Skin Sens. 1A:H317 STOT RE 2:H373o	Autoclassified < REACH

[Impurities:](#)
 Does not contain other components or impurities which will influence the classification of the product.

[Stabilizers:](#)
 None

[Reference to other sections:](#)
 For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

[SUBSTANCES OF VERY HIGH CONCERN \(SVHC\):](#)

List updated by ECHA on 08/07/2021.

[Substances SVHC subject to authorisation, included in Annex XIV of Regulation \(EC\) no. 1907/2006:](#)

None

[Substances SVHC candidate to be included in Annex XIV of Regulation \(EC\) no. 1907/2006:](#)

Chlorinated paraffins C14-C17 , PBT (Article 57d) , vPvB (Article 57e) , Resolution: ECHA/D(2021)4569-DC.

[PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPvB SUBSTANCES:](#)

Does not contain substances that fulfil the PBT/vPvB criteria.

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT
 Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015



SECTION 4 : FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST-AID MEASURES:



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
<u>Inhalation:</u> 	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Inhalation produces irritation to mucus, coughing and breathlessness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
<u>Skin:</u>	Prolonged contact may cause skin dryness.	Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.
<u>Eyes:</u> 	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
<u>Ingestion:</u>	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient.

Antidotes and contraindications: Specific antidote not known.

SECTION 5 : FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

Extinguishing powder or CO₂. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide, halogenated compounds, hydrochloric acid. Exposure to combustion or decomposition products may be a hazard to health.

5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

Hazchem (Emergency Action) Code: ■ 3Y

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.

6.2 ENVIRONMENTAL PRECAUTIONS:

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). Clean preferably with a biodegradable detergent. Avoid use of solvents. Keep the remains in a dosed container.

6.4 REFERENCE TO OTHER SECTIONS:

For contact information in case of emergency, see section 1.
 For information on safe handling, see section 7.
 For exposure controls and personal protection measures, see section 8.
 For waste disposal, follow the recommendations in section 13.

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT
 Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015,
 6301952015, 6301953015, 6301954015, 6301957015



SECTION 7 : HANDLING AND STORAGE

7.1	<p>PRECAUTIONS FOR SAFE HANDLING: Comply with the existing legislation on health and safety at work. <u>General recommendations:</u> Avoid any type of leakage or escape. Keep the container tightly closed. <u>Recommendations for the prevention of fire and explosion risks:</u> Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.</p> <table border="0"> <tr> <td>- Flash point</td> <td>:</td> <td>42* °C</td> <td>CLP 2.6.4.3.</td> </tr> <tr> <td>- Autoignition temperature</td> <td>:</td> <td>447* °C</td> <td></td> </tr> <tr> <td>- Lower/upper flammability or explosive limits</td> <td>:</td> <td>0.8* - 7.2* % Volume 25°C</td> <td></td> </tr> </table> <p><u>Recommendations for the prevention of toxicological risks:</u> Do not eat, drink or smoke in application and drying areas. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8. <u>Recommendations for the prevention of environmental contamination:</u> Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instruction indicated in section 6.</p>	- Flash point	:	42* °C	CLP 2.6.4.3.	- Autoignition temperature	:	447* °C		- Lower/upper flammability or explosive limits	:	0.8* - 7.2* % Volume 25°C	
- Flash point	:	42* °C	CLP 2.6.4.3.										
- Autoignition temperature	:	447* °C											
- Lower/upper flammability or explosive limits	:	0.8* - 7.2* % Volume 25°C											
7.2	<p>CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.</p> <table border="0"> <tr> <td><u>Class of storage</u></td> <td>:</td> <td>According to current legislation.</td> </tr> <tr> <td><u>Maximum storage period</u></td> <td>:</td> <td>24. months</td> </tr> <tr> <td><u>Temperature interval</u></td> <td>:</td> <td>min: 5. °C, max: 40. °C (recommended).</td> </tr> </table> <p><u>Incompatible materials:</u> Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. <u>Type of packaging:</u> According to current legislation. <u>Limit quantity (Seveso III): Directive 2012/18/EU:</u> - Named dangerous substances/mixtures: None - Hazard categories and lower-/upperthreshold quantities in tonnes (t): - Physical hazards: Flammable liquid and vapour (P5c) (5000t/50000t). - Health hazards: Not applicable - Environmental hazards: Very toxic to aquatic life with long lasting effects (E1) (100t/200t). - Other hazards: Not applicable. - Threshold quantity for the application of lower-tier requirements: 100 tons - Threshold quantity for the application of upper-tier requirements: 200 tons - Remarks: The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.</p>	<u>Class of storage</u>	:	According to current legislation.	<u>Maximum storage period</u>	:	24. months	<u>Temperature interval</u>	:	min: 5. °C, max: 40. °C (recommended).			
<u>Class of storage</u>	:	According to current legislation.											
<u>Maximum storage period</u>	:	24. months											
<u>Temperature interval</u>	:	min: 5. °C, max: 40. °C (recommended).											
7.3	<p>SPECIFIC END USES: For the use of this product particular recommendations apart from that already indicated are not available.</p>												

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT

Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015



SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (WEL)

EH40/2005 WELs (United Kingdom) 2018	Year	WEL-TWA		WEL-STEL		Remarks
		ppm	mg/m ³	ppm	mg/m ³	
Hydrocarbons C9 aromatics		50.	290.	-	-	Recommended TLV (AGCIH)
Xylene (mixture of isomers)	1996	100.	434.	150.	651.	

WEL - Workplace Exposure Limit, TWA - Time Weighted Average (8 hours), STEL - Short Term Exposure Limit (15 min).

BMGV - Biological monitoring guidance value. BMGVs are non-statutory and any biological monitoring undertaken in association with a guidance value needs to be conducted on a voluntary basis (ie with the fully informed consent of all concerned).

BIOLOGICAL LIMIT VALUES:

Biological monitoring can be a very useful complementary technique to air monitoring when air sampling techniques alone may not give a reliable indication of exposure. Biological monitoring is the measurement and assessment of hazardous substances or their metabolites in tissues, secretions, excreta or expired air, or any combination of these, in exposed workers. Measurements reflect absorption of a substance by all routes. Biological monitoring may be particularly useful in circumstances where there is likely to be significant skin absorption and/or gastrointestinal tract uptake following ingestion, where control of exposure depends on respiratory protective equipment, where there is a reasonably well-defined relationship between biological monitoring and effect, or where it gives information on accumulated dose and target organ body burden which is related to toxicity.

This preparation contains the following substances that have established a biological limit value:

- Xylenes: Biological determinant: methylhippuric acids in urine, BEI: 1.5 g/g creatinine, Sampling time: end of shift (2).

(2) When the end of the exposition not coincide with the end of the working day, the sample will be taken as soon as possible after the real exposition ceases.

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers:

- Systemic effects, acute and chronic:

Hydrocarbons C9 aromatics Reaction mass of ethylbenzene and m-xylene and p-xylene	DNEL Inhalation		DNEL Cutaneous		DNEL Oral	
	mg/m ³		mg/kg bw/d		mg/kg bw/d	
	- (a)	150. (c)	- (a)	25.0 (c)	- (a)	- (c)
	289. (a)	77.0 (c)	s/r (a)	180. (c)	- (a)	- (c)

Derived no-effect level, workers:

- Local effects, acute and chronic:

Hydrocarbons C9 aromatics Reaction mass of ethylbenzene and m-xylene and p-xylene	DNEL Inhalation		DNEL Cutaneous		DNEL Eyes	
	mg/m ³		mg/cm ²		mg/cm ²	
	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
	289. (a)	s/r (c)	s/r (a)	s/r (c)	- (a)	- (c)

Derived no-effect level, general population:

Not applicable (product for professional or industrial use).

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT

Code : 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015

PREDICTED NO-EFFECT CONCENTRATION (PNEC):Predicted no-effect concentration, aquatic organisms:

- Fresh water, marine water and intermittent release:
Hydrocarbons C9 aromatics
Reaction mass of ethylbenzene and m-xylene and p-xylene

PNEC Fresh water

mg/l
uvcb
0.327

PNEC Marine

mg/l
uvcb
0.327

PNEC Intermittent

mg/l
uvcb
0.327

- Wastewater treatment plants (STP) and sediments in fresh- and marine water:

Hydrocarbons C9 aromatics
Reaction mass of ethylbenzene and m-xylene and p-xylene

PNEC STP

mg/l
uvcb
6.58

PNEC Sediments

mg/kg dw/d
uvcb
12.5

PNEC Sediments

mg/kg dw/d
uvcb
12.5

Predicted no-effect concentration, terrestrial organisms:

- Air, soil and effects for predators and humans:
Hydrocarbons C9 aromatics
Reaction mass of ethylbenzene and m-xylene and p-xylene

PNEC Air

mg/m³
uvcb
-

PNEC Soil

mg/kg dw/d
uvcb
2.31

PNEC Oral

mg/kg dw/d
uvcb
-

(-) - PNEC not available (without data of registration REACH).

uvcb - The substance has an unknown or variable composition (UVCB). The conventional methods to derive the PNEC are not appropriate and it is not possible to identify a single PNEC representative for these substances, and therefore not used in calculations for risk assessment.

8.2

EXPOSURE CONTROLS:ENGINEERING MEASURES:

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

Protection of respiratory system: Avoid the inhalation of vapours.

Protection of eyes and face: It is recommended to install water taps, sources or eyewash bottles with clean water close to the working area.

Protection of hands and skin: It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: Regulation (EU) No. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

Mask:

A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.

Safety goggles:

Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.

Face shield:

No.

Gloves:

Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. The gloves should be immediately replaced when any sign of degradation is noted.

Boots:

No.

Apron:

No.

Clothing:

Advisable.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: Prevent contamination of soil.

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT

Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015



Spills in water: Do not allow to escape into drains, sewers or water courses.

- **Water Management Act:** This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

- **VOC (product ready for use*):** It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: PAINTS AND VARNISHES (defined in the Directive 2004/42/EC, Annex I.1): Emission subcategory i) One-pack performance coating, solvent-borne. VOC (product ready for use*) (produto pronto a usar.) : 454.8* g/l* (VOC max. 500. g/l* starting from 01.01.2010).

- **VOC (industrial installations):** If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents : 37.2% Weight , VOC (supply) : 37.2% Weight , VOC : 33.3% C (expressed as carbon) , Molecular weight (average) : 120.9 , Number C atoms (average) : 9.0.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

Appearance

- Physical state : Liquid.
- Colour : White.
- Odour : Characteristic.

pH-value

- pH : Not applicable (non-aqueous media).

Change of state

- Melting point : Not applicable (mixture).

Initial boiling point

- Initial boiling point : 137.2* °C at 760 mmHg

Density

- Relative density : 1.223* at 20/4°C Relative water

StabilityViscosity:Volatility:

- Vapour pressure : 2.5* mmHg at 20°C
- Vapour pressure : 2.1* kPa at 50°C

Solubility(ies)

- Partition coefficient: n-octanol/water : Not applicable (mixture).

Flammability:

- Flash point : 42* °C CLP 2.6.4.3.
- Lower/upper flammability or explosive limits : 0.8* - 7.2* % Volume 25°C
- Autoignition temperature : 447* °C

Explosive properties:

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

9.2 OTHER INFORMATION:

- Solids : 62.5 % Weight
- VOC (supply) : 37.2 % Weight
- VOC (supply) : 454.8 g/l

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

SECTION 10 : STABILITY AND REACTIVITY

10.1 REACTIVITY:

Corrosivity to metals: It is not corrosive to metals.

Pyrophorical properties: It is not pyrophoric.

10.2 CHEMICAL STABILITY:

Stable under recommended storage and handling conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Possible dangerous reaction with oxidizing agents, acids, metals.

10.4 CONDITIONS TO AVOID:

Heat: Keep away from sources of heat.

Light: If possible, avoid direct contact with sunlight.

Air: The product is not affected by exposure to air, but should not be left the containers open.

Humidity: Avoid extreme humidity conditions.

Pressure: Not relevant.

Shock: The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT
 Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015



10.5 **INCOMPATIBLE MATERIALS:**
 Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

10.6 **HAZARDOUS DECOMPOSITION PRODUCTS:**
 As consequence of thermal decomposition, hazardous products may be produced: hydrochloric acid, halogenated compounds.

SECTION 11 : TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

Dose and lethal concentrations

for individual ingredients :

Hydrocarbons C9 aromatics
 Xylene (mixture of isomers)
 Chlorinated paraffins C14-C17
 Tall-oil fatty acids oleylamide

LD50 (OECD 401)

mg/kg bw oral

3592. Rat
 4300. Rat
 26100. Rat
 > 2000. Rat

LD50 (OECD 402)

mg/kg bw cutaneous

3160. Rabbit
 1700. Rat
 13500. Rabbit

LC50 (OECD 403)

mg/m³-4h inhalation

> 6193. Rat
 > 22080. Rat
 > 20000. Rat

Estimates of acute toxicity (ATE)

for individual ingredients :

Xylene (mixture of isomers)

ATE

mg/kg bw oral

-

ATE

mg/kg bw cutaneous

1100.*

ATE

mg/m³-4h inhalation

11000.* Vapours

(*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

(-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

No observed adverse effect level

Not available

Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE : Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
Inhalation: Not classified	ATE > 20000 mg/m ³	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Skin: Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Eyes: Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Ingestion: Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
Respiratory corrosion/irritation: 	Respiratory tract 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 1.2.6. 3.8.3.4.
Skin corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.2.3.3.
Serious eye damage/irritation: 	Eyes 	Cat.2	IRRITANT: Causes serious eye irritation.	GHS/CLP 3.3.3.3.
Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
Skin sensitisation: Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT
 Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015

**ASPIRATION HAZARD:**

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Aspiration hazard:</u> Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Respiratory:</u> 	SE	Respiratory tract 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 3.8.3.4.
<u>Cutaneous:</u>	RE	Skin 	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.	GHS/CLP 1.2.4.
<u>Neurological:</u> 	SE	CNS 	Cat.3	NARCOSIS: May cause drowsiness or dizziness if inhaled.	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

Carcinogenic effects: It is not considered as a carcinogenic product.

Genotoxicity: It is not considered as a mutagenic product.

Toxicity for reproduction: Does not harm fertility. Does not harm the unborn child.

Effects via lactation: May cause harm to breast-fed children.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.

Short-term exposure: Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat and other effects may be the same as described in the exposure to vapours.

Long-term or repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:

Dermal absorption: Not available.

Basic toxicokinetics: Not available.

ADDITIONAL INFORMATION:

Not available.

SECTION 12 : ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).

12.1	<u>TOXICITY:</u>	<u>LC50 (OECD 203)</u>	<u>EC50 (OECD 202)</u>	<u>EC50 (OECD 201)</u>
		mg/l-96hours	mg/l-48hours	mg/l-72hours
	<u>Acute toxicity in aquatic environment for individual ingredients:</u> Hydrocarbons C9 aromatics Xylene (mixture of isomers) Chlorinated paraffins C14-C17 Tall-oil fatty acids oleylamide	> 9.2 Fishes > 14. Fishes 5000. Fishes > 100. Fishes	> 3.2 Daphnia > 16. Daphnia 0.0059 Daphnia > 15. Daphnia	> 2.9 Algae > 10. Algae > 3.2 Algae > 7.0 Algae
	<u>No observed effect concentration</u> Chlorinated paraffins C14-C17	<u>NOEC (OECD 210)</u> mg/l-28days 0.13 Fishes	<u>NOEC (OECD 211)</u> mg/l-21days 0.0040 Daphnia	<u>NOEC (OECD 201)</u> mg/l-72hours
	<u>Lowest observed effect concentration</u> Chlorinated paraffins C14-C17	<u>LOEC (OECD 210)</u> mg/l-28days	<u>LOEC (OECD 211)</u> mg/l-21days 0.018 Daphnia	<u>LOEC (OECD 201)</u> mg/l-72hours

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT
 Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015

**ASSESSMENT OF AQUATIC TOXICITY:**

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
<u>Acute aquatic toxicity:</u> 	Cat.1	VERY TOXIC: Very toxic to aquatic life.	GHS/CLP 4.1.3.5.5.3.
<u>Chronic aquatic toxicity:</u> 	Cat.1	VERY TOXIC: Very toxic to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

Not available.

<u>Aerobic biodegradation for individual ingredients:</u> Hydrocarbons C9 aromatics Xylene (mixture of isomers) Chlorinated paraffins C14-C17 Tall-oil fatty acids oleylamide	<u>DQO</u> mgO2/g	<u>%DBO/DQO</u> 5 days 14 days 28 days	<u>Biodegradability</u>
	3195.		Easy
	2620.	~ 52. ~ 81. ~ 88.	Easy
	~ 1500.		Not easy
		51. 72. 87.	Easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

12.3 BIOACCUMULATIVE POTENTIAL:

Not available.

<u>Bioaccumulation for individual ingredients:</u> Hydrocarbons C9 aromatics Xylene (mixture of isomers) Chlorinated paraffins C14-C17 Tall-oil fatty acids oleylamide	<u>log Pow</u>	<u>BCF</u> L/kg	<u>Potential</u>
	3.30	70. (calculated)	Low
	3.16	57. (calculated)	Low
	7.40	2152. (calculated)	High
	13.5	71. (calculated)	Low

12.4 MOBILITY IN SOIL:

Not available.

<u>Mobility for individual ingredients:</u> Hydrocarbons C9 aromatics Xylene (mixture of isomers) Chlorinated paraffins C14-C17 Tall-oil fatty acids oleylamide	<u>log Poc</u>	<u>Constant of Henry</u> Pa·m ³ /mol 20°C	<u>Potential</u>
	2.96	440. (calculated)	Low
	2.25	660. (calculated)	Low
	6.42		High
	8.16		Low

12.5 RESULTS OF PBT AND VPVB ASSESSMENT: Annex XIII of Regulation (EC) no. 1907/2006:

Does not contain substances that fulfil the PBT/vPvB criteria.

12.6 OTHER ADVERSE EFFECTS:Ozone depletion potential: Not available.Photochemical ozone creation potential: Not available.Earth global warming potential: In case of fire or incineration liberates CO₂.Endocrine disrupting potential: Not available.**SECTION 13 : DISPOSAL CONSIDERATIONS****13.1 WASTE TREATMENT METHODS: Directive 2008/98/EC~Regulation (EU) no. 1357/2014:**

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers: Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

Procedures for neutralising or destroying the product:

Controlled incineration in special facilities for chemical waste, in accordance with local regulations. Contains halogenated compounds: In the case of incineration, take all necessary measures in order to avoid production and emission of furanes and dioxines into the atmosphere above the legal limits allowed.

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT

Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015



SECTION 14 : TRANSPORT INFORMATION

14.1 **UN NUMBER:** 126314.2 **UN PROPER SHIPPING NAME:**
PAINT14.3 **TRANSPORT HAZARD CLASS(ES):**

Transport by road (ADR 2021) and
Transport by rail (RID 2021):

- Class: 3
 - Packing group: III
 - Classification code: F1
 - Tunnel restriction code: (D/E)
 - Transport category: 3, max. ADR 1.1.3.6. 1000 L
 - Limited quantities: 5 L (see total exemptions ADR 3.4)
 - Transport document: Consignment paper.
 - Instructions in writing: ADR 5.4.3.4



Transport by sea (IMDG 39-18):

- Class: 3
 - Packing group: III
 - Emergency Sheet (EmS): F-E,S_E
 - First Aid Guide (MFAG): 310,313
 - Marine pollutant: Yes.
 - Transport document: Shipping Bill of lading.



Transport by air (ICAO/IATA 2021):

- Class: 3
 - Packing group: III
 - Transport document: Air Bill of lading.



Transport by inland waterways (ADN):

Not available.

14.4 **PACKING GROUP:**

See section 14.3

14.5 **ENVIRONMENTAL HAZARDS:**

Classified as hazardous for the environment.

14.6 **SPECIAL PRECAUTIONS FOR USER:**

Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.

14.7 **ADDITIONAL INFORMATION:**

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.

Hazchem (Emergency Action) Code: ■ 3Y

SECTION 15 : REGULATORY INFORMATION

15.1 **EU SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC:**

The regulations applicable to this product generally are listed throughout this Safety Data Sheet.

Restrictions on manufacture, placing on market and use: See section 1.2

Tactile warning of danger: Not applicable (the classification criteria are not met).

Child safety protection: Not applicable (the classification criteria are not met).

VOC information on the label:

Contains VOC max. 455. g/l - The limit value 2004/42/CE-IIA cat. i) for the product ready for use is VOC max. 500. g/l (2010).

OTHER REGULATIONS:

Control of the risks inherent in major accidents (Seveso III): See section 7.2

Other local legislations:

The receiver should verify the possible existence of local regulations applicable to the chemical.

15.2 **CHEMICAL SAFETY ASSESSMENT:**

A chemical safety assessment has not been carried out for this mixture.

AMPERE - TRAFFIC ANTISLIP FLOOR PAINT

Code: 630195100, 6301952001, 6301953001, 6301954001, 6301957001, 6301959001, 6301951015, 6301952015, 6301953015, 6301954015, 6301957015



SECTION 16 : OTHER INFORMATION

TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:Hazard statements according the Regulation (EU) No. 1272/2008~2020/1182 (CLP), Annex III:

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H362 May cause harm to breast-fed children. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H373i May cause damage to organs through prolonged or repeated exposure if inhaled. H373o May cause damage to organs through prolonged or repeated exposure if swallowed.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES: See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Workplace Exposure Limits, (United Kingdom, 2018).
- European agreement on the international carriage of dangerous goods by road, (ADR 2021).
- International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LD50: Lethal dose, 50 percent.
- LC50: Lethal concentration, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangerous goods by road.
- RID: Regulations concerning the international transport of dangerous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.

HISTORIC:

Version: 4
Version: 5

Revision:

08/07/2021
08/10/2021

Changes since previous Safety Data Sheet:

Legislative, contextual, numerical, methodological and normative changes since the previous version of the present Safety Data Sheet are identified by a red-italic hash (#).

DISCLAIMER

The information contained in this sheet comes from reliable sources. It has been drawn up based on our knowledge at the time of the most recent update, as indicated. This information is intended as an aid to the user and should not be considered as a guarantee.

Conditions or methods of handling, storage, use or disposal of the product are outside our control, and we may not be held responsible for any loss, damage or expenses incurred as a result of, or in connection with, the latter.

All substances or mixtures can present unknown dangers and must be used with caution. We cannot guarantee that all dangers have been set out in an exhaustive manner.

This sheet has been drawn up for, and must be used for, this product only. If the product is used as a component in another product, the information given with it may not be applicable.

This sheet does not under any circumstances exempt the user from complying with all laws, regulations and administrative requirements related to the product, health and safety, and the protection of human health and the environment.

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.