

**AMPERE - TRAFFIC FLOOR PAINT**  
 Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015



Version: 5 Revision: 07/10/2021

Previous revision: 07/07/2021

Date of printing: 07/10/2021

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

1.1	<b>PRODUCT IDENTIFIER:</b> UFI: 6NR5-S025-J002-QEP4	AMPERE - TRAFFIC FLOOR PAINT Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015
1.2	<b>RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:</b> <u>Intended uses (main technical functions):</u> One-pack performance coating, solvent-borne. <u>Uses advised against:</u> This product is not recommended for any use or sector of use industrial, professional or consume other than those previously listed as 'Intended or identified uses'. <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Not restricted.	[X] Industrial [X] Professional [ ] Consumers
1.3	<b>DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:</b> A.M.P.E.R.E. SYSTEM 3 rue Antoine Balard - Z.I. du Vert Galant 95310 Saint-Ouen-l'Aumône - FRANCE Tél: + 33 1 34 64 72 72 / Fax: +33 1 30 37 55 17 <u>E-mail address of the person responsible for the safety data sheet:</u> e-mail: fds@ampersystem.com	
1.4	<b>EMERGENCY TELEPHONE NUMBER:</b> +386 41 650 500	

**SECTION 2 : HAZARDS IDENTIFICATION**

2.1	<b>CLASSIFICATION OF THE SUBSTANCE OR MIXTURE :</b> Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture. <u>Classification in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP):</u> ATENCIÓN: Flam. Liq. 3:H226   Skin Irrit. 2:H315   Eye Irrit. 2:H319   Lact.:H362   STOT SE (irrit.) 3:H335   STOT SE (narcosis) 3:H336   Aquatic Acute 1:H400   Aquatic Chronic 1:H410   EUH066					
	<b>Danger class</b>	<b>Classification of the mixture</b>	<b>Cat.</b>	<b>Routes of exposure</b>	<b>Target organs</b>	<b>Effects</b>
	<u>Physicochemical:</u> 	Flam. Liq. 3:H226 Skin Irrit. 2:H315 Eye Irrit. 2:H319	c) c) c)	Cat.3 Cat.2 Cat.2	- Skin Eyes	- Irritation Irritation
	<u>Human health:</u> 	Lact.:H362 STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 Aquatic Acute 1:H400	c) c) c) c)	- Inhalation Inhalation	- Respiratory system CNS	- Irritation Narcosis
	<u>Environment:</u> 	Aquatic Chronic 1:H410 EUH066	c) c)	Cat.1 -	- Skin	- Dryness, Cracking
	Full text of hazard statements mentioned is indicated in section 16.					
	Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.					

2.2	<b>LABEL ELEMENTS:</b> 	This product is labelled with the signal word ATENCIÓN in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP)
	<u>Hazard statements:</u> H226 H362 H319 H335 H315 H336 H410	Vnetljiva tekočina in hlapi. Lahko škoduje dojenim otrokom. Povzročča hudo draženje oči. Lahko povzročči draženje dihalnih poti. Povzročča draženje kože. Lahko povzročči zaspanost ali omotico. Zelo strupeno za vodne organizme, z dolgotrajnimi učinki.
	<u>Precautionary statements:</u> P102 P210 P280F  P303+P361+P353-P352-P312 P305+P351+P338	Hraniti zunaj dosega otrok. Hraniti ločeno od vročine, vročih površin, isker, odprtega ognja in drugih virov vžiga. Kajenje prepovedano. Nositi zaščitne rokavice, zaščitno obleko in zaščito za oči. Ob nezadostnem prezračevanju nositi opremo za zaščito dihal. PRI STIKU S KOŽO (ali lasmi): Takoj sleči vsa kontaminirana oblačila. Kožo izprati z vodo ali prho. Umiti z veliko mila in vode. Ob slabšem počutju pokličite CENTER ZA ZASTRUPITVE ali zdravnika. PRI STIKU Z OČMI: Previdno izpirati z vodo nekaj minut. Odstranite kontaktne leče, če jih imate in če to lahko storite brez težav. Nadaljujte z izpiranjem.

## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015



P273-P391-P501a Preprečiti sproščanje v okolje. Prestreči razlito tekočino. Odstraniti vsebino/posodo v skladu z lokalnimi predpisi.  
 Supplementary statements:  
 EUH208 Vsebuje tall-oil fatty acids oleylamide. Lahko povzroči alergijski odziv.  
 EUH211 Pozor! Pri razprševanju lahko nastanejo nevarne vdihljive kapljice. Ne vdihavajte razpršila ali meglic.  
 Substances that contribute to classification:  
 Hydrocarbons C9 aromatics  
 Xylene (mixture of isomers)

- 2.3 **OTHER HAZARDS:**  
 Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:  
**Other physicochemical hazards:** Vapours may form with air a mixture potentially flammable or explosive.  
**Other adverse human health effects:** No other relevant adverse effects are known.  
**Other negative environmental effects:** Does not contain substances that fulfil the PBT criteria.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.1 **SUBSTANCES:**  
 Not applicable (mixture).

3.2 **MIXTURES:**  
 This product is a mixture.  
**Chemical description:**  
 Mixture of pigments, resins and additives in organic solvents.

**HAZARDOUS INGREDIENTS:**  
 Substances taking part in a percentage higher than the exemption limit:

30 < 40 % 	<b>Hydrocarbons C9 aromatics</b> (CAS: 64742-95-6) , List No. 918-668-5 REACH: 01-2119455851-35 CLP: Peligro: Flam. Liq. 3:H226   STOT SE (irrit.) 3:H335   STOTSE (narcosis) 3:H336   Asp. Tox. 1:H304   Aquatic Chronic 2:H411   EUH066	Autoclassified < REACH
5 < 10 % 	<b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b> List No. 905-562-9 REACH: 01-2119488216-32 CLP: Peligro: Flam. Liq. 3:H226   Acute Tox. (in h.) 4:H332   Acute Tox. (skin) 4:H312   Skin Irrit. 2:H315   Eye Irrit. 2:H319   STOT SE (irrit.) 3:H335   STOTRE 2 H373   Asp. Tox. 1:H304	Autoclassified < REACH
2,5 < 5 % 	<b>Chlorinated paraffins C14-C17</b> CAS: 85535-85-9 , EC: 287-477-0 CLP: Atención: Lact.:H362   Aquatic Acute 1:H400 (M=100)   Aquatic Chronic 1:H410 (M=10)   EUH066	Index No. 602-095-00-X < ATP01
1 < 2 % 	<b>Bután-1-ol</b> CAS: 71-36-3 , EC: 200-751-6 REACH: 01-2119484630-38 CLP: Peligro: Flam. Liq. 3:H226   Acute Tox. (oral) 4:H302   Skin Irrit. 2 H315   Eye Dam. 1:H318   STOT SE (irrit.) 3:H335   STOTSE (narcosis) 3:H336	Index No. 603-004-00-6 < REACH / ATP01
< 0,025 % 	<b>Tall-oil fatty acids oleylamide</b> CAS: 85711-55-3 , EC: 288-315-1 CLP: Peligro: Eye Dam. 1:H318   Skin Sens. 1A:H317   STOT RE 2:H373o	Autoclassified < REACH

**Impurities:**  
 Does not contain other components of impurities which will influence the classification of the product.

**Stabilizers:**  
 None

**Reference to other sections:**  
 For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

**SUBSTANCES OF VERY HIGH CONCERN (SVHC):**

# List updated by ECHA on 08/07/2021.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

None

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

# Chlorinated paraffins C14-C17 , PBT (Article 57d), vPvB (Article 57e), Resolution: ECHA/D(2021)4569-DC.

**PERSISTENT, BIOACCUMULABLE AND TOXIC (PBT), OR VERY PERSISTENT AND VERY BIOACCUMULABLE (VPvB) SUBSTANCES:**

Does not contain substances that fulfill the PBT/vPvB criteria.

## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015



## SECTION 4 : FIRST AID MEASURES

## 4.1 DESCRIPTION OF FIRST-AID MEASURES:



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
<u>Inhalation:</u> 	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Inhalation produces irritation to mucus, coughing and breathlessness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
<u>Skin:</u> 	Skin contact causes redness. In case of prolonged contact, the skin may become dry.	Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.
<u>Eyes:</u> 	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
<u>Ingestion:</u>	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

## 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

## 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient.

Antidotes and contraindications: Specific antidote not known.

## SECTION 5 : FIRE-FIGHTING MEASURES

## 5.1 EXTINGUISHING MEDIA:

Extinguishing powder or CO<sub>2</sub>. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

## 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Fire can produce a dense black smoke. Como consecuencia de la combustión o de la descomposición térmica, pueden formarse productos peligrosos: monóxido de carbono, dióxido de carbono, compuestos halogenados, ácido clorhídrico. Exposure to combustion or decomposition products may be a hazard to health.

## 5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or not used, combat fire from a sheltered position or at a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

## 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with the product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.

## 6.2 ENVIRONMENTAL PRECAUTIONS:

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

## 6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). Clean preferably with a biodegradable detergent. Avoid use of solvents. Keep the remains in a dosed container.

## 6.4 REFERENCE TO OTHER SECTIONS:

For contact information in case of emergency, see section 1.  
For information on safe handling, see section 7.  
For exposure controls and personal protection measures, see section 8.  
For waste disposal, follow the recommendations in section 13.

## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015



## SECTION 7 : HANDLING AND STORAGE

7.1	<p><b>PRECAUTIONS FOR SAFE HANDLING:</b> Comply with the existing legislation on health and safety at work.</p> <p><b>General recommendations:</b> Avoid any type of leakage or escape. Keep the container tightly closed.</p> <p><b>Recommendations for the prevention of fire and explosion risks:</b> Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.</p> <table border="0"> <tr> <td>- Temperatura de inflamación</td> <td>:</td> <td>42* žC</td> <td>CLP 2.6.4.3.</td> </tr> <tr> <td>- Temperatura autoignición</td> <td>:</td> <td>444* žC</td> <td></td> </tr> <tr> <td>- Lower/upper flammability or explosive limits</td> <td>:</td> <td>0.8* - 7.2* % Volumen 25žC</td> <td></td> </tr> </table> <p><b>Recommendations for the prevention of toxicological risks:</b> Do not eat, drink or smoke in application and drying areas. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.</p> <p><b>Recommendations for the prevention of environmental contamination:</b> Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.</p>	- Temperatura de inflamación	:	42* žC	CLP 2.6.4.3.	- Temperatura autoignición	:	444* žC		- Lower/upper flammability or explosive limits	:	0.8* - 7.2* % Volumen 25žC	
- Temperatura de inflamación	:	42* žC	CLP 2.6.4.3.										
- Temperatura autoignición	:	444* žC											
- Lower/upper flammability or explosive limits	:	0.8* - 7.2* % Volumen 25žC											
7.2	<p><b>CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</b> Prevent unauthorized access. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.</p> <table border="0"> <tr> <td><b>Class of store</b></td> <td>:</td> <td>According to current legislation.</td> </tr> <tr> <td><b>Maximum storage period</b></td> <td>:</td> <td>24. meses</td> </tr> <tr> <td><b>Temperature interval</b></td> <td>:</td> <td>min: 5. žC, max: 40. žC (recommended).</td> </tr> </table> <p><b>Incompatible materials:</b> Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.</p> <p><b>Type of packaging:</b> According to current legislation.</p> <p><b>Limit quantity (Seveso III): Directive 2012/18/EU:</b></p> <ul style="list-style-type: none"> <li>- Named dangerous substances/mixtures: None</li> <li>- Hazard categories and lower-/upperthreshold quantities in tonnes (t):</li> <li>- Physical hazards: Vnetljiva tekočina in hlapi (P5c) (5000t/50000t).</li> <li>- Health hazards: Not applicable</li> <li>- Environmental hazards: Zelo strupeno za vodne organizme, z dolgotrajnimi učinki (E1) (100t/200t).</li> <li>- Other hazards: Not applicable.</li> <li>- Threshold quantity for the application of lower-tier requirements: 100 tons</li> <li>- Threshold quantity for the application of upper-tier requirements: 200 tons</li> <li>- Remarks:</li> </ul> <p>The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.</p>	<b>Class of store</b>	:	According to current legislation.	<b>Maximum storage period</b>	:	24. meses	<b>Temperature interval</b>	:	min: 5. žC, max: 40. žC (recommended).			
<b>Class of store</b>	:	According to current legislation.											
<b>Maximum storage period</b>	:	24. meses											
<b>Temperature interval</b>	:	min: 5. žC, max: 40. žC (recommended).											
7.3	<p><b>SPECIFIC END USES:</b> For the use of this product do not exist particular recommendations apart from that already indicated.</p>												

## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015



## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2020	Year	TLV-TWA		TLV-STEL		Observations
		ppm	mg/m3	ppm	mg/m3	
Hydrocarbons C9 aromatics		50.	290.	-	-	Recomendado
Xylene (mixture of isomers)	1996	100.	434.	150.	651.	A4 , BEI
Bután-1-ol	1998	20.	61.	-	-	

TLV - Threshold Limit Value ,TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

A4 - Non classified as carcinogenic in humans.

BEI - Biological exposure index (biological monitoring).

BIOLOGICAL LIMIT VALUES:

Not available

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers:

- Systemic effects, acute and chronic:

Hydrocarbons C9 aromatics

Reaction mass of ethylbenzene and m-xylene and p-xylene

Bután-1-ol

DNEL Inhalation

mg/m3

- (a) 150. (c)

289. (a) 77.0 (c)

- (a) 310. (c)

DNEL Cutaneous

mg/kg bw/d

- (a) 25.0 (c)

s/r (a) 180. (c)

- (a) - (c)

DNEL Oral

mg/kg bw/d

- (a) - (c)

- (a) - (c)

- (a) - (c)

Derived no-effect level, workers:

- Local effects, acute and chronic:

Hydrocarbons C9 aromatics

Reaction mass of ethylbenzene and m-xylene and p-xylene

Bután-1-ol

DNEL Inhalation

mg/m3

- (a) - (c)

289. (a) s/r (c)

- (a) 310. (c)

DNEL Cutaneous

mg/cm2

- (a) - (c)

s/r (a) s/r (c)

- (a) - (c)

DNEL Eyes

mg/cm2

- (a) - (c)

- (a) - (c)

- (a) - (c)

Derived no-effect level, general population:

Not applicable (product for professional or industrial use).

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).

## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015

PREDICTED NO-EFFECT CONCENTRATION (PNEC):Predicted no-effect concentration, aquatic organisms:

- Fresh water, marine water and intermitent release:  
Hydrocarbons C9 aromatics  
Reaction mass of ethylbenzene and m-xylene and p-xylene  
Bután-1-ol

PNEC Fresh water  
mg/l

uvcb  
0.327  
0.0820

PNEC Marine  
mg/l

uvcb  
0.327  
0.00820

PNEC Intermittent  
mg/l

uvcb  
0.327  
2.25

- Wastewater treatment plants (STP) and sediments in fresh- and marine water:

Hydrocarbons C9 aromatics  
Reaction mass of ethylbenzene and m-xylene and p-xylene  
Bután-1-ol

PNEC STP  
mg/l

uvcb  
6.58  
2476.

PNEC Sediments  
mg/kg dw/d

uvcb  
12.5  
0.178

PNEC Sediments  
mg/kg dw/d

uvcb  
12.5  
0.0178

Predicted no-effect concentration, terrestrial organisms:

- Air, soil and effects for predators and humans:  
Hydrocarbons C9 aromatics  
Reaction mass of ethylbenzene and m-xylene and p-xylene  
Bután-1-ol

PNEC Air  
mg/m3

uvcb  
-  
-

PNEC Soil  
mg/kg dw/d

uvcb  
2.31  
0.0150

PNEC Oral  
mg/kg dw/d

uvcb  
-  
-

(-) - PNEC not available (without data of registration REACH).

uvcb - The substance has an unknown or variable composition (UVCB). The conventional methods to derive the PNEC are not appropriate and it is not possible to identify a single PNEC representative for these substances, and therefore not used in calculations for risk assessment.

8.2

EXPOSURE CONTROLS:ENGINEERING MEASURES:

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

Protection of respiratory system: Avoid the inhalation of vapours.

Protection of eyes and face: It is recommended to dispose of water taps, sources or eyewash bottles with clean water close to the working area.

Protection of hands and skin: It is recommended to dispose of water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCUPATIONAL EXPOSURE CONTROLS: Regulation (EC) No. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding EC marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

Mask:

A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Classe 1: low capacity up to 1000 ppm, Classe 2: medium capacity up to 5000 ppm, Classe 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.

Goggles:

Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.

Face shield:

No.

Gloves:

Gloves resistant against chemicals (EN374). When it can be a repeated or prolonged contact, it is recommended to use gloves with a protection level 5 or higher, with a breakthrough time >240 min. When you only expects a short contact, it is recommended to use gloves with a protection level 2 or higher, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, we must have in mind the manual of instructions from manufacturers of gloves. The gloves should be immediately replaced when any sign of degradation is noted.

Boots:

No.

Apron:

No.

Clothing:

Advisable.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: Prevent contamination of soil.

## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015



**Spills in water:** Do not allow to escape into drains, sewers or water courses.

- **Water Management Act:** This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

**Emissions to the atmosphere:** Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

- **VOC (product ready for use\*):** It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: PAINTS AND VARNISHES (defined in the Directive 2004/42/EC, Annex I.1): Emission subcategory i) One-pack performance coating, solvent-borne. COV (producto listo al uso\*) ( producto pronto a usar. ) : 496.2\* g/l\* (VOC max. 500. g/l\* starting from 01.01.2010).

- **VOC (industrial installations):** If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Disolventes : 43.7% Peso , COV (suministro) : 43.7% Peso , COV : 39.1% C (expressed as carbon) , Peso molecular (promedio) : 120.9 , Número átomos C (promedio) : 9.0.

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

**Appearance**

- Forma física : Liquid.
- Color : Blanco.
- Olor : Característico.

**pH-value**

- pH : Not applicable (medio no acuoso).

**Change of state**

- Temperatura de fusión : Not applicable (mixture).

- Temperatura de ebullición : 117.7\* ºC a 760 mmHg

**Density**

- Densidad relativa : 1.135\* a 20/4ºC (agua=1)

**Stability****Viscosity:****Volatility:**

- Presión de vapor : 2.6\* mmHg a 20ºC
- Presión de vapor : 2.2\* kPa a 50ºC

**Solubility(ies)**

- Partition coefficient: n-octanol/water : Not applicable (mixture).

**Flammability:**

- Temperatura de inflamación : 42\* ºC
- Lower/upper flammability or explosive limits : 0.8\* - 7.2\* % Volumen 25ºC
- Temperatura autoignición : 444\* ºC

**Explosive properties:**

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

**Oxidizing properties:**

Not classified as oxidizing product.

\*Estimated values based on the substances composing the mixture.

## 9.2 OTHER INFORMATION:

- No volátiles : 55.9 % Peso
- COV (suministro) : 43.7 % Peso
- COV (suministro) : 496.2 g/l

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the technical data sheet of the same. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

## SECTION 10 : STABILITY AND REACTIVITY

## 10.1 REACTIVITY:

**Corrosivity to metals:** It is not corrosive to metals.

**Pyrophorical properties:** It is not pyrophoric.

## 10.2 CHEMICAL STABILITY:

Stable under recommended storage and handling conditions.

## 10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Posible reacción peligrosa con agentes oxidantes, ácidos, metales.

## 10.4 CONDITIONS TO AVOID:

**Heat:** Keep away from sources of heat.

**Light:** If possible, avoid direct contact with sunlight.

**Air:** The product is not affected by exposure to air, but should not be left the containers open.

**Humidity:** Avoid extreme humidity conditions.

**Pressure:** Not relevant.

**Shock:** The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.

## 10.5 INCOMPATIBLE MATERIALS:

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

## 10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

Como consecuencia de la descomposición térmica, pueden formarse productos peligrosos: ácido clorhídrico, compuestos halogenados.



## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015



## SECTION 11 : TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:ACUTE TOXICITY:Dose and lethal concentrations for individual ingredients :

Hydrocarbons C9 aromatics  
Xylene (mixture of isomers)  
Chlorinated paraffins C14-C17  
Bután-1-ol  
Tall-oil fatty acids oleylamide

DL50 (OECD 401)

mg/kg bw oral  
3592. Rat  
4300. Rat  
26100. Rat  
790. Rat  
> 2000. Rat

DL50 (OECD 402)

mg/kg bw cutaneous  
3160. Rabbit  
1700. Rat  
13500. Rabbit  
3430. Rabbit

CL50 (OECD 403)

mg/m3.4h inhalation  
> 6193. Rat  
> 22080. Rat  
> 20000. Rat  
> 24665. Rat

Estimates of acute toxicity (ATE)

for individual ingredients :  
Xylene (mixture of isomers)  
Bután-1-ol

ATE

mg/kg bw oral  
-  
790.

ATE

mg/kg bw cutaneous  
1100.\*  
-

ATE

mg/m3.4h inhalation  
11000.\* Vapours  
-

(\*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

(-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

No observed adverse effect level

Not available

Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE :Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Merilo
<u>Inhalation:</u> Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
<u>Skin:</u> Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
<u>Eyes:</u> Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
<u>Ingestion:</u> Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Razvrstitev zmesi na podlagi sestavin zmesi (metoda dodajanja).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Merilo
<u>Respiratory corrosion/irritation:</u> 	Respiratory system 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 1.2.6. 3.8.3.4.
<u>Skin corrosion/irritation:</u> 	Skin 	Cat.2	IRRITANT: Causes skin irritation.	GHS/CLP 3.2.3.3.
<u>Serious eye damage/irritation:</u> 	Eyes 	Cat.2	IRRITANT: Causes serious eye irritation.	GHS/CLP 3.3.3.3.
<u>Respiratory sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
<u>Skin sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Razvrstitev zmesi, kadar so na voljo podatki za vse ali le nekatere sestavine zmesi.

GHS/CLP 3.3.3.3: Razvrstitev zmesi, kadar so na voljo podatki za vse ali le nekatere sestavine zmesi.

GHS/CLP 3.4.3.3: Razvrstitev zmesi, kadar so na voljo podatki za vse ali le nekatere sestavine zmesi.

GHS/CLP 3.8.3.4: Razvrstitev zmesi, kadar so na voljo podatki za vse ali le nekatere sestavine zmesi.



## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015

ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Merilo
<u>Aspiration hazard:</u> Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Razvrstitev zmesi, kadar so na voljo podatki za vse ali le nekatere sestavine zmesi.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Merilo
<u>Respiratory:</u> 	SE	Respiratory system 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 3.8.3.4.
<u>Cutaneous:</u>	RE	Skin 	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.	GHS/CLP 1.2.4.
<u>Neurological:</u> 	SE	CNS 	Cat.3	NARCOSIS: May cause drowsiness or dizziness if inhaled.	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Razvrstitev zmesi, kadar so na voljo podatki za vse ali le nekatere sestavine zmesi.

CMR EFFECTS:Carcinogenic effects: Is not considered as a carcinogenic product.Genotoxicity: Is not considered as a mutagenic product.Toxicity for reproduction: Do not harm fertility. Do not harm the fetus developing.Effects via lactation: May cause harm to breast-fed children.DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.Short-term exposure: Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours.Long-term or repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:Dermal absorption: Not available.Basic toxicokinetics: Not available.ADDITIONAL INFORMATION:

Not available.

**SECTION 12 : ECOLOGICAL INFORMATION**

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).

12.1	<u>TOXICITY:</u>	<u>CL50 (OECD 203)</u>	<u>CE50 (OECD 202)</u>	<u>CE50 (OECD 201)</u>
		mg/l 96hours	mg/l 48hours	mg/l 72hours
	<u>Acute toxicity in aquatic environment for individual ingredients:</u> Hydrocarbons C9 aromatics Xylene (mixture of isomers) Chlorinated paraffins C14-C17 Bután-1-ol Tall-oil fatty acids oleylamide	> 9.2 Fishes > 14. Fishes 5000. Fishes 1376. Fishes > 100. Fishes	> 3.2 Daphnia > 16. Daphnia 0.0059 Daphnia 1328. Daphnia > 15. Daphnia	> 2.9 Algae > 10. Algae > 3.2 Algae 500. Algae > 7.0 Algae
	<u>No observed effect concentration</u> Chlorinated paraffins C14-C17 Bután-1-ol	<u>NOEC (OECD 210)</u> mg/l 28days 0.13 Fishes	<u>NOEC (OECD 211)</u> mg/l 21days 0.0040 Daphnia 4.1 Daphnia	<u>NOEC (OECD 201)</u> mg/l 72hours
	<u>Lowest observed effect concentration</u> Chlorinated paraffins C14-C17	<u>LOEC (OECD 210)</u> mg/l 28days	<u>LOEC (OECD 211)</u> mg/l 21days 0.018 Daphnia	<u>LOEC (OECD 201)</u> mg/l 72hours

## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Merilo
<u>Acute aquatic toxicity:</u> 	Cat.1	VERY TOXIC: Very toxic to aquatic life.	GHS/CLP 4.1.3.5.5.3.
<u>Chronic aquatic toxicity:</u> 	Cat.1	VERY TOXIC: Very toxic to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

Not available.

Biodegradación aeróbica for individual ingredients:	DQO mgO <sub>2</sub> /g	%DBO/DQO 5 days 14 days 28 days	Biodegradabilidad
Hydrocarbons C9 aromatics	3195.		Fácil
Xylene (mixture of isomers)	2620.	~ 52. ~ 81. ~ 88.	Fácil
Chlorinated paraffins C14-C17	~ 1500.		No fácil
Bután-1-ol	2590.	~ 68. ~ 92. ~ 99.	Fácil
Tall-oil fatty acids oleylamide		51. 72. 87.	Fácil

Opomba: Podatki o biorazgradljivosti ustrezajo povprečju podatkov iz različnih bibliografskih virov.

12.3 BIOACCUMULATIVE POTENTIAL:

Not available.

Bioaccumulation for individual ingredients:	log Pow	BCF L/kg	Potential
Hydrocarbons C9 aromatics	3.30	70. (calculated)	Low
Xylene (mixture of isomers)	3.16	57. (calculated)	Low
Chlorinated paraffins C14-C17	7.40	2152. (calculated)	High
Bután-1-ol	0.880	3.2 (calculated)	No bioaccumulable
Tall-oil fatty acids oleylamide	13.5	71. (calculated)	Low

12.4 MOBILITY IN SOIL:

Not available.

Movilidad for individual ingredients:	log Poc	Constante de Henry Pa·m <sup>3</sup> /mol 20°C	Potential
Hydrocarbons C9 aromatics	2.96	440. (calculated)	Low
Xylene (mixture of isomers)	2.25	660. (calculated)	Low
Chlorinated paraffins C14-C17	6.42		High
Bután-1-ol	0.390	0.63 (calculated)	No bioaccumulable
Tall-oil fatty acids oleylamide	8.16		Low

12.5 RESULTS OF PBT AND VPVB ASSESSMENT: Annex XIII of Regulation (EC) no. 1907/2006:

Does not contain substances that fulfill the PBT/vPvB criteria.

12.6 OTHER ADVERSE EFFECTS:Ozone depletion potential: Not available.Photochemical ozone creation potential: Not available.Earth global warming potential: In case of fire or incineration liberates CO<sub>2</sub>.Endocrine disrupting potential: Not available.**SECTION 13 : DISPOSAL CONSIDERATIONS**13.1 WASTE TREATMENT METHODS: Directive 2008/98/EC~Regulation (EU) no. 1357/2014:

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose of at an authorised waste collection point. Waste should be handled and disposed of in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers: Directive 94/62/EC~2015/720/EC, Decision 2000/532/EC~2014/955/EC:

Emptied containers and packaging should be disposed of in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

Procedures for neutralising or destroying the product:

Controlled incineration in special facilities for chemical waste, but in accordance with local regulations. Contains halogenated compounds: In the case of incineration, take all necessary measures in order to avoid production and emission of furanes and dioxines into the atmosphere above the legal limits allowed.

## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015



## SECTION 14 : TRANSPORT INFORMATION

14.1 UN NUMBER: 126314.2 UN PROPER SHIPPING NAME:  
PAINT14.3 TRANSPORT HAZARD CLASS(ES):

Transport by road (ADR 2021) and  
Transport by rail (RID 2021):

- Class: 3  
 - Packaging group: III  
 - Classification code: F1  
 - Tunnel restriction code: (D/E)  
 - Transport category: 3, max. ADR 1.1.3.6. 1000 L  
 - Limited quantities: 5 L (see total exemptions ADR 3.4)  
 - Transport document: Consignment paper.  
 - Instructions in writing: ADR 5.4.3.4



Transport by sea (IMDG 39-18):

- Class: 3  
 - Packaging group: III  
 - Emergency Sheet (EmS): F-E,S\_E  
 - First Aid Guide (MFAG): 310,313  
 - Marine pollutant: Si.  
 - Transport document: Shipping Bill of lading.



Transport by air (ICAO/IATA 2021):

- Class: 3  
 - Packaging group: III  
 - Transport document: Air Bill of lading.



Transport by inland waterways (ADN):  
Not available.

14.4 PACKAGING GROUP:  
See section 14.314.5 ENVIRONMENTAL HAZARDS:  
Classified as hazardous for the environment.14.6 SPECIAL PRECAUTIONS FOR USER:  
Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:  
Not applicable.

## SECTION 15 : REGULATORY INFORMATION

15.1 EU SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC:  
The regulations applicable to this product generally are listed throughout this material safety data sheet.

Restrictions on manufacture, placing on market and use: See section 1.2

Tactile warning of danger: Not applicable (no se cumplen los criterios de clasificación).

Child safety protection: Not applicable (no se cumplen los criterios de clasificación).

VOC information on the label:  
Contains VOC max. 496. g/l for the product ready for use - The limit value 2004/42/CE-IIA cat i) is VOC max. 500. g/l (2010).

OTHER REGULATIONS:

Control of the risks inherent in major accidents (Seveso III): See section 7.2

Other local legislations:  
The receiver should verify the possible existence of local regulations applicable to the chemical.

15.2 CHEMICAL SAFETY ASSESSMENT:  
A chemical safety assessment has not been carried out for this mixture.

## AMPERE - TRAFFIC FLOOR PAINT

Code: 6301941001, 6301942001, 6301943001, 6301944001, 6301947001, 6301949001, 6301941015, 6301942015, 6301943015, 6301944015, 6301947015, 6301949015



## SECTION 16 : OTHER INFORMATION

TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:Hazard statements according to the Regulation (EU) No. 1272/2008~2020/1182 (CLP), Annex III:

H226 Vnetljiva tekočina in hlapi. H302 Zdravju škodljivo pri zaužitju. H304 Pri zaužitju in vstopu v dihalne poti je lahko smrtno. H312 Zdravju škodljivo v stiku s kožo. H315 Povzroča draženje kože. H317 Lahko povzroči alergijski odziv kože. H318 Povzroča hude poškodbe oči. H319 Povzroča hudo draženje oči. H332 Zdravju škodljivo pri vdihavanju. H335 Lahko povzroči draženje dihalnih poti. H336 Lahko povzroči zaspanost ali omotico. H362 Lahko škoduje dojenim otrokom. H400 Zelo strupeno za vodne organizme. H410 Zelo strupeno za vodne organizme, z dolgotrajnimi učinki. H411 Strupeno za vodne organizme, z dolgotrajnimi učinki. EUH066 Ponavljajoča izpostavljenost lahko povzroči nastanek suhe ali razpokane kože. H373i Lahko škoduje organom pri dolgotrajni ali ponavljajoči se izpostavljenosti pri vdihavanju. H373o Lahko škoduje organom pri dolgotrajni ali ponavljajoči se izpostavljenosti pri zaužitju.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES: See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of material safety data sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (ACGIH, 2018).
- European agreement on the international carriage of dangerous goods by road, (ADR 2021).
- International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this material safety data sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials).
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LD50: Lethal dose, 50 percent.
- LC50: Lethal concentration, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangerous goods by road.
- RID: Regulations concerning the international transport of dangerous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

MATERIAL SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.

HISTORY:Revision:

Version: 4 07/07/2021  
Version: 5 07/10/2021

Modifications with respect to the previous Material Safety Data Sheet:

# The possible legislative, contextual, numerical, methodological and normative changes with respect to the previous version are highlighted in this Material Safety Data Sheet by a mark # in red and italic.

IZJAVA O OMEJITVI ODGOVORNOSTI

Informacije, ki jih vsebuje ta list, izhajajo iz zanesljivih virov. Kot je navedeno, je bil list bil pripravljen na podlagi našega znanja v času najnovejše posodobitve.

Te informacije so namenjene pomoči uporabniku in se ne bi smele obravnavati kot jamstvo.

Pogoji in metode rokovanja, shranjevanja, uporabe ali odstranjevanja izdelka so zunaj našega nadzora in nismo odgovorni za kakršno koli izgubo, škodo ali stroške, ki nastanejo zaradi ali v povezavi z naštetim.

Vse snovi ali zmesi lahko predstavljajo neznane nevarnosti in jih je treba uporabljati previdno. Ne moremo zagotoviti, da so vse nevarnosti podrobno opisane.

Ta list je pripravljen samo za ta izdelek in ga je tako treba tudi uporabiti. Če se izdelek uporablja kot komponenta v drugem izdelku, informacije, ki so priložene zraven izdelka, morda ne bodo uporabne.

S tem listom uporabnik v nobenem primeru ni oproščen izpolnjevanja vseh zakonov, predpisov in upravnih zahtev v zvezi z izdelkom, zdravjem in varnostjo ter varovanjem zdravja ljudi in okolja.

The information of this Material Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Material Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.