











Absorbent sheeting qualities

<p style="text-align: center;"><b>Absorbent sheeting qualities</b></p> <p><b>Characteristics</b></p>	 <b>FIRST - medium</b> 	 <b>First - heavy</b> 	 <b>BASIC</b> 	 <b>PRO</b> 	 <b>PRO PLUS</b> 
<b>Absorption capacity</b>	+	++	++	+++	+++
<b>1-ply</b>	x	x			
<b>2-ply</b>			x		
<b>3-ply</b>				x	x
<b>Top</b>	open	open	reinforced fleece layer, hardwearing, fuzz free, smooth	reinforced fleece layer, hardwearing, fuzz free, smooth	reinforced fleece layer, hardwearing, fuzz free, smooth
<b>Bottom</b>	open	open	open	reinforced fleece layer, hardwearing, fuzz free, smooth	dense, anti-slip film and reinforced fleece layer, hardwearing, fuzz free, smooth
<b>Single use (simple applications)</b>	x	x	x	x	x
<b>Oil and water separation</b>	x	x			
<b>Under machines to absorb smaller, regular leakages</b>	x	x	x		
<b>Wiping and drying surfaces (normal applications)</b>			x	x	x
<b>As an underlay (long-term applications)</b>				x	x
<b>Anti-slip, can be walked and driven on</b>					x
<b>Dust-free use</b>				x	x
<b>Wiping machine parts</b>				x	
<b>Work underlay</b>				x	
<b>Prevention (floor protection, anti-slip surface, unsealed floors)</b>					x