




Safety steering unit with ergonomic controls



Accessible passageway width:
2210 mm for 800 x 1200 mm pallets,
lengthwise entry



€ 3350.00

Ref. 118 454 3H



Electric drawbar stackers

- Electric drive – electro-hydraulic lifting
- Maintenance free AGM batteries
- Operates for approx 2 hours

Lifting range: 90 – 1600 mm. Fork length: 1153 mm. Fork width: 150 mm. Distance across forks: 560 mm. Length: 1675 mm. Width: 794 mm. Overall height: 1970 mm. Min. lifting speed: 110 mm/s. Max. lifting speed: 180 mm/s. Min. driving speed: 3.7 km/h. Max. driving speed: 4.3 km/h. Climbing performance with load: 9 %. Climbing performance without load: 25 %. Design of mast: single mast. Turning radius: 1344 mm. Thickness of fork prong: 60 mm. Battery: 2 x 12 V / 70 Ah. Battery charger: 8 A impulse charger. Working gangway for pallet length: 2120 mm. Fork roller material: polyurethane. Fork roller version: single. Fork roller diameter: 82 mm. Fork roller width: 70 mm. Steering wheel width: 50 mm. Steering wheel diameter: 186 mm. Travel motor: 0.35 kW. Lifting motor: 2.2 kW. Max. load: 1100 kg.

Ref. 118 455 3H € 4650.00

On request

- Max. load up to 1600 kg
- Lifting height up to 5000 mm
- Wide gauge chassis possible



Electric lifting trolleys

- European product with high quality standard
- Maintenance free AGM batteries
- Operates for approx 2 – 3 hours

Max. load: 1200 kg. Lifting range: 85 – 200 mm. Fork length: 1150 mm. Fork width: 150 mm. Distance across forks: 520 mm. Length: 1510 mm. Width: 520 mm. Overall height: 1345 mm. Min. lifting speed: 0.03 m/s. Max. lifting speed: 0.04 m/s. Min. driving speed: 4.3 km/h. Max. driving speed: 4.8 km/h. Climbing performance with load: 10 %. Climbing performance without load: 25 %. Turning radius: 1268 mm. Thickness of fork prong: 55 mm. Battery: 2 x 12 V / 60 Ah. Battery charger: 8 A impulse charger. Working gangway for pallet length: 2120 mm. Fork roller material: polyurethane. Fork roller version: single. Fork roller diameter: 82 mm. Fork roller width: 82 mm. Steering wheel width: 50 mm. Steering wheel diameter: 186 mm.

Ref. 118 454 3H € 3350.00

Other lifting trolleys on request

- Fork lengths 800 or 1000 mm
- Lifting truck with scales
- Larger models – also with operator platform
- Inverter charger for trucks