

5 – 10 | Material lifter

- Exchangeable load support
- Optionally available with fixed castors or 4-way chassis
- Swivel castors with wheel stops

Overall length: 970 mm. Overall width: 506 mm. Overall height: 1265 mm. Clearance height: 75 mm. Material: steel. Feature: manual. Finish: powder coated. Colour: signal blue RAL 5005. Steering wheel diameter: 125 mm. Support leg length: 610 mm. Conforms to: DIN EN ISO 3691-5:2014. Lift per crank rotation: 130 mm.



Video
Online!



5

7



Available in most
RAL colours.
Only 10% extra.

Type		5	6	7	8	9	10
		platform / fixed castors	platform / 4-way chassis	spike / fixed castors	spike / 4-way chassis	adjustable box fork / fixed castors	adjustable box fork / 4-way chassis
Load suspension device LxW/Ø	mm	600 x 430	600 x 430	600 x 42	600 x 42	450 x 140 - 330	450 x 140 - 330
Max. load	kg	120	120	120	120	100	100
Load centre	mm	300	300	300	300	270	270
Lifting range	mm	80 – 945	80 – 945	120 – 985	120 – 985	110 – 970	110 – 970
Distance across forks		430	430				
Wheel fittings		2 swivel castors with wheel stops, 2 fork rollers	2 steering wheels with wheel stops, 2 swivel castors	2 swivel castors with wheel stops, 2 fork rollers	2 steering wheels with wheel stops, 2 swivel castors	2 swivel castors with wheel stops, 2 fork rollers	2 steering wheels with wheel stops, 2 swivel castors
Castor diameter front / rear	mm	70 / 125	35 / 125	70 / 125	35 / 125	70 / 125	70 / 125
Fork roller material		nylon	polyurethane	nylon	polyurethane	nylon	nylon
Ref.		522 654 6F	522 655 6F	522 656 6F	522 657 6F	569 591 6F	569 592 6F
£		799.00	779.00	779.00	779.00	799.00	819.00

14 – 16 | Lift trucks

- Can be moved as a truck for long routes
- Exact positioning on 4 wheels
- Exchangeable load supports

Overall length: 925 mm. Overall width: 575 mm. Overall height: 1265 mm. Clearance height: 75 mm. Material: steel. Feature: manual. Finish: powder coated. Colour: signal blue RAL 5005. Wheel fittings: 2 wheels, 2 swivel castors. Castor diameter front / rear: 35 / 200 mm. Fork roller diameter: 35 mm. Support leg length: 610 mm. Conforms to: DIN EN ISO 3691-5:2014. Lift per crank rotation: 130 mm. Wheel Ø: 200 mm.



15

14



11 | Box forks for material lifter and lift truck

Adjustment range: 140 – 330 mm.
Length: 450 mm.

11 | Ref. 569 590 6F £ 149.00

12 | Platform for material lifter and lift truck

Length: 600 mm. Width: 430 mm. Max. load: 120 kg.

12 | Ref. 522 663 6F £ 74.90

13 | Spike for material lifter and lift truck

Length: 600 mm. Max. load: 120 kg.
Diameter: 42 mm.

13 | Ref. 522 664 6F £ 49.90



Video
Online!



Type		14	15	16
		with adjustable box fork	with platform	with spike
Load suspension device LxW/Ø	mm	450 x 140-330	600 x 430	600 x 42
Max. load	kg	100	120	120
Load centre	mm	270	300	300
Lifting range	mm	110 – 970	80 – 945	120 – 985
Fork roller material		nylon	polyurethane	polyurethane
Weight	kg	43.5	45.8	37.3
Ref.		569 593 6F	522 660 6F	522 661 6F
£		939.00	859.00	829.00



Available in most
RAL colours.
Only 10% extra.