



Rotary lift tables

- Rotating platform
- Simple and robust
- No hydraulics – no leaks

Max. load: 2000 kg. Lifting range: 241 – 705 mm. Platform design: round/turntable. Lift drive: spring balance. Fittings: stacker forklift pockets. Platform width: 1110 mm. Platform length: 1110 mm. Feature: mobile / manual.

Finish: powder coated. Frame colour: melon yellow RAL 1028.

► **Ref. 532 962 3H £ 1700.00**

Finish: stainless steel. Frame colour: stainless steel.

► **Ref. 532 963 3H £ 3725.00**



From

£ 2050.00

Ref. 474 536 3H

Compact lift tables

- Free standing
- Can be built-in to floor for ground level loading / unloading
- To be loaded with a counterbalance forklift

Frame colour: jet black RAL 9005.

Fittings: with hand operated control unit.

Lifting capacity at full load in 1 shift operations: 6 cycles per hour. Platform width: 800 mm. Platform length: 1300 mm. Feature: stationary / electro-hydraulic.

Lifting range: 190 – 1010 mm. Platform design: closed. Operating voltage: 400 V. Control voltage: 24 V. Lift drive: electro-hydraulic. Platform colour: light blue RAL 5012. Scissor mechanism colour: jet black RAL 9005. Finish: powder coated.

Max. load	kg	1000	2000
Operating voltage			
230 V	Ref.	554 815 3H	554 817 3H
	£	2300.00	2525.00
400 V	Ref.	968 791 3H	
	£	2200.00	



More products online!

All lift tables are fitted with safety rails and safety valves, and comply with EN 1570-1 as well as VDE requirements.



From

£ 2850.00

Ref. 968 793 3H

Supplied with ramp element for loading with pallet truck

Low profile lift tables

- Suitable for Euro pallets and industrial pallets
- A counterbalance forklift is not required

Max. load: 1000 kg. Control voltage: 24 V. Platform colour: light blue RAL 5012. Frame colour: jet black RAL 9005. Fittings: with hand operated control unit. Lifting capacity at full load in 1 shift operations: 6 cycles per hour. Lifting time without load: 18 sec. Lifting time with full load: 23 sec. Platform width: 1140 mm. Platform length: 1450 mm. Feature: stationary / electro-hydraulic.

Lifting range	mm	80 – 840	85 – 840
Platform design		U-shaped	closed
Internal width		580	
Operating voltage			
230 V	Ref.	554 809 3H	
	£	2950.00	
400 V	Ref.	968 793 3H	► 968 794 3H
	£	2850.00	2925.00