



VERIBOR
MADE IN GERMANY

Suction lifters

- For lifting, carrying and holding glass, panes, etc.
- For level, non-porous surfaces
- Secure hold and convenient transport

Material: aluminium element.

		10	11	12	13	14	15	16
Head Ø	mm	120	120	120	120	120	120	210
Max. load	kg	30	35	60	60	70	100	120
Number of heads	pcs.	1	2	2	2	2	3	1
Material		aluminium element	plastic body	cast aluminium styrene butadiene rubber	aluminium element	aluminium element	aluminium element	aluminium element
From								
1 pcs.	Ref.	►759 405 3H	►704 521 3H	455 688 3H	►759 408 3H	►759 412 3H	►759 410 3H	►759 417 3H
	£	73.00	101.00	93.00	62.00	79.00	90.00	275.00
								►773 271 3H
								171.00
2 pcs.	Ref.	►759 407 3H	►704 522 3H		►759 409 3H	►759 413 3H	►759 411 3H	
	£	62.00	90.00		56.00	68.00	85.00	

PULLMASTER-II spur gear block and tackle units

- Tempered safety hook with custom-fit hook lock
- Robust, durable steel housing
- Flexible use due to hook suspension

Lift: 3 m. Housing material: sheet steel, powder coated. Scope of delivery: with load chain.

Max. load: 500 kg. Number of chain strands: 1. Overall height: 285 mm. Hand chain tensile force at full load: 26.2 daN.

Ref. 491 259 3H £ 173.00

Max. load: 1000 kg. Number of chain strands: 1. Overall height: 332 mm. Hand chain tensile force at full load: 32.4 daN.

Ref. 491 260 3H £ 225.00



Premium PRO spur gear block and tackle units

- Compact and lightweight
- Overload protection as standard (max. load 500 kg or higher)
- Annealed, galvanised load chain compliant with DIN EN 818-7-T

Lift: 3 m. Housing material: sheet steel, chrome plated.

Max. load: 500 kg. Number of chain strands: 1. Overall height: 309 mm. Hand chain tensile force at full load: 24 daN.

Ref. 478 276 3H £ 225.00

Max. load: 1500 kg. Number of chain strands: 1. Overall height: 460 mm. Hand chain tensile force at full load: 36 daN.

Ref. 478 278 3H £ 405.00



Value pack: pack of 2.

Professional balancers

- Comfortable working even with heavy tools due to weight counterbalance
- Durable and robust construction
- Low friction stainless steel wire cable and adjustable load bearing range

Design of hooks: safety hooks. Housing material: aluminium.

Max. load from – to	kg	1 – 2	2 – 3	2 – 4	4 – 6	6 – 8
Cable length	mm	1600	1600	2000	2000	2000
	Ref.	175 855 3H	175 856 3H	175 857 3H	175 858 3H	175 859 3H
	£	55.00	56.00	123.00	147.00	169.00

Balancers

- Infinite max. load setting
- High gloss chrome plated steel housing
- Steel cable sheathed in plastic with snap hook for tool suspension

Cable length: 1700 mm. Weight: 0.4 kg. Suspension eye: rigid. Design of hooks: safety hooks. Housing material: steel, chrome plated. Weight per item: 0.2 kg. Pack of: 2.

Max. load from – to: 0.5 – 1.5 kg.

►Ref. 176 344 3H £/pack 66.00


Max. load from – to: 1.5 – 3 kg.

►Ref. 176 345 3H £/pack 77.00

Balancers

- Comfortable working even with heavy tools due to weight counterbalance
- High quality construction made of cast aluminium housing and a stainless steel cable
- An integrated securing mechanism prevents the load from dropping if the spring breaks (> 3 kg)

Cable length: 2000 mm. Design of hooks: safety hooks.



Max. load from – to	kg	4 – 7	7 – 10	10 – 14	14 – 18	18 – 22	22 – 25
	Ref.	175 868 3H	175 869 3H	175 871 3H	175 872 3H	175 873 3H	175 874 3H
	£	299.00	299.00	329.00	329.00	359.00	359.00



Free delivery to UK mainland for over 80,000 products.

UK
Ireland

01442 238 000
1 800 677 300

KAISER+KRAFT