

Thermoplastic rubber tyres

- Non-leak tyres
- Low rolling resistance, smooth running
- Non-marking tyres, hardwearing

Wheel material: thermoplastic rubber. Material of rim: polypropylene. Housing material: steel. Type of mounting: with top plate. Wheel bearing: plain bearing. Temperature resistance: -10 °C to +70 °C. Housing surface: zinc plated. Shore hardness: 85 ± 3 A. Feature: non-marking / low wear / low rolling resistance / low swivel resistance.

Wheel Ø	mm	75	100	125	
Max. load at 4 km/h	kg	75	80	100	
Wheel width	mm	25	32	32	
Overall height	mm	100	135	160	
Screw hole diameter	mm	6	8.5	8.5	
Fixed castor plate dimensions	mm	60 x 60	77 x 67	77 x 67	
Swivel castor plate dimensions	mm	60 x 60	77 x 67	77 x 67	
Screw hole spacing	mm	48 / 38 x 48 / 38	61.5 / 51.5 x 56.5 / 46.5	61.5 / 51.5 x 56.5 / 46.5	
Structure	Scope of delivery				
swivel castor	4 swivel castors,	Ref.	►969 286 3H	►969 288 3H	►969 291 3H
swivel castor with double stop	2 with double stop	£	39.50	50.00	57.00
swivel castor with double stop	2 swivel castors with double stops,	Ref.	►969 287 3H	►969 289 3H	►969 292 3H
fixed castor	2 fixed castors	£	34.00	43.00	52.00

Thermoplastic rubber tyres

- On polypropylene rim
- Low rolling resistance, smooth running
- Non-marking tyres, hardwearing

Wheel material: thermoplastic rubber. Material of rim: polypropylene. Housing material: steel. Type of mounting: with threaded pin / with bolt hole. Wheel bearing: plain bearing. Temperature resistance: -10 °C to +70 °C. Threaded pin dimensions: M 10 x 18 mm. Housing surface: zinc plated. Shore hardness: 85 ± 3 A. Feature: non-marking / low wear / low rolling resistance / low swivel resistance.

Wheel Ø	mm	75	100	125
Max. load at 4 km/h	kg	75	80	100
Wheel width	mm	25	32	32
Overall height	mm	100	135	160
Screw hole diameter	mm	10.5	11	11
Scope of delivery				
4 swivel castors	Ref.	►969 293 3H	►969 295 3H	►969 297 3H
	£	33.00	40.00	49.00
4 swivel castors, 2 with double stop	Ref.	►969 294 3H	►969 296 3H	►969 298 3H
	£	43.00	52.00	58.00

Housing and wheel axles made of rust free **stainless steel**. Swivel bearing with double ball race, swivel bearing protection.

Polyurethane tyres on nylon rims

- Non-marking
- Hardwearing and cut resistant
- Largely resistant against many thinned oils, greases, and alkaline solutions

Wheel material: polyurethane. Material of rim: nylon. Housing material: stainless steel. Type of mounting: with top plate. Wheel bearing: plain bearing. Temperature resistance: -15 °C to +60 °C. Housing surface: stainless steel. Shore hardness: 95 A. Feature: does not damage floors / low wear / low rolling resistance / low swivel resistance / non-marking.



High load capacity



Non-marking



INOX STAINLESS STEEL

Wheel Ø	mm	100	125	160
Max. load at 4 km/h	kg	140	180	240
Wheel width	mm	30	32	38
Overall height	mm	128	155	197
Screw hole diameter	mm	9	9	11
Hub length	mm	40	44	58
Hub bore	mm	12	15	20
Fixed castor plate dimensions	mm	102 x 80	102 x 80	135 x 110
Swivel castor plate dimensions	mm	102 x 80	102 x 80	135 x 110
Screw hole spacing	mm	80 x 60	80 x 60	105 x 80
Structure				
fixed castor	Ref.	►610 055 3H	►610 059 3H	►940 284 3H
	£	23.00	30.50	50.00
swivel castor	Ref.	►610 052 3H	►610 057 3H	►940 281 3H
	£	33.00	36.00	64.00
swivel castor with double stop	Ref.	►610 053 3H	►610 058 3H	►940 282 3H
	£	39.50	45.00	75.00
Accessories				
Wheels	Ref.	►610 056 3H	►610 060 3H	►940 285 3H
	£	6.60	10.25	17.50

Nylon wheels

- Maintenance free, smooth running
- Hardwearing
- High maximum load

Wheel material: nylon. Material of rim: nylon. Housing material: stainless steel. Type of mounting: with top plate. Wheel bearing: plain bearing. Temperature resistance: -20 °C to +60 °C. Housing surface: stainless steel. Feature: does not damage floors / low wear / low rolling resistance / low swivel resistance / non-marking.



High load capacity



Maintenance-free



INOX STAINLESS STEEL

Wheel Ø	mm	80	100	125	160	200
Max. load at 4 km/h	kg	150	150	180	300	300
Wheel width	mm	30	32	34	40	50
Overall height	mm	108	128	155	197	235
Screw hole diameter	mm	9	9	9	11	11
Hub length	mm	40	40	48	58	60
Hub bore	mm	12	12	10	20	20
Fixed castor plate dimensions	mm	105 x 85	105 x 85	105 x 85	137 x 105	137 x 105
Swivel castor plate dimensions	mm	105 x 85	105 x 85	105 x 85	137 x 105	137 x 105
Screw hole spacing	mm	80 x 60	80 x 60	80 x 60	105 x 80	105 x 80
Structure						
fixed castor	Ref.	►940 288 3H	►940 293 3H	►940 297 3H	►940 301 3H	►940 306 3H
	£	18.00	18.50	23.00	45.00	51.00
swivel castor	Ref.	►940 286 3H	►940 290 3H	►940 295 3H	►940 299 3H	►940 303 3H
	£	26.00	27.50	31.50	56.00	64.00
swivel castor with double stop	Ref.	►940 287 3H	►940 292 3H	►940 296 3H	►940 300 3H	►940 304 3H
	£	35.00	35.00	38.50	69.00	75.00
Accessories						
Wheels	Ref.	►940 289 3H	►940 294 3H	►940 298 3H	►940 302 3H	►940 307 3H
	£	2.90	3.60	6.40	8.60	14.25

proroll®



Non-marking



Free delivery to UK mainland for over 80,000 products.

UK
Ireland

01442 238 000
1 800 677 300

KAISER+KRAFT