



## Solid rubber tyres

- On sheet steel rim
- For light to medium duty requirements
- Very quiet on hard floors

Wheel material: solid rubber. Material of rim: sheet steel, bright zinc plated. Housing material: steel. Type of mounting: with top plate. Wheel bearing: roller bearing. Temperature resistance: -5 °C to +60 °C. Housing surface: zinc plated blue passivated. Shore hardness: 85 ±3 A. Feature: does not damage floors.

Swivel bearing with double ball race, swivel bearing protection.

Wheel Ø	mm	80	100	125	160	200
Max. load at 4 km/h	kg	50	70	100	135	205
Wheel width	mm	25	30	38	40	50
Overall height	mm	100	125	155	200	240
Screw hole diameter	mm	9	9	9	11	11
Hub length	mm	40	40	50	58	58
Hub bore	mm	12	12	15	20	20
Fixed castor plate dimensions	mm	102 x 87	102 x 87	102 x 87	137 x 115	137 x 115
Swivel castor plate dimensions	mm	105 x 80	105 x 80	105 x 80	137 x 105	137 x 105
Screw hole spacing	mm	76 – 80 x 60	76 – 80 x 60	76 – 80 x 60	105 x 75 – 80	105 x 75 – 80
<b>Structure</b>						
fixed castor	Ref.	►969 237 3H	►969 241 3H	►969 245 3H	►969 270 3H	►969 275 3H
	£	9.70	11.75	17.00	19.75	28.50
swivel castor	Ref.	►969 235 3H	►969 239 3H	►969 243 3H	►969 268 3H	►969 272 3H
	£	17.50	19.25	19.75	22.00	30.50
swivel castor with double stop	Ref.	►969 236 3H	►969 240 3H	►969 244 3H	►969 269 3H	►969 274 3H
	£	27.50	31.50	34.00	35.00	43.00
<b>Accessories</b>						
Wheels	Ref.	►969 238 3H	►969 242 3H	►969 246 3H	►969 271 3H	►969 276 3H
	£	5.80	7.10	7.50	14.25	16.00



## Solid rubber tyres

- On sheet steel rim
- For light to medium duty requirements
- Very quiet on hard floors

Wheel material: solid rubber. Material of rim: sheet steel, bright zinc plated. Housing material: steel. Type of mounting: with top plate. Wheel bearing: roller bearing. Temperature resistance: -5 °C to +60 °C. Screw hole diameter: 15 mm. Hub bore: 25 mm. Fixed castor plate dimensions: 220 x 120 mm. Swivel castor plate dimensions: 175 x 175 mm. Housing surface: zinc plated blue passivated. Shore hardness: 85 ±3 A. Feature: does not damage floors.

Swivel bearing with double ball race, swivel bearing protection.

Wheel Ø	mm	250	250	280	280
Max. load at 4 km/h	kg	295	295	385	385
Wheel width	mm	60	60	70	70
Overall height	mm	295	295	320	320
Hub length	mm	65	65	75	75
Screw hole spacing	mm	190 x 75	140 x 140	190 x 75	140 x 140
<b>Structure</b>					
fixed castor	Ref.	►190 861 3H		►190 896 3H	
	£	58.00		80.00	
swivel castor	Ref.		►191 248 3H		►191 264 3H
	£		75.00		97.00
swivel castor with double stop	Ref.		►751 731 3H		►751 758 3H
	£		94.00		129.00
<b>Accessories</b>					
Wheels	Ref.	►191 345 3H	►191 345 3H	►191 361 3H	►191 361 3H
	£	34.00	34.00	48.00	48.00

Also available as electrically conductive models on request.



## Solid rubber tyres, non-marking

- On sheet steel rim
- No annoying black marks on flooring
- Very quiet on hard floors

Wheel material: solid rubber, non-marking. Material of rim: sheet steel, galvanised. Housing material: steel. Type of mounting: with top plate. Wheel bearing: roller bearing. Temperature resistance: -5 °C to +60 °C. Housing surface: zinc plated. Shore hardness: 82 ±3 A. Feature: does not damage floors / non-marking.



Non-marking



Swivel bearing with sealed double ball race.

Wheel Ø	mm	80	100	125	160	200
Max. load at 4 km/h	kg	50	70	100	135	205
Wheel width	mm	25	30	38	40	50
Overall height	mm	100	125	155	190	235
Screw hole diameter	mm	9	9	9	11	11
Hub length	mm	40	40	50	60	60
Hub bore	mm	12	12	15	20	20
Fixed castor plate dimensions	mm	102 x 87	102 x 87	102 x 87	135 x 114	135 x 114
Swivel castor plate dimensions	mm	105 x 80	105 x 80	105 x 80	135 x 110	135 x 110
Screw hole spacing	mm	76 – 80 x 60	76 – 80 x 60	76 – 80 x 60	105 x 75 – 80	105 x 75 – 80
<b>Structure</b>						
fixed castor	Ref.	►957 984 3H	►957 992 3H	►958 000 3H	►958 018 3H	►958 026 3H
	£	16.50	17.50	23.00	40.00	54.00
swivel castor	Ref.	►957 747 3H	►957 755 3H	►957 763 3H	►957 771 3H	►957 780 3H
	£	20.00	23.00	29.50	47.00	57.00
swivel castor with double stop	Ref.	►957 810 3H	►957 828 3H	►957 836 3H	►957 844 3H	►957 852 3H
	£	29.50	31.50	38.50	54.00	73.00
<b>Accessories</b>						
Wheels	Ref.	►958 107 3H	►958 115 3H	►958 123 3H	►958 131 3H	►958 140 3H
	£	7.20	8.50	10.25	20.00	33.00