



High load capacity



Hard wearing

Two component solid rubber tyres

- On sheet steel rims
- Very smooth running
- Non-marking

Wheel material: semi-elastic solid rubber. Material of rim: sheet steel, galvanised. Housing material: steel. Type of mounting: with top plate. Wheel bearing: roller bearing. Temperature resistance: -25 °C to +80 °C. Housing surface: zinc plated blue passivated. Shore hardness: 65 A. Feature: does not damage floors / low rolling resistance.



Swivel bearing with double ball race, smooth rolling with a minimum of play.

Wheel Ø	mm	125	140	160	180	200	250
Max. load at 4 km/h	kg	120	175	225	300	350	450
Wheel width	mm	37.5	37.5	40	50	50	60
Overall height	mm	150	170	195	215	235	295
Screw hole diameter	mm	9	11	11	11	11	15
Hub length	mm	45	45	60	60	60	65
Hub bore	mm	15	15	20	20	20	25
Fixed castor plate dimensions	mm	100 x 85	140 x 110	140 x 110	140 x 110	140 x 110	175 x 175
Swivel castor plate dimensions	mm	100 x 85	140 x 110	140 x 110	140 x 110	140 x 110	175 x 175
Screw hole spacing	mm	80 x 60	105 x 75 - 80	105 x 75 - 80	105 x 75 - 80	105 x 75 - 80	140 x 140
Structure							
fixed castor	Ref.	►179 233 3H	►179 241 3H	►179 234 3H	►190 624 3H	►179 235 3H	►179 236 3H
	£	22.00	35.00	43.00	54.00	56.00	107.00
swivel castor	Ref.	►179 229 3H	►179 240 3H	►179 230 3H	►191 507 3H	►179 231 3H	►179 232 3H
	£	26.00	43.00	48.00	57.00	58.00	129.00
swivel castor with double stop	Ref.	►179 228 3H	►179 242 3H	►179 239 3H	►751 804 3H	►179 238 3H	►179 237 3H
	£	40.00	64.00	64.00	86.00	80.00	161.00
Accessories							
Wheels	Ref.	►179 223 3H	►179 224 3H	►179 225 3H	►191 639 3H	►179 226 3H	►179 227 3H
	£	15.25	17.00	22.00	38.50	49.00	89.00



Fixed castor



Swivel castor with double stop



Swivel castor



Wheels



More products online!



Solid rubber tyres

- On plastic rims
- For light to medium duty requirements
- Very quiet on hard floors

Wheel material: solid rubber. Material of rim: plastic. Housing material: steel. Type of mounting: with top plate. Wheel bearing: roller bearing. Temperature resistance: -5 °C to +60 °C. Housing surface: zinc plated blue passivated. Shore hardness: 85 ± 3 A. Feature: does not damage floors.

Swivel bearing with double ball race and swivel bearing protection.

Wheel Ø	mm	80	100	125	160	200
Max. load at 4 km/h	kg	50	70	100	135	205
Wheel width	mm	25	30	38	40	50
Overall height	mm	100	125	155	200	240
Screw hole diameter	mm	9	9	9	11	11
Hub length	mm	40	40	50	58	58
Hub bore	mm	12	12	15	20	20
Fixed castor plate dimensions	mm	102 x 87	102 x 87	102 x 87	137 x 115	137 x 115
Swivel castor plate dimensions	mm	105 x 80	105 x 80	105 x 80	137 x 105	137 x 105
Screw hole spacing	mm	76 - 80 x 60	76 - 80 x 60	76 - 80 x 60	75 - 80 x 105	75 - 80 x 105
Structure						
fixed castor	Ref.	►969 250 3H	►969 254 3H	►969 259 3H	►969 279 3H	►969 284 3H
	£	8.00	9.20	11.00	22.50	31.50
swivel castor	Ref.	►969 247 3H	►969 252 3H	►969 256 3H	►969 277 3H	►969 282 3H
	£	10.25	11.75	13.75	25.00	34.00
swivel castor with double stop	Ref.	►969 248 3H	►969 253 3H	►969 258 3H	►969 278 3H	►969 283 3H
	£	19.75	22.00	24.00	34.00	49.00
Accessories						
Wheels	Ref.	►969 251 3H	►969 255 3H	►969 260 3H	►969 280 3H	►969 285 3H
	£	4.30	5.10	5.80	11.25	19.75

Free delivery to UK mainland for over 80,000 products.

UK
Ireland

01442 238 000
1 800 677 300

KAISER+KRAFT