



Nylon wheels

- Maintenance free, smooth running
- Hardwearing
- Largely resistant against many thinned acid and alkaline solutions

Wheel material: nylon. Material of rim: nylon. Housing material: steel. Type of mounting: with top plate. Temperature resistance: -20 °C to +80 °C. Housing surface: galvanised and chrome-plated. Feature: low wear / low rolling resistance / low swivel resistance / non-marking.



Swivel bearing with double ball race, swivel bearing protection.

Wheel Ø	mm	65	80	100	125	150	200	80	100	125
Max. load at 4 km/h	kg	100	150	180	200	300	300	150	180	200
Wheel width	mm	30	35	38	38	40	50	35	38	38
Overall height	mm	93	100	125	155	185	235	100	125	155
Wheel bearing		plain bearing	plain bearing	plain bearing	plain bearing	plain bearing	plain bearing	roller bearing	roller bearing	roller bearing
Screw hole diameter	mm	9	9	9	9	11	11	9	9	9
Hub length	mm	40	40	40	50	60	60	40	40	50
Hub bore	mm	12	12	12	15	20	20	12	12	15
Fixed castor plate dimensions	mm	100 x 70	102 x 87	102 x 87	102 x 87	135 x 114	135 x 114	102 x 87	102 x 87	102 x 87
Swivel castor plate dimensions	mm	100 x 70	105 x 80	105 x 80	105 x 80	135 x 110	135 x 110	105 x 80	105 x 80	105 x 80
Screw hole spacing	mm	75 x 45	76 - 80 x 60	76 - 80 x 60	76 - 80 x 60	105 x 75 - 80	105 x 75 - 80	76 - 80 x 60	76 - 80 x 60	76 - 80 x 60
Structure										
fixed castor	Ref.	► 192 716 3H	► 192 724 3H	► 659 139 3H	► 192 767 3H	► 192 783 3H	► 192 821 3H	► 892 149 3H	► 892 181 3H	► 892 246 3H
	£	10.25	10.50	20.00	18.00	27.50	37.00	12.00	14.25	19.25
swivel castor	Ref.	► 192 910 3H	► 192 929 3H	► 659 140 3H	► 192 961 3H	► 192 996 3H	► 193 011 3H	► 892 122 3H	► 892 165 3H	► 892 211 3H
	£	14.75	16.50	25.00	22.50	37.00	44.00	17.00	19.25	26.00
swivel castor with double stop	Ref.		► 771 155 3H	► 659 141 3H	► 771 201 3H	► 771 236 3H	► 771 252 3H	► 892 130 3H	► 892 173 3H	► 892 238 3H
	£		26.00	30.50	31.50	54.00	62.00	28.50	30.50	34.00
Accessories										
Wheels	Ref.	► 193 178 3H	► 193 186 3H	► 659 137 3H	► 193 224 3H	► 193 240 3H	► 193 267 3H	► 892 157 3H	► 892 203 3H	► 892 254 3H
	£	3.00	5.70	10.25	12.00	13.00	26.00	6.20	8.00	10.75
2 swivel castors, 2 swivel castors with double stops	Ref.		► 986 094 3H	► 986 099 3H	► 986 104 3H			► 986 096 3H	► 986 102 3H	► 986 106 3H
	£	—	68.00	73.00	90.00	—	—	73.00	85.00	99.00
2 swivel castors with double stops, 2 fixed castors	Ref.		► 986 095 3H	► 986 101 3H	► 986 105 3H			► 986 098 3H	► 986 103 3H	► 986 107 3H
	£	—	62.00	68.00	85.00	—	—	68.00	73.00	90.00

 **More products online!**



Nylon wheels

- Smooth running, maintenance free
- Largely resistant against many thinned acid and alkaline solutions
- Hardwearing

Wheel material: nylon. Material of rim: nylon. Housing material: steel. Type of mounting: with bolt hole. Wheel bearing: roller bearing. Temperature resistance: -20 °C to +80 °C. Bolt hole diameter: 12 mm. Plate diameter: 70 mm. Housing surface: galvanised and chrome-plated. Feature: low wear / low rolling resistance / low swivel resistance.



Wheel Ø	mm	80	100	125
Max. load at 4 km/h	kg	150	180	200
Wheel width	mm	35	38	38
Overall height	mm	100	125	155
Hub length	mm	40	40	50
Hub bore	mm	12	12	15
Structure				
swivel castor	Ref.	► 704 694 3H	► 704 697 3H	► 704 699 3H
	£	12.00	12.00	15.25
swivel castor with double stop	Ref.	► 704 696 3H	► 704 698 3H	► 704 700 3H
	£	19.25	20.00	23.00
Accessories				
Wheels	Ref.	► 892 157 3H	► 892 203 3H	► 892 254 3H
	£	6.20	8.00	10.75