



Swivel bearing with double ball race, swivel bearing protection.



TENTE

Polyurethane tyres

- On nylon rim
- Extremely durable for high performance, low rolling resistance
- Largely resistant against many thinned oils, greases, and chemicals

Wheel material: polyurethane. Material of rim: nylon. Housing material: steel. Type of mounting: with top plate. Wheel bearing: roller bearing.

Temperature resistance: -40 °C to +80 °C. Housing surface: galvanised and chrome-plated. Shore hardness: D40. Feature: does not damage floors / low wear / low rolling resistance / low swivel resistance / non-marking.

Wheel Ø	mm	80	100	125	160	200
Max. load at 4 km/h	kg	100	150	200	350	350
Wheel width	mm	32	32	32	40	46
Overall height	mm	108	128	155	200	240
Screw hole diameter	mm	9	9	9	11	11
Hub length	mm	44.4	44.4	44.4	58	58
Hub bore	mm	12	12	12	20	20
Fixed castor plate dimensions	mm	103 x 85	103 x 85	103 x 85	137 x 115	137 x 115
Swivel castor plate dimensions	mm	105 x 85	105 x 85	105 x 85	137 x 105	137 x 105
Screw hole spacing	mm	60 x 77 - 80	60 x 77 - 80	60 x 77 - 80	105 x 75 - 80	105 x 75 - 80
Structure						
fixed castor	Ref.	►918 653 3H	►918 657 3H	►918 662 3H	►918 666 3H	►918 670 3H
	£	14.75	15.25	17.00	38.50	47.00
swivel castor	Ref.	►918 650 3H	►918 655 3H	►918 659 3H	►918 664 3H	►918 668 3H
	£	17.50	17.00	18.00	49.00	54.00
swivel castor with double stop	Ref.	►918 651 3H	►918 656 3H	►918 661 3H	►918 665 3H	►918 669 3H
	£	26.00	22.00	25.00	67.00	72.00
Accessories						
Wheels	Ref.	►918 654 3H	►918 658 3H	►918 663 3H	►918 667 3H	►918 671 3H
	£	6.90	9.10	11.25	26.00	38.50
2 swivel castors, 2 swivel castors with double stops	Ref.	►985 957 3H	►985 959 3H	►985 962 3H	-	-
	£	61.00	56.00	61.00	-	-
2 swivel castors with double stops, 2 fixed castors	Ref.	►985 958 3H	►985 960 3H	►985 963 3H	-	-
	£	56.00	56.00	61.00	-	-

Nylon wheels

- Extremely hardwearing
- Largely resistant against many thinned acid and alkaline solutions
- High maximum load

Structure: wheel. Wheel material: thermoplastic plastic. Material of rim: nylon. Temperature resistance: -40 °C to +80 °C.



Thermoplastic nylon-based plastic.

Wheel Ø	mm	50	65	70	75	80	100	125	150	200	250
Max. load at 4 km/h	kg	150	170	200	200	300	450	600	600	1000	1000
Wheel width	mm	25	30	30	23	35	40	40	50	50	50
Hub length	mm	30	35	40	25	35	50	53	55	52	58
Wheel bearing											
deep groove ball bearing	12 mm	Ref.				►194 689 3H	►194 549 3H				
		£				27.50	31.50				
deep groove ball bearing	20 mm	Ref.						►194 557 3H	►194 565 3H	►194 603 3H	
		£						44.00	47.00	55.00	
plain bearing	10 mm	Ref.	►194 832 3H	►194 840 3H	►194 859 3H						
		£	3.00	4.30	5.50						
plain bearing	15 mm	Ref.				►194 867 3H	►194 697 3H	►194 700 3H			
		£				5.00	14.75	20.00			
plain bearing	20 mm	Ref.				►194 875 3H			►194 719 3H	►194 743 3H	
		£				11.00			24.00	35.00	
plain bearing	25 mm	Ref.									►194 778 3H
		£									55.00

Free delivery to UK mainland for over 80,000 products.

UK
Ireland 01442 238 000
1 800 677 300

KAISER+KRAFT