

1–3 | LIGHT clamping bars

- Can be used horizontally and vertically
- Infinitely variable adjustment range
- Fitted with rubber feet on both sides

Material: aluminium. Max. load: 200 daN.

Adjustment range: 2100 – 2470 mm.

1 | Ref. 532 205 6F £ 74.90

Adjustment range: 2350 – 2720 mm.

2 | Ref. 532 206 6F £ 79.90

Adjustment range: 2650 – 3020 mm.

3 | Ref. 532 207 6F £ 82.90



4–5 | PAT interior locking bars, aluminium

- Horizontal securing of mesh pallets, cardboard boxes, and much more, on lorries and trailers
- Easy handling makes work fast
- 400 daN holding force for more safety

Material: aluminium.

Adjustment range: 2290 – 2520 mm. Max. load: 1000 daN.

4 | Ref. 532 203 6F £ 155.00

Adjustment range: 2400 – 2700 mm. Max. load: 400 daN.

5 | Ref. 532 204 6F £ 119.00



6–10 | MT non-slip pads

- Especially suitable for Euro pallets (for placing underneath the outer pallet runners)
- Can be used multiple times due to PU-bonded rubber granulate and pure rubber

Material: rubber granulate, PU bound. Temperature resistance: –40 °C to +115 °C. Colour: black. Feature: non-slip. Surface: closed.



11–14 | MT non-slip matting

- Optimum friction values and multiple use through high binding agent proportion
- Also suitable for heavy loads and uneven vehicle floors

Material: rubber granulate, PU bound. Temperature resistance: –40 °C to +115 °C. Colour: black. Feature: non-slip.



	6	7	8	9	10
Width mm	80	100	100	125	200
Height mm	5	8	8	8	8
Length mm	240	100	200	180	300
Weight kg	12	13.6	14	15.3	12
Weight per item kg	0.08	0.07	0.14	0.15	0.4
Pack of pcs	150	200	100	100	30
Ref.	532 145 6F	532 147 6F	532 144 6F	532 143 6F	532 146 6F
£ / pack	69.90	79.90	64.90	62.90	57.90

	11	12	13	14
Width mm	125	150	150	250
Height mm	8	3	3	8
Length mm	5000	13600	20000	5000
Weight kg	8.5	11.6	16	8.5
Weight per item kg	4.25	5.8	8	8.5
Pack of pcs	2	2	2	1
Ref.	532 140 6F	532 141 6F	532 149 6F	532 139 6F
£ / pack	52.90	59.90	52.90	31.90



15 | Non-slip trays

- Can be used as a lay-on tray (for hazardous goods) or cover (non-slip mat) for Euro pallets
- Absorbs vibrations due to its thickness of 8 mm
- High sliding friction coefficient

Width: 800 mm. Height: 8 mm. Material: solid rubber. Temperature resistance: –40 °C to +115 °C. Colour: black. Length: 1200 mm. Weight: 12 kg. Feature: non-slip. Weight per item: 12 kg.

15 | Ref. 532 148 6F £ 139.00



16–17 | Wheel chocks, yellow

- Stable and durable
- Manufactured from high quality plastic, with integrated carrying handle

Material: plastic. Colour: yellow. Pack of: 2.

Length: 380 mm. Width: 160 mm. Height: 190 mm.

16 | Ref. 532 129 6F £/pack 47.90

Length: 470 mm. Width: 200 mm. Height: 230 mm.

17 | Ref. 532 130 6F £/pack 52.90



18 | Rubber wheel chocks, black

- Extremely stable and highly durable
- Grooved base for even better grip
- Integrated handle

Length: 380 mm. Width: 160 mm. Height: 190 mm. Material: rubber mixture. Colour: black. Pack of: 2.

18 | Ref. 532 131 6F £/pack 79.90