

**Elastic solid rubber tyres**

- On aluminium rim with non-marking tyres
- Low rolling resistance, quiet running
- Very smooth running, low rolling resistance

Wheel material: solid rubber fully elastic. Material of rim: aluminium. Housing material: steel. Type of mounting: with top plate. Wheel bearing: precision ball bearing. Temperature resistance: -20 °C to +70 °C. Housing surface: zinc plated. Shore hardness: 70 A. Feature: low rolling resistance / does not damage floors / non-marking.



Vulcanised running surface. Swivel bearing with double ball race, swivel bearing protection.

Wheel Ø	mm	100	100	125	125	160	200
Max. load at 4 km/h	kg	180	180	200	200	350	400
Wheel width	mm	40	40	40	40	50	50
Overall height	mm	125	128	155	158	190	235
Screw hole diameter	mm	9	11	9	11	11	11
Hub length	mm	41	41	41	50	60	60
Hub bore	mm	12	12	15	20	20	20
Design of wheel rims		spoke rim	spoke rim	spoke rim	spoke rim	honeycomb rim	honeycomb rim
Fixed castor plate dimensions	mm	105 x 80	135 x 105	105 x 80	135 x 105	135 x 110	135 x 110
Swivel castor plate dimensions	mm	105 x 80	135 x 105	105 x 80	135 x 105	135 x 110	135 x 110
Screw hole spacing	mm	80 x 60	105 x 75 - 80	80 x 60	105 x 75 - 80	105 x 80	105 x 80
<b>Structure</b>							
fixed castor	Ref.	▶969 174 3H	▶969 179 3H	▶969 183 3H	▶969 188 3H	▶969 193 3H	▶969 197 3H
	£	36.00	39.50	45.00	49.00	75.00	80.00
swivel castor	Ref.	▶969 172 3H	▶969 177 3H	▶969 181 3H	▶969 186 3H	▶969 190 3H	▶969 195 3H
	£	37.00	43.00	47.00	51.00	80.00	86.00
swivel castor with double stop	Ref.	▶969 173 3H	▶969 178 3H	▶969 182 3H	▶969 187 3H	▶969 191 3H	▶969 196 3H
	£	45.00	51.00	55.00	57.00	91.00	97.00
<b>Accessories</b>							
Wheels	Ref.	▶969 175 3H	▶969 175 3H	▶969 185 3H	▶969 189 3H	▶969 194 3H	▶969 198 3H
	£	29.50	29.50	35.00	36.00	51.00	56.00



Fixed castor



Swivel castor with double stop



Swivel castor



Wheels



High load capacity



Hard wearing

**Elastic solid rubber tyres**

- On aluminium rim
- Low rolling resistance, quiet running
- Very smooth running, low rolling resistance

Wheel material: solid rubber fully elastic. Material of rim: aluminium. Housing material: steel. Type of mounting: with top plate. Wheel bearing: precision ball bearing. Temperature resistance: -20 °C to +70 °C. Housing surface: zinc plated. Shore hardness: 70 A. Feature: low rolling resistance / does not damage floors.

Vulcanised running surface. Swivel bearing with double ball race, swivel bearing protection.

Wheel Ø	mm	80	100	100	125	125	160	200
Max. load at 4 km/h	kg	120	180	180	200	200	350	400
Wheel width	mm	38	40	40	40	40	50	50
Overall height	mm	100	125	128	155	158	190	235
Screw hole diameter	mm	9	9	11	9	11	11	11
Hub length	mm	40	41	41	41	50	60	60
Hub bore	mm	12	12	12	15	20	20	20
Design of wheel rims		spoke rim	spoke rim	spoke rim	spoke rim	spoke rim	honeycomb rim	honeycomb rim
Fixed castor plate dimensions	mm	105 x 85	105 x 80	135 x 105	105 x 80	135 x 105	135 x 110	135 x 110
Swivel castor plate dimensions	mm	105 x 85	105 x 80	135 x 105	105 x 80	135 x 105	135 x 110	135 x 110
Screw hole spacing	mm	80 x 60	80 x 60	105 x 75 - 80	80 x 60	105 x 75 - 80	105 x 80	105 x 80
<b>Structure</b>								
fixed castor	Ref.	▶969 201 3H	▶969 205 3H	▶969 210 3H	▶969 215 3H	▶969 219 3H	▶969 224 3H	▶969 228 3H
	£	33.00	31.50	37.00	41.00	43.00	69.00	75.00
swivel castor	Ref.	▶969 199 3H	▶969 203 3H	▶969 208 3H	▶969 212 3H	▶969 217 3H	▶969 221 3H	▶969 226 3H
	£	35.00	34.00	39.50	48.00	48.00	75.00	80.00
swivel castor with double stop	Ref.	▶969 200 3H	▶969 204 3H	▶969 209 3H	▶969 213 3H	▶969 218 3H	▶969 223 3H	▶969 227 3H
	£	40.00	39.50	49.00	51.00	54.00	80.00	94.00
<b>Accessories</b>								
Wheels	Ref.	▶969 202 3H	▶969 207 3H	▶969 207 3H	▶969 216 3H	▶969 220 3H	▶969 225 3H	▶969 229 3H
	£	26.00	23.00	23.00	33.00	34.00	46.00	52.00