

20–29 | Nylon wheels

- High maximum load
- Extremely durable
- Reinforced housing



Hard wearing



High load capacity

Swivel bearing with double ball race, swivel bearing protection.



Wheel material: nylon. Material of rim: nylon. Housing material: steel. Type of mounting: with top plate. Temperature resistance: -40 °C to +90 °C. Housing surface: galvanised and chrome-plated.



NEW

		20	21	22	23	24	25	26	27	28	29	
Wheel Ø	mm	100	100	125	150	200	100	100	125	150	200	
Max. load at 4 km/h	kg	450	450	550	850	900	500	500	600	900	900	
Wheel width	mm	35	35	45	50	50	35	35	45	50	50	
Overall height	mm	140	140	170	200	245	140	140	170	200	245	
Wheel bearing		plain bearing	plain bearing	plain bearing	plain bearing	plain bearing	ball bearing	ball bearing	ball bearing	ball bearing	ball bearing	
Screw hole diameter	mm	9	9	11	11	11	9	9	11	11	11	
Hub length	mm	40	40	50	60	60	40	40	50	60	60	
Screw hole spacing	mm	80 / 75 x 60 / 55	80 / 76 x 60	105 x 75 / 80	105 x 75 / 80	105 x 75 / 80	80 / 75 x 60 / 55	80 / 76 x 60	105 x 75 / 80	105 x 75 / 80	105 x 75 / 80	
Structure	Plate dimensions											
fixed castor	100 x 85 mm	Ref.	569 652 6F					569 649 6F				
		£	20.90					32.90				
fixed castor	135 x 114 mm	Ref.		569 658 6F	569 664 6F	569 670 6F			569 655 6F	569 661 6F	569 667 6F	
		£		36.90	38.90	40.90			39.90	42.90	48.90	
swivel castor	100 x 85 mm	Ref.	569 650 6F				569 647 6F					
		£	38.90				48.90					
swivel castor	135 x 110 mm	Ref.		569 656 6F	569 662 6F	569 668 6F			569 653 6F	569 659 6F	569 665 6F	
		£		48.90	52.90	52.90			52.90	59.90	64.90	
swivel castor with double stop	100 x 85 mm	Ref.	569 651 6F				569 648 6F					
		£	48.90				59.90					
swivel castor with double stop	135 x 110 mm	Ref.		569 657 6F	569 663 6F	569 669 6F			569 654 6F	569 660 6F	569 666 6F	
		£		59.90	62.90	74.90			67.90	74.90	82.90	
Accessories												
Nylon wheels		Ref.	645 389 6F	645 389 6F	193 100 6F	193 127 6F	193 143 6F	892 386 6F	892 386 6F	423 240 6F	423 241 6F	423 263 6F
		£	26.90	26.90	31.90	28.90	37.90	27.90	27.90	27.90	38.90	46.90

30–32 | Nylon wheels

- Smooth running, maintenance free
- Largely resistant against many thinned acid and alkaline solutions
- Hardwearing



Maintenance-free

Swivel bearing with double ball race.



Wheel material: nylon. Material of rim: nylon. Housing material: steel. Type of mounting: with bolt hole. Wheel bearing: roller bearing. Temperature resistance: -20 °C to +80 °C. Bolt hole diameter: 12 mm. Plate diameter: 70 mm. Housing surface: galvanised and chrome-plated.



		30	31	32
Wheel Ø	mm	80	100	125
Max. load at 4 km/h	kg	150	180	200
Wheel width	mm	35	38	38
Overall height	mm	100	125	155
Hub length	mm	40	40	50
Hub bore	mm	12	12	15
Structure				
swivel castor	Ref.	704 694 6F	704 697 6F	704 699 6F
	£	17.49	18.95	23.90
swivel castor with double stop	Ref.	704 696 6F	704 698 6F	704 700 6F
	£	27.90	27.90	34.90
Accessories				
Wheels	Ref.	892 157 6F	892 203 6F	892 254 6F
	£	10.49	12.95	17.49

Free delivery to UK mainland for over 70,000 products!

SALES FREEPHONE 0800 0234 771

KAISER+KRAFT