

Light duty roller conveyors, aluminium frame with plastic rollers

- Optimises the material flow in the company
- Modular system, making it individually adjustable
- A very low empty weight makes it suitable for flexible use

Design of frame: aluminium. Overall height: 70 mm. Roller Ø: 50 mm. Roller material: plastic. Max. load with 1 m frame support spacing: 200 kg.



Planning
Expertise



TRANSPORT

Track width	mm	300	300	300	500	500	500	600	600	600
Overall width	mm	340	340	340	540	540	540	640	640	640
Axle spacing	mm	62.5	75	100	62.5	75	100	62.5	75	100
Width of goods conveyed	mm	450	450	450	600	600	600	750	750	750
Installation length	mm	300	300	300	502	502	502	603	603	603
Tube length	mm	283	283	283	485	485	485	586	586	586
Type										
90° curve	Ref.		903 644 3H	903 857 3H		903 654 3H	903 858 3H		903 665 3H	903 859 3H
	£		415.00	395.00		709.00	609.00		809.00	679.00
straight 1 m	Ref.	903 860 3H	903 640 3H	903 635 3H	903 864 3H	903 650 3H	903 645 3H	903 869 3H	903 660 3H	903 656 3H
	£	237.00	201.00	179.00	275.00	237.00	201.00	297.00	237.00	201.00
straight 1.5 m	Ref.	903 861 3H	903 641 3H	903 636 3H	903 865 3H	903 651 3H	903 646 3H	903 870 3H	903 661 3H	903 657 3H
	£	319.00	285.00	237.00	395.00	319.00	275.00	415.00	349.00	285.00
straight 2 m	Ref.	903 862 3H	903 642 3H	903 637 3H	903 866 3H	903 652 3H	903 648 3H	903 871 3H	903 662 3H	903 658 3H
	£	415.00	359.00	305.00	505.00	415.00	359.00	549.00	459.00	395.00



Alternative versions, 45° curves and passages available on request.

Light duty roller conveyors, steel frame with plastic rollers

- Optimises the material flow in the company
- Modular system, making it individually adjustable
- A very low empty weight makes it suitable for flexible use

Design of frame: steel, zinc plated. Overall height: 70 mm. Roller Ø: 50 mm. Roller material: plastic. Max. load with 1 m frame support spacing: 200 kg.

Track width	mm	300	300	300	500	500	500	600	600	600
Overall width	mm	340	340	340	540	540	540	640	640	640
Axle spacing	mm	62.5	75	100	62.5	75	100	62.5	75	100
Width of goods conveyed	mm	450	450	450	600	600	600	750	750	750
Installation length	mm	300	300	300	502	502	502	603	603	603
Tube length	mm	283	283	283	485	485	485	586	586	586
Type										
90° curve	Ref.		903 614 3H	903 840 3H		903 624 3H	903 842 3H		903 634 3H	903 843 3H
	£		429.00	395.00		679.00	595.00		759.00	609.00
straight 1 m	Ref.	903 844 3H	903 609 3H	903 605 3H	903 848 3H	903 619 3H	903 615 3H	903 853 3H	903 629 3H	903 625 3H
	£	213.00	183.00	161.00	259.00	213.00	173.00	275.00	237.00	191.00
straight 1.5 m	Ref.	903 845 3H	903 610 3H	903 606 3H	903 849 3H	903 621 3H	903 616 3H	903 854 3H	903 631 3H	903 626 3H
	£	305.00	263.00	213.00	359.00	297.00	259.00	405.00	339.00	275.00
straight 2 m	Ref.	903 846 3H	903 611 3H	903 607 3H	903 851 3H	903 622 3H	903 617 3H	903 855 3H	903 632 3H	903 627 3H
	£	405.00	319.00	275.00	469.00	405.00	319.00	505.00	429.00	339.00



Dual frame supports

Material: rectangular steel pipe, galvanised.
Max. load: 200 kg.



Lightweight tripod frame supports, zinc plated

Material: zinc plated. Max. load: 100 kg.



Track width	mm	200	300	400	500	600
Height adjustment range						
330 – 480 mm	Ref.	977 617 3H	903 676 3H	977 622 3H	903 677 3H	903 878 3H
	£	131.00	131.00	131.00	131.00	131.00
380 – 580 mm	Ref.	977 618 3H	903 678 3H	977 623 3H	903 679 3H	903 879 3H
	£	131.00	131.00	131.00	131.00	131.00
470 – 750 mm	Ref.	977 619 3H	903 681 3H	977 625 3H	903 682 3H	903 880 3H
	£	147.00	147.00	147.00	147.00	147.00
580 – 950 mm	Ref.	977 620 3H	903 683 3H	977 626 3H	903 684 3H	903 881 3H
	£	147.00	147.00	147.00	147.00	147.00
730 – 1250 mm	Ref.	977 621 3H	903 685 3H	977 627 3H	903 686 3H	903 882 3H
	£	157.00	157.00	157.00	157.00	157.00

Track width	mm	300	500	600
Height adjustment range				
210 – 350 mm	Ref.	903 667 3H	903 668 3H	903 873 3H
	£	89.00	89.00	89.00
340 – 590 mm	Ref.	903 669 3H	903 670 3H	903 874 3H
	£	94.00	94.00	94.00
430 – 720 mm	Ref.	903 672 3H	903 673 3H	903 875 3H
	£	94.00	94.00	94.00
590 – 1080 mm	Ref.	903 674 3H	903 675 3H	903 877 3H
	£	100.00	100.00	100.00

Free delivery to UK mainland
for over 80,000 products.

UK
Ireland

01442 238 000
1 800 677 300

KAISER+KRAFT