



Special designs, 45° curves and passages available on request.



19–24 | Skate wheel conveyors

- Optimise the material flow in the company
- Modular system, making it individually adjustable
- A very low empty weight makes it suitable for flexible use

Design of frame: steel, zinc plated. Skate wheel material: steel, zinc plated. Max. load: 200 kg. Overall height: 69 mm.

		19	20	21	22	23	24
Track width	mm	300	300	300	500	500	500
Axle spacing	mm	50	75	100	50	75	100
Width of goods conveyed	mm	150 – 400	150 – 400	150 – 400	150 – 600	150 – 600	150 – 600
Length of goods conveyed	mm	150 – 1000	225 – 1000	300 – 1000	150 – 1000	225 – 1000	300 – 1000
Skate wheel arrangement		3 : 3	3 : 3	3 : 3	5 : 5	5 : 5	5 : 5
Overall width	mm	340	340	340	540	540	540
Type							
straight 1 m	Ref.	759 579 6F	759 574 6F	759 545 6F	759 594 6F	759 590 6F	759 584 6F
	£	215.00	179.00	159.00	309.00	239.00	209.00
straight 1.5 m	Ref.	759 580 6F	759 576 6F	759 547 6F	759 595 6F	759 591 6F	759 585 6F
	£	309.00	249.00	199.00	419.00	329.00	295.00
straight 2 m	Ref.	759 581 6F	759 577 6F	759 559 6F	759 596 6F	759 592 6F	759 586 6F
	£	389.00	299.00	275.00	519.00	399.00	359.00

25–30 | Light duty skate wheel conveyors, steel frame with plastic skate wheels

- Optimises the material flow in the company
- Modular system, making it individually adjustable
- A very low empty weight makes it suitable for flexible use

Design of frame: steel, zinc plated. Skate wheel material: plastic. Max. load: 200 kg. Overall height: 69 mm.

		25	26	27	28	29	30
Track width	mm	300	300	300	500	500	500
Axle spacing	mm	50	75	100	50	75	100
Width of goods conveyed	mm	150 – 400	150 – 400	150 – 400	150 – 600	150 – 600	150 – 600
Length of goods conveyed	mm	150 – 1000	225 – 1000	300 – 1000	150 – 1000	225 – 1000	300 – 1000
Skate wheel arrangement		3 : 3	3 : 3	3 : 3	5 : 5	5 : 5	5 : 5
Overall width	mm	340	340	340	540	540	540
Type							
straight 1 m	Ref.	903 480 6F	903 474 6F	903 491 6F	903 506 6F	903 501 6F	903 496 6F
	£	229.00	179.00	159.00	309.00	239.00	199.00
straight 1.5 m	Ref.	903 481 6F	903 475 6F	903 492 6F	903 508 6F	903 502 6F	903 497 6F
	£	309.00	259.00	209.00	409.00	329.00	295.00
straight 2 m	Ref.	903 482 6F	903 476 6F	903 494 6F	903 509 6F	903 503 6F	903 498 6F
	£	389.00	309.00	275.00	519.00	399.00	359.00

31–34 | ° curves

- Modular system facilitates rapid material flow
- High quality workmanship
- Ideal supplement in a conveyor system

Overall height: 69 mm. Curve: 90°. Radius of curve: 800 mm. Roller Ø: 48 mm. Design of frame: steel, zinc plated. Max. load with 1 m frame support spacing: 200 kg.

		31	32	33	34
Track width	mm	300	300	500	500
Axle spacing	mm	75	100	75	100
Overall width	mm	340	340	540	540
Length of goods conveyed	mm	225 – 1000	300 – 1000	225 – 1000	300 – 1000
Skate wheel arrangement		3 : 3	3 : 3	5 : 5	5 : 5
Width of goods conveyed	mm	150 – 400	150 – 400	150 – 600	150 – 600
Skate wheel material					
plastic	Ref.	903 479 6F	903 473 6F	903 505 6F	903 500 6F
	£	329.00	289.00	429.00	359.00
steel, zinc plated	Ref.	759 583 6F	759 573 6F	759 599 6F	759 588 6F
	£	329.00	275.00	429.00	359.00

Free delivery to UK mainland for over 70,000 products!

SALES FREEPHONE 0800 0234 771

KAISER+KRAFT