

Premium assembly trolleys, ESD

- Ergonomic – comfortable working and push handle height
- Durable – permanently welded construction
- ESD model, zinc plated and with electrically conductive castors

Max. load: 500 kg. Height: 1120 mm. Working height: 895 mm. Number of levels: 2. Shelf heights: 275 / 895 mm. Platform material: steel, zinc plated. Frame material: steel. Worktop material: sheet steel, galvanised. Wheel fittings: 2 swivel castors with wheel stop, 2 fixed castors. Wheel type: solid rubber. Wheel Ø: 200 mm. Wheel bearing: roller bearing. Push handle height: 1105 mm. Colour: zinc plated.

Platform length: 1050 mm. Platform width: 700 mm. Length: 1195 mm. Width: 700 mm.

►Ref. 659 802 3H £ 479.00

Platform length: 1250 mm. Platform width: 800 mm. Length: 1395 mm. Width: 800 mm.

►Ref. 659 810 3H £ 469.00

All items on this page

EUROKRAFT
pro
by KAISER+KRAFT

10
Year
Guarantee



Prevent damage from electrostatic discharge in production, storage, dispatch, etc.

NEW



Premium general purpose trolleys, ESD model

- Oil and waterproof welding
- Easy to move even with heavy loads
- ESD model with electrically conductive coating and electrically conductive castors

Platform length: 900 mm. Platform width: 500 mm. Length: 1055 mm. Width: 508 mm.

Height: 1140 mm. Platform material: sheet steel, powder coated. Frame material: steel. Wheel fittings: 2 swivel castors with wheel stop, 2 fixed castors. Wheel type: solid rubber. Wheel Ø: 160 mm. Wheel bearing: roller bearing. Push handle height: 1120 mm. Raised edge: 40 mm. Colour: light grey RAL 7035.

Max. load: 250 kg. Number of levels: 2. Shelf heights: 220 / 875 mm.

►Ref. 659 814 3H £ 279.00

Max. load: 350 kg. Number of levels: 3. Shelf heights: 220 / 560 / 875 mm.

►Ref. 659 816 3H £ 345.00

Premium ESD shelf trucks

- Easy to move and manoeuvrable
- Highly versatile
- ESD model with electrically conductive castors and electrically conductive coating

Max. load: 500 kg. Platform length: 1015 mm. Platform width: 680 mm. Length: 1210 mm.

Width: 740 mm. Height: 1780 mm. Max. load per platform: 50 kg. Base plate: sheet steel, galvanised. Material: steel, powder coated. Colour: light grey RAL 7035.

Wheel fittings: 2 swivel castors with wheel stop, 2 fixed castors. Wheel Ø: 200 mm.

Wheel type: solid rubber. Adjustment pattern for internal shelves: 50 mm. Mesh width for end face: 50 x 50 mm. Mesh width for rear wall: 50 x 50 mm. Loading height: 280 mm. Wheel bearing: roller bearing. Frame colour: light grey RAL 7035. Frame material: sheet steel, galvanised. Feature: lockable.

Type of shelf trolley: with lockable double doors. Number of levels: 2. Weight: 100 kg.

►Ref. 659 553 3H £ 839.00

Type of shelf trolley: with lockable double doors and shelves. Weight: 131 kg. Platform colour: zinc plated. Platform material: sheet steel, galvanised.

►Ref. 659 561 3H £ 1120.00

