

Crash guards

- Compliant with EN 15635 and BGR 234 guidelines

Colour: black / yellow. Material: steel. Type of mounting: floor attachment. Panel thickness: 6 mm.

In accordance with EN 15635 and the BGR 234 guidelines, crash guards must be installed in front of uprights at the beginning and end of shelving units located in transport areas.

Shape		L-shaped	L-shaped	L-shaped	U-shaped	U-shaped
Overall width	mm	160	160	180	245	281
Overall height	mm	800	1200	400	400	400
	Ref.	▶171 374 3H	▶171 373 3H	▶171 372 3H	▶171 370 3H	▶179 244 3H
	£	235.00	335.00	52.00	62.00	99.00



Shelf unit crash protection guards with guide rollers

- Optimum protection against damage to shelving units and logistics equipment
- The guide rollers deflect the majority of the impact force resulting from a crash

Overall width: 160 mm. Overall height: 400 mm. Colour: traffic yellow RAL 1023 / jet black RAL 9005. Material: steel. Type of mounting: for bolting in place. Panel thickness: 6 mm. Overall depth: 160 mm.

Shape		L-shaped	U-shaped
	Ref.	122 518 3H	122 519 3H
	£	113.00	173.00



Crash protection guards

- Protect against damage to warehouse doors, fire doors and safety doors
- Yellow/black warning stripes for effective visual warning

Shape: L-shaped. Overall height: 150 mm. Colour: traffic yellow RAL 1023 / jet black RAL 9005. Material: steel. Finish: plastic coated. Type of mounting: for bolting in place. Panel thickness: 6 mm. Overall depth: 100 mm.

Overall length	mm	800	1200
	Ref.	122 520 3H	122 522 3H
	£	137.00	183.00



Free delivery to UK mainland for over 80,000 products.

UK
Ireland

01442 238 000
1 800 677 300

KAISER+KRAFT