



Display pallets and half pallets

- Ideal load carrier for small consignments
- Low empty weight, perforated top deck
- Durable

Material: high-pressure recycled polyethylene.
Colour: charcoal. Type: nestable. Temperature resistance: -30 °C to +80 °C.



Lightweight pallet without non-slip edges available on request.

Lightweight pallets

- 5 mm high non-slip edges secure the load against slipping
- Saves space in storage and during empty transport (nestable)
- Low empty weight, perforated top deck

Material: recycled polyethylene. Length: 1200 mm.
Width: 800 mm. Height: 140 mm. Colour: charcoal.
Max. load static: 2500 kg. Max. load dynamic: 1200 kg.

Length	mm	600	800	800
Width	mm	400	600	600
Height	mm	150	115	140
Max. load static	kg	500	1500	3000
Max. load dynamic	kg	200	500	600
Weight per item	kg	2.5	2.5	3.6
Pack of	pcs.	5	5	20
From				
1 pack	Ref.	516 495 3H	516 498 3H	►603 617 3H
	£ / pack	67.00	100.00	549.00
5 pack	Ref.	516 496 3H	516 497 3H	►603 618 3H
	£ / pack	61.00	94.00	515.00

Type: 9 feet. Weight: 5.8 kg. Fork entry option: 4-way.
Forklift access height: 100 mm. Forklift access width short side: 590 mm. Forklift access width long side: 700 mm.
Temperature resistance: -20 °C to +70 °C.

Ref. 453 814 3H **£ 29.50**

From: 20.

Ref. 453 815 3H **£ 27.50**



Euro stacking pallets

- Saves space (nestable) in storage and during empty transport
- Very high strength and a low weight
- Long lasting and returns your investment quickly

Material: recycled polyethylene. Length: 1200 mm.
Width: 800 mm. Height: 140 mm. Colour: charcoal.
Max. load static: 4000 kg. Max. load dynamic: 1200 kg.

Weight: 13 kg. Fork entry option: 4-way. Forklift access height: 100 mm. Forklift access width short side: 570 mm. Forklift access width long side: 710 mm. Temperature resistance: -30 °C to +70 °C.

Type: closed.

Ref. 538 730 3H **£ 45.00**

From: 10.

Ref. 538 733 3H **£ 39.50**



Industrial stacking pallets

- Saves space (nestable) in storage and during empty transport
- Long lasting and returns your investment quickly
- Very high strength and a low weight

Material: recycled polyethylene. Length: 1200 mm.
Width: 1000 mm. Height: 140 mm. Colour: charcoal.
Max. load static: 4000 kg. Max. load dynamic: 1200 kg.
Type: perforated. Weight: 10.2 kg. Fork entry option: 4-way.

Forklift access height: 100 mm. Forklift access width short side: 550 mm. Forklift access width long side: 810 mm. Temperature resistance: -20 °C to +70 °C.

► **Ref. 572 345 3H** **£ 78.00**

From: 10.

► **Ref. 572 346 3H** **£ 72.00**



Disposable Euro pallets made of recycled PO

- Cannot be washed, resistant to insects, bacteria and fungi
- Ideal for use indoors
- Low weight – also suitable for air freight

Material: recycled plastic / polyolefin. Length: 1200 mm.
Width: 800 mm. Height: 140 mm. Colour: black. Max. load static: 2800 kg. Max. load dynamic: 1200 kg. Type: 9 feet. Weight: 75 kg. Fork entry option: 4-way. Forklift access height: 101 mm. Forklift access width short side: 601 mm.

Forklift access width long side: 809 mm. Temperature resistance: 0 °C to +60 °C. Weight per item: 7.5 kg. Pack of: 10.

► **Ref. 523 234 3H** **£ /pack 247.00**

From: 3 pack.

► **Ref. 523 235 3H** **£ /pack 215.00**

