



Justrite

Small FM safety cupboards

- For the storage of flammable and water hazardous liquids according to FM (please observe country-specific regulations)
- Effective storage directly at the workstation
- Quick, direct access to frequently used media

Material: sheet steel, powder coated. Hazard class: for water hazardous liquids in GHS categories 1 – 4. Body colour: yellow. Door colour: yellow. Door type: hinged door. Lock type: three point locking. Number of shelves: 1. Shelf material: sheet steel, galvanised. Max. shelf load: 159 kg. Number of sump trays: 1.

These cupboards are not approved for the storage of flammable media in Germany, Switzerland, Austria, the Netherlands, Belgium, and Luxembourg.

Please observe the regulations and requirements binding for your country.

Please contact your responsible authority to determine approval for your application.

External width	mm	432	432	591	591	889	889
External height	mm	559	559	889	889	889	889
External depth	mm	432	432	457	457	559	559
Internal width		349					
Internal height		470					
Internal depth		349					
Door version		manual	self-closing	manual	self-closing	manual	self-closing
Number of doors	pcs.	1	1	1	1	2	2
Shelf height adjustment increments	mm			76	76	76	76
Base sump tray capacity	l	6	6	10	10	18.5	18.5
	Ref.	▶424 758 3H	424 760 3H	▶424 762 3H	424 764 3H	424 767 3H	424 769 3H
	£	659.00	879.00	799.00	1060.00	1260.00	1460.00
Accessories							
Shelves	Ref.	516 574 3H	516 574 3H	516 576 3H	516 576 3H	516 578 3H	516 578 3H
	£	49.00	49.00	64.00	64.00	107.00	107.00



Fire resistant hazardous goods wall-mounted cupboards type 30

- For regulation compliant storage of small quantities of flammable liquids in workshops in accordance with EN 14470-1 and TRGS 510
- Flammable liquids such as spray cans, paints, etc. can be stored safely directly at the workstation – e.g. above the worktop
- Quick access – saves time and ensures safety at the workplace

Weight: 76.68 kg. Body colour: charcoal RAL 7016. Door colour: charcoal RAL 7016. Door type: hinged door. Number of doors: 2. Number of sump trays: 1. Base sump tray capacity: 5 l.

Lock type: without lock.

Ref. 118 465 3H £ 1020.00

Lock type: profile cylinder lock.

Ref. 118 466 3H £ 1180.00

Fire resistance: 30 minutes. External width: 995 mm. External height: 482 mm. External depth: 470 mm. Internal width: 942 mm. Internal height: 414 mm. Internal depth: 419 mm. Material: sheet steel, powder coated. Hazard class: for flammable media in work rooms in accordance with DIN EN 14470-1 and TRGS 510 (appendix 3). Ventilation: ventilation connection (NW 75).

Shelves for safety box

Material: sheet steel. Max. load: 75 kg.

Ref. 118 468 3H £ 78.00

With profile cylinder lock