Eye wash bottles with sterile sodium chloride solution (saline solution)

- For rinsing out foreign particles fast and easy to use
- Bottle with ergonomically shaped eye cup and dust cap
- Compliant with EN 15154-4 unopened bottles have a 3 year shelf life

Cylinder capacity: saline solution. Conforms to: DIN EN 15154-4. Area of application: for rinsing out foreign particles. Pack of: 3.

Capacity: 200 ml. Scope of delivery: 3 x 200 ml.

▶Ref. 111 605 3H £/pack 44.00

Capacity: 500 ml. Scope of delivery: 3 x 500 ml.

▶Ref. 111 606 3H £/pack 54.00

Eye wash bottles with sterile phosphate buffer solution

- For neutralising acids and many alkaline substances fast and easy to use
- Bottle with ergonomically shaped eye cup and dust cap
- Compliant with EN 15154-4 unopened bottles have a 3 year shelf life

Capacity: 200 ml. Cylinder capacity: phosphate buffer solution. Scope of delivery: 3 x 200 ml. Conforms to: DIN EN 15154-4. Area of application: for neutralising acids. Pack of: 3.

▶Ref. 111 607 3H £/pack 54.00



Video





Emergency wall boxes with eye wash bottles

- · Easy and fast use for eye injuries
- Bottle with ergonomically shaped eye cup and dust cap
- Compliant with EN 15154-4 unopened bottles have a 3 year shelf life

Conforms to: DIN EN 15154-4. Height: 270 mm. Width: 225 mm. Depth: 110 mm. Type of mounting: wall mounting.

Capacity: 700 ml. Cylinder capacity: sodium chloride solution / sterile phosphate buffer solution, pH neutral. Scope of delivery: 1 x 500 ml sodium chloride solution, 1 x 200 ml sterile phosphate buffer solution, pH-neutral. Area of application: for neutralising acids / for rinsing out foreign particles.

▶Ref. 111 608 3H £ 71.00

Capacity: 1000 ml. Cylinder capacity: sodium chloride solution. Scope of delivery: 2 x 500 ml sodium chloride solution. Area of application: for rinsing out foreign particles.

▶Ref. 111 609 3H £ 71.00





Hand eye showers with one spray head

- Effective first aid for foreign particles in the eye, burns, irritations, scalding etc.
- Compliant with EN 15154-1/2 and DIN 12899, including information signs, connects to an existing cold drinking water supply
- Shower heads with large area water distribution/soft jet, rubber caps around the spray heads

Max. pressure up to: 6 bar. Thread: 1/2 inch. Height: 260 mm. Depth: 75 mm. Hose length: 1.5 m. Water flow: 6 l/min. Material: brass / plastic. Type of mounting: wall mounting. Min. pressure: 2 bar.

Colour: green.

▶Ref. 177 084 3H £ 219.00

Colour: red.

▶Ref. 177 085 3H £ 219.00

Body and eye emergency showers

- Central and effective first aid for foreign particles in the eye, burns, irritations, scalding etc.
- Compliant with EN 15154-1/2 and DIN 12899, including information signs, connects to an existing cold drinking water supply
- Shower heads with large area water distribution/ soft jet, rubber caps around the spray heads

Max. pressure up to: 6 bar. Thread: 1 inch. Height: 2230 mm. Depth: 855 mm. Water flow: 30 l/ min. Material: powder coated stainless steel / plastic. Type of mounting: floor attachment. Min. pressure: 4 bar.

Colour: green.

▶Ref. 177 088 3H £ 819.00

Colour: red.

▶Ref. 177 089 3H £ 819.00





Eye showers with basin and two spray heads

- Effective first aid for foreign particles in the eye, burns, irritations, scalding etc.
- Compliant with EN 15154-1/2 and DIN 12899, including information signs, connects to an existing cold drinking water supply
- Shower heads with large area water distribution/soft jet, rubber caps around the spray heads

Max. pressure up to: 6 bar. Thread: 1/2 inch. Height: 260 mm. Depth: 395 mm. Water flow: 12 l/min. Material: powder coated stainless steel / plastic. Type of mounting: wall mounting. Min. pressure: 2 bar.

Colour: green.

▶Ref. 177 086 3H £ 385.00

Colour: red.

▶Ref. 177 087 3H £ 385.00

Body emergency showers

- Effective first aid for burns, irritations, scalding etc.
- Compliant with EN 15154-1/2 and DIN 12899, including information signs, connects to an existing cold drinking water supply
- Shower heads with large area water dissipation and soft water jet

Max. pressure up to: 6 bar. Thread: 1 inch. Height: 600 mm. Depth: 685 mm. Water flow: 30 l/min. Material: powder coated stainless steel / plastic. Type of mounting: wall mounting. Min. pressure: 2 bar.

Colour: green.

▶Ref. 177 090 3H £ 439.00

Colour: red.

▶Ref. 177 092 3H £ 439.00



01442 238 000 1 800 677 300