



Industrial rubber

- Hardness: Shore A, 68°
- Tensile strength: 3.0 MPa
- Elongation at break: 200 %

Width: 1400 mm. Material: rubber. Temperature resistance: -10 °C to +60 °C. Colour: black. Type: closed. Work area: dry. Surface: closed. Form of delivery: cuts per metre.



More products online!

Height	mm	1.5	3	4.5	6	8	10	20	25
Max. roll length	m	10	10	10	10	5	5	5	5
Weight	kg	3.36	6.72	10	13.44	17.92	21	44.8	56
Weight	kg/m ²	2.4	4.80	7.14	9.60	12.80	15.00	32.00	40.00
	Ref.	123 955 3H	123 956 3H	123 957 3H	123 882 3H	123 883 3H	123 884 3H	123 885 3H	123 886 3H
	£ / m	27.00	42.00	65.00	70.00	95.00	117.00	249.00	287.00



Chemical resistant

EPDM industrial rubber

- Chemical resistant
- Can be used to produce water resistant seals
- Elongation at break 300%

Width: 1400 mm. Material: rubber. Temperature resistance: -20 °C to +85 °C. Colour: black. Max. roll length: 10 m. Type: closed. Work area: dry. Surface: closed. Form of delivery: cuts per metre.

Height: 4.5 mm. Weight: 10.5 kg. Weight: 7.50 kg/m².

Ref. 123 888 3H £/m 101.00

Height: 1.5 mm. Weight: 3.15 kg. Weight: 2.25 kg/m².

Ref. 123 963 3H £/m 44.00

Height: 3 mm. Weight: 6.3 kg. Weight: 4.50 kg/m².

Ref. 123 964 3H £/m 76.00

Height: 6 mm. Weight: 12.6 kg. Weight: 9.0 kg/m².

Ref. 123 965 3H £/m 127.00



Chemical resistant

Industrial rubber, oil and chemical resistant

- Hardness: Shore A, 62°
- Tensile strength: 5.0 MPa
- Elongation at break: 200%

Width: 1400 mm. Material: rubber. Temperature resistance: -10 °C to +60 °C. Colour: black. Max. roll length: 10 m. Type: closed. Feature: oil resistant / chemical resistant. Work area: dry / oily. Surface: closed. Form of delivery: cuts per metre.

Height: 1.5 mm. Weight: 3.15 kg. Weight: 2.25 kg/m².

Ref. 123 961 3H £/m 44.00

Height: 3 mm. Weight: 6.3 kg. Weight: 4.50 kg/m².

Ref. 123 962 3H £/m 70.00

