



Articulated LED machine lamps IP65

- Robust design with integrated screw-on flange for harsh ambient conditions
- Powerful and concentrated light
- Dust and splash water protection IP65

Power: 12 watt. Bulb: LED.

Mains voltage: 100 – 240 V / 50 – 60 Hz.

Colour: silver grey. Protection type: IP65. Energy consumption: 13.2 kWh/1000h. Mains cable: 1.5 m. Light head: tilting / rotating. Head material: aluminium extruded profile. Light head Ø: 130 mm. Luminous flux: 1260 lumen. Lamp head height: 120 mm. Weight: 2.9 kg. Colour temperature: 6000 K. Material: aluminium extruded profile / cast aluminium / tubular steel / glass fibre reinforced plastic.

► Ref. 611 704 3H £ on request

Table clamp

► Ref. 615 932 3H £ 32.50

All luminaires subject to technical modifications based on EU regulations (EU) 2019/2020 and (EU) 2019/2015. More data can be found in our webshop.



LED spotlights with flexible arm IP20

- Bright, concentrated light directly at the workstation
- Flexible and robust 520 mm long metal spiral tube for fast and flexible positioning of the light
- Suitable for universal use at workplaces and machines with normal ambient conditions

Power: 4,5 watt. Bulb: LED. Mains voltage: 100 – 240 V / 50 – 60 Hz. Colour: black. Protection type: IP20. Energy consumption: 5 kWh/1000h. Mains cable: 1.8 m. Light head Ø: 75 mm. Ballast model: integrated LED drivers. Service life: 50000 hrs. Luminous flux: 630 lumen. Lamp head depth: 120 mm. Max. brightness: 14000 lux. Luminous colour: daylight white. Colour temperature: 5700 K. Material: glass fibre reinforced plastic / metal. Beam angle: 30 °. Colour reproduction index: 80.

Lamp base: with screw-on base. Weight: 1.06 kg.

► Ref. 701 313 3H £ on request

Lamp base: with magnetic base. Weight: 1.7 kg.

► Ref. 701 314 3H £ on request

Table clamps

► Ref. 760 113 3H £ 19.50

LED magnifying lamps

- Symmetrical light distribution
- Large 3 dioptries glass lens – 175% magnification
- Robust metal sprung swivel arm

Bulb: LED. Mains voltage: 100 – 240 V / 50 – 60 Hz. Colour: white. Frame material: metal. Protection type: IP20. Mains cable: 2.0 m. Lamp base: with table clamp. Axes: 6. Light head: 3D joint. Head material: ABS plastic. Service life: 50000 hrs. Luminous colour: neutral white. Colour temperature: 5000 K. Arm length: 455/455 mm. Material: plastic / metal. Beam angle: 120 °.

Power: 12 watt. Energy consumption: 13.2 kWh/1000h. Lens Ø: 150 mm. Lamp head width: 198 mm. Light head Ø: 198/250 mm. Luminous flux: 1500 lumen. Lamp head height: 32 mm. Lamp head depth: 250 mm. Max. brightness: 4000 lux. Weight: 2.5 kg.

► Ref. 667 008 3H £ 299.00

Power: 6 watt. Energy consumption: 6.6 kWh/1000h. Lens Ø: 120 mm. Lamp head width: 167 mm. Light head



Ø: 167/205 mm. Luminous flux: 750 lumen. Lamp head height: 26 mm. Lamp head depth: 205 mm. Max. brightness: 1950 lux. Weight: 2.33 kg. Colour reproduction index: 90.

► Ref. 760 141 3H £ on request



8 W LED machine lighting

- With high light output for industrial and machine workplaces
- Light head remains cool when used continuously
- Dust and splash water protection IP54

Power: 8 watt. Bulb: LED. Mains voltage: 220 – 240 V / 50 – 60 Hz. Colour: silver grey. Protection type: IP54. Energy consumption: 8.8 kWh/1000h. Mains cable: 2.0 m. Lamp head width: 178 mm. Axes: 5. Light head: tilting / rotating. Head material: aluminium profile. Ballast model: integrated LED drivers. Luminous flux: 1400 lumen. Lamp head height: 65 mm. Lamp head depth: 175 mm. Max. brightness: 1500 lux. Weight: 2.9 kg. Luminous colour: neutral white. Colour temperature: 5000 K. Material: aluminium / plastic. Beam angle: 100 °. Colour reproduction index: 80.

► Ref. 760 131 3H £ on request

Table clamp

► Ref. 760 120 3H £ 20.50

Wall bracket

► Ref. 760 121 3H £ 15.00



MAG PRO LED hand torches

- Infinite dimmer function 10 – 100%
- COB LEDs main light (up to 600 lumen) and spot light (150 lumen)
- Light head pivots by 180°

Type of spot lamp: handheld light. Bulb: COB LED. Luminous flux: 60-600 lumen. Max. brightness: 900 lux. Illuminates up to: 30/45 m. Luminous colour: daylight white. Colour temperature: 6000 K. Colour reproduction index: 80. Power supply: operated by rechargeable battery. Battery version: lithium ion rechargeable battery. Rechargeable battery voltage: 3,7 V. Battery capacity: 2.6 Ah. Charging time: 4 hrs. Mains voltage: 100 – 240 V / 50 – 60 Hz. Protection type: IP54. Length: 270 mm. Width: 70 mm. Height: 65 mm. Weight: 0.33 kg. Material: ABS plastic. Colour: blue.

Ref. 539 537 3H £ 66.00