



QUIPO

★★★

5

Year
Guarantee

Cable reels

- Complete with cable and safety plug
- Dust and splash water protection to IP42

Housing material: impact resistant plastic. Length: 350 mm. Width: 180 mm. Height: 325 mm. Protection type: IP42. Cable type: H07RN-F3G. Cable cross section: 1.5 mm².

Cable length: 10 m.

►Ref. 176 341 3H £ 193.00

Cable length: 15 m.

►Ref. 176 342 3H £ 205.00

Cable length: 20 m.

►Ref. 176 343 3H £ 215.00



QUIPO

★★★

5

Year
Guarantee

Hose reels

- For compressed air and water – max. 20 bar / 60 °C
- Suitable for indoor and outdoor use
- Inexpensive model for medium duty applications

Area of application: for compressed air and water. Max. pressure up to: 20 bar. Housing material: impact resistant plastic. Fittings: flexible hose. Manual arresting mechanism.

Nominal hose diameter: DN 9. External connection: G 3/8 inch. Hose length: 9 m. Length: 383 mm. Width: 163 mm. Height: 309 mm.

►Ref. 176 333 3H £ 139.00

Nominal hose diameter: DN 6. External connection: G 1/4 inch. Hose length: 20 m. Length: 422 mm. Width: 191 mm. Height: 368 mm.

►Ref. 176 334 3H £ 173.00

Nominal hose diameter: DN 12. External connection: G 1/2 inch. Hose length: 15 m. Length: 487 mm. Width: 199 mm. Height: 411 mm.

►Ref. 176 335 3H £ 205.00

Nominal hose diameter: DN 9. External connection: G 3/8 inch. Hose length: 20 m. Length: 487 mm. Width: 199 mm. Height: 411 mm.

►Ref. 176 336 3H £ 215.00



Tripping hazards are one of the most frequent causes of accidents in workshops! Cable reels help to eliminate them.



Hose reels

- Includes a 20 m hose and multifunction nozzle
- Roll up mechanism for automatic, uniform retraction
- Connections compatible with water operated tools made by other manufacturers

Area of application: for water. Max. pressure up to: 10 bar. Nominal hose diameter: DN 12. External connection: G 1/2 inch. Hose length: 20 m. Housing material: impact resistant plastic. Length: 610 mm. Width: 247 mm. Height: 430 mm.

►Ref. 176 337 3H £ 215.00



Stainless steel hose reels

- Ideal for hygienically sensitive areas, wet environments, etc.
- Made of V2A stainless steel with multiple latches for optimum use at work
- Optionally available with dairy steam hose suitable for foodstuffs

Nominal hose diameter: DN 12. External connection: G 1/2 inch. Housing material: stainless steel V2A. Width: 200 mm.

Area of application		for water	for water	for water and steam	for water and steam
Max. pressure up to	bar	60	60	10	10
Hose length	m	10	15	8	12
Length	mm	460	490	460	490
Height	mm	460	490	460	490
Ref.		979 510 3H	979 513 3H	114 893 3H	114 894 3H
£		709.00	939.00	939.00	1180.00

