



Strapping

Professional PET strapping set

With semi-automatic tensioning and sealing device

The set consists of

- Mobile strap dispenser, painted, core Ø 200, 280 or 406 mm
- Rechargeable cordless strapping device, semi-automatic, sealing without seals
- Polyester strapping

All components can be re-ordered separately.

PET strapping (polyester)



- Very high tensile strength
- Minimal stretching
- Sealing: with or without seals
- Weather resistant, no sharp edges

Application

For pallets, heavy boxes, etc. Ideal for high volume strapping, quick and easy use.

Strap width	mm	12.7	16	19
Strap length	m	2500	2000	1200
Material thickness	mm	0.6	0.6	0.85
Tensile strength	kg/cm ²	321	401	650
Set	Ref.	611 273-1Y	611 274-1Y	611 275-1Y
	£	2598.00	2602.00	2609.00
Strap dispenser	Ref.	502 349-1Y	502 349-1Y	502 349-1Y
	£	259.00	259.00	259.00
Tensioning and sealing device	Ref.	918 956-1Y	918 956-1Y	918 956-1Y
	£	1944.00	1944.00	1944.00
PET strapping	Ref.	979 822-1Y	979 819-1Y	611 276-1Y
	£ / each	138.00	139.00	169.00



PET strapping set for demanding requirements

With fully automatic battery powered strapping device

The set consists of

- Mobile strap dispenser, zinc plated, core Ø 406 mm
- Threading rod which makes it easier to slide the strap underneath packages
- Rechargeable cordless strapping device for strap width 12 – 16 mm, fully automatic, sealing without sleeves
- Polyester strapping, width 16 mm, core Ø 406 mm, roll length 2000 m

All components can be re-ordered separately.



Strap width	mm	16
Strap length	m	2000
Material thickness	mm	0.6
Tensile strength	kg/cm ²	401
Set	Ref.	615 693-1Y
	£	4133.00
Strap dispenser	Ref.	985 437-1Y
	£	415.00
Battery powered strapping devices	Ref.	483 849-1Y
	£	3300.00
PET strapping	Ref.	979 819-1Y
	£ / each	139.00



Heavy duty PET set

With fully automatic battery powered strapping device

- Impact resistant full touch operating display and 3 colour information display
- Variable strapping speed, with strap alignment control
- Tensioning up to 4500 N
- For working with PP and PET strapping with width of 16 – 19 mm and thickness of 0.8 – 1.3 mm

The set consists of

- Mobile strap dispenser, zinc plated, core Ø 406 mm, incl. threading rod
- Rechargeable cordless strapping device for strap width 16 – 19 mm, fully automatic, sealing without sleeves
- 1 roll PET strapping, width 19 mm, length 1200 m

All components can be re-ordered separately.

Heavy duty strapping



- Highest tensile strength for heavy loads
- Extra wide strapping

Application

Heavy loads, e.g. in machine workshops, in metal, wood and building material industries.

Strap width	mm	19
Strap length	m	1200
Material thickness	mm	0.85
Tensile strength	kg/cm ²	650
Set	Ref.	522 131-1Y
	£	4329.00
Strap dispenser	Ref.	985 437-1Y
	£	415.00
Battery powered strapping devices	Ref.	483 852-1Y
	£	3550.00
PET strapping	Ref.	611 276-1Y
	£ / each	169.00



WORKSHOP

ALL ORDERS DELIVERED FREE
SALES FREE FAX: 0800 0234 983

KAISER + KRAFT
EVERYTHING FOR THE BUSINESS.

YELLOW =
5 working days