



Semi automatic battery powered strapping tools for PP, PET strapping

- Manual, semi automatic tensioning, sealing and cutting at the touch of a button
- With friction weld seal
- Suitable for mobile use

For strap width: 12 – 16 mm. For strap type: PP / PET. Tensioning type: semi-automatic. Sealing: no seals. For strapping thickness: 0,5 – 0,9 mm. Battery version: Li Po rechargeable battery. Max. strapping speed: 8 m/min. Tensioning force: 1500 N. Voltage: 14,8 V. Strength of current: 3 Ah. Length: 320 mm. Width: 140 mm. Height: 160 mm.

Ref. 493 682 3H £ 1980.00



Semi automatic battery powered strapping tools for PP, PET strapping

- Semi-automatic entry level model
- Light device, easy to program
- Sealing time and strap tension are adjusted using a touch sensitive keypad with digital display

For strap width: 12 – 16 mm. For strap type: PP / PET. Tensioning type: semi-automatic. Sealing: no seals. For strapping thickness: 0.5 – 1.05 mm. Battery version: Li Po rechargeable battery. Max. strapping speed: 12 m/min. Tensioning force: 2200 N. Voltage: 14.8 V. Strength of current: 2 Ah. Length: 290 mm. Width: 140 mm. Height: 165 mm.

Ref. 116 309 3H £ 2150.00



Battery powered strapping tools for PP and PET strapping

- Impact resistant full touch operating display and 3 colour information display
- With acoustic signal to prevent operating errors
- Variable strapping speed, with strap alignment control

For strap type: PP / PET. Tensioning type: fully automatic. Sealing: no seals. Battery version: lithium ion rechargeable battery. Voltage: 100 – 230 V. Length: 370 mm. Width: 141 mm. Height: 135 mm.

For strap width: 12 – 16 mm. For strapping thickness: 0,5 – 1 mm. Max. strapping speed: 220 mm/s. Tensioning force: 900 – 2500 N. Strength of current: 2 Ah.

Ref. 483 849 3H £ 3125.00

For strap width: 16 – 19 mm. For strapping thickness: 0,8 – 1,3 mm. Max. strapping speed: 120 mm/s. Tensioning force: 1300 – 4500 N. Strength of current: 4 Ah.

Ref. 483 852 3H £ 3250.00



Battery powered strapping tools for PP and PET strapping

- Manual, semi automatic and fully automatic tensioning, sealing and cutting
- With friction weld seal
- Suitable for mobile use

For strap width: 13 – 16 mm. For strap type: PP / PET. Tensioning type: fully automatic. Sealing: no seals. For strapping thickness: 0,5 – 1,05 mm. Battery version: Li Po rechargeable battery. Max. strapping speed: 0.26 m/s. Tensioning force: 2500 N. Voltage: 14,8 V. Strength of current: 2 Ah. Length: 300 mm. Width: 150 mm. Height: 160 mm.

Ref. 493 677 3H £ 2375.00