

15

Year
Guarantee



Video
online!



Hook-on platform for
accessories



MUNK
GÜNZBURGER STEIGTECHNIK

Professional hinged ladders

- Can be used as a step ladder, lean-to ladder or as a practical working platform when combined with the work platform
- Particularly easy reconfiguration in just a few simple steps
- Sturdy 4-part aluminium construction with strong box section struts

Access type: rungs. Frame material: aluminium. Rungs material: aluminium. Step width: 300 mm. Max. load: 150 kg.

Number of rungs	pcs.	10	12	14
Length as a lean-to ladder	mm	2850	3650	4200
Retracted length	mm	1000	1000	1230
Height as a step ladder	mm	1490	1760	2020
	Ref.	572 172 3H	572 173 3H	572 174 3H
	£	305.00	329.00	385.00
Accessories				
Hook-on platforms	Ref.	544 627 3H	544 627 3H	544 627 3H
	£	37.00	37.00	37.00

PREMIUM telescopic ladders

- One ladder – many options
- Particularly easy and safe handling
- Very robust due to 8-fold special riveting

Access type: rungs. Frame material: aluminium. Rungs material: aluminium.
Feature: folding. Depth folded: 210 mm. Max. load: 150 kg.

The foot extension element must be included with your order as an optional accessory for the models with 4 x 4 rungs or more to ensure use that is compliant with EN 131.

Number of rungs	pcs.	4 x 3	4 x 4	4 x 5	4 x 6
Length as a lean-to ladder	mm	2980	4200	5300	6400
Height as a step ladder	mm	1300	1850	2400	2900
	Ref.	►731 469 3H	►131 296 3H	►131 318 3H	►131 326 3H
	£	299.00	405.00	485.00	549.00
Accessories					
Foot extension elements	Ref.	—	591 886 3H	591 886 3H	591 886 3H
	£	—	137.00	137.00	137.00

KRAUSE

STABILO hinged ladders

- Patented safety lock hinge system with one-hand release bar (SpeedMatic system) for fast and convenient operation
- Two wide cross beams with anti-slip foot caps (Safety Cap)
- Lightweight and space saving storage

Access type: rungs. Rungs material: aluminium.
Width folded: 370 mm. Depth folded: 280 mm.
Rung spacing: 250 mm. Rung depth: 30 mm.
Conforms to: EN 131. Max. load: 150 kg.

Number of rungs	pcs.	4 x 3	4 x 4
Length as a lean-to ladder	mm	3550	4700
Retracted length	mm	1000	1300
Feature		with work platform	without work platform
Height as a step ladder	mm	1750	2250
	Ref.	569 353 3H	569 354 3H
	£	259.00	275.00



Stainless steel
locking pins



8-fold special
riveting



10

Year
Guarantee

WORKSHOP

Free delivery to UK mainland
for over 80,000 products.

UK
Ireland

01442 238 000
1 800 677 300

KAISER+KRAFT

751