



Other expansion options and platforms available on request.



Aluminium mobile access towers

- Flexible – platform can be inserted at different heights
- Compact – space saving transport dimensions
- Practical – innovative hinge system for fast unfolding and folding

Platform width: 0,60 m. Platform length: 1.80 m. Material: aluminium. Max. load: 750 kg. Wheel fittings: 4 swivel castors with wheel stops. Wheel Ø: 125 mm. Scaffolding width: 0.75 m. Scaffolding length: 2.0 m. Feature: folding. Conforms to: EN 1004.

Platform height	m	0,95	1,8	3,8	5,8
Working height	m	3	3.8	5.8	7.8
Tower height	m	1.83	2.8	4.8	6.8
Weight	kg	32	50	105	145.2
	Ref.	944 182 3H	944 183 3H	944 185 3H	727 746 3H
	£	689.00	1280.00	2075.00	3025.00



Please observe the required ballasting in accordance with the assembly and usage instructions.

Layher

Einfach sicher. Die Steigtechnik.

Aluminium mobile access tower

- Practical – folding base unit ready for use in just a few steps
- Compact – fits through standard room doors without having to be collapsed and when fully loaded
- Safe – with track girder for platform heights of 2.76 m or higher

Platform width: 0,75 m. Platform length: 1.8 m. Material: aluminium. Max. load: 200 kg/m². Wheel Ø: 150 mm. Feature: folding. Tube diameter: 48.3 mm. Conforms to: EN 1004.

Platform height	m	0,86	1,61	2,76	3,76	4,76	5,76
Working height	m	2.86	3.61	4.76	5.76	6.76	7.76
Tower height	m	1.83	2.83	3.98	4.98	5.98	6.98
Weight	kg	42	58	140.5	169.6	192.2	218
	Ref.	523 106 3H	523 127 3H	523 135 3H	523 141 3H	523 142 3H	523 143 3H
	£	869.00	1140.00	2300.00	2850.00	3175.00	3625.00