

Bicycle racks

- Space saving high/low bicycle positioning
- Prepared for anchoring to floor and connecting in rows

Material: steel. Finish: hot dip galvanised. Overall height: 415 mm. Type of mounting: for bolting in place with plugs or anchoring in place. Wheel spacing: 350 mm. Tyre width up to: 55 mm. Colour: zinc plated. Height above ground: 415 mm. Tube diameter: 18 mm.

Supplied flat pack – easy self-assembly.



From
€ 71.00
Ref. 928 009 3H



Suitable for bicycles with a maximum tyre width of 55 mm.

Other RAL colours available (extra cost).

Bicycle racks with advertising panels available on request.



WORKSHOP

		1	2	3	4	5	6	7
Parking spaces	pcs.	2	3	4	5	6	10	12
Overall width	mm	700	1050	1400	1750	2100	1750	2100
Overall depth	mm	550	550	550	550	550	710	710
Bicycle parking		single sided	single sided	single sided	single sided	single sided	double sided	double sided
Bay depth	mm	1850	1850	1850	1850	1850	3250	3250
High/low positioning	pcs.	1 / 1	2 / 1	2 / 2	3 / 2	3 / 3	5 / 5	6 / 6
Ref.		►928 009 3H	►706 806 3H	►928 010 3H	►706 648 3H	►706 649 3H	►706 650 3H	►706 651 3H
£		71.00	99.00	109.00	153.00	175.00	281.00	339.00

Ground assembly brackets

Pack of: 2.

►Ref. 114 222 3H **£/pack 15.25**

Ground anchors

Pack of: 2.

►Ref. 114 223 3H **£/pack 41.00**

Free delivery to UK mainland for over 80,000 products.

UK
Ireland

01442 238 000
1 800 677 300