



**MAUL**



## LED desk lamps

- With integrated wireless charger, Qi-certified – simply place your smartphone or smartwatch on the charging area and charging starts automatically
- Charge two devices simultaneously: by induction and by using the USB port (5 V, max. 500 mA)
- Illuminance dimmable in 3 levels, colour temperature adjustable in 3 levels

Lamp base: pedestal base. Energy consumption: 5 kWh/1000h. Bulb: LED. Power: 8 watt. Luminous colour: daylight white / warm white. Colour temperature: 3000 / 6500 K. Colour reproduction index: 81. Max. brightness: 1480 lux. Luminous flux: 733 lumen. Mains voltage: 100 – 240 V. Mains cable: 1.7 m. Service life: 20000 hrs. Protection type: II Euro plug power supply unit.

Colour: charcoal. Feature: dimmable. Light head: tilting. Fittings: inductive, Qi-certified charging function / USB port. Activation: touch sensor. Material: aluminium / plastic. Overall height: 410 mm. Arm length: 380 mm. Weight: 0.87 kg. Lamp head dimensions: 50 x 230 mm. Base dimensions: 110 x 180 mm.

**Ref. 587 966 3H £ on request**



**HANSA**  
by styro

## LED ceiling lamps

- Powerful, neutral-white light for optimal illumination of the room
- The lamp switches on immediately without flickering
- Glare free polycarbonate cover

Energy consumption: 40 kWh/1000h. Bulb: LED. Power: 40 watt. Luminous colour: neutral white. Colour temperature: 4100 K. Colour reproduction index: 84. Max. brightness: 500 lux. Luminous flux: 2956 lumen. Mains voltage: 100 – 265 V. Service life: 30000 hrs. Protection type: IP20. Colour: light grey. Material: metal, painted / plastic. Overall height: 46 mm. Overall width: 124 mm. Overall length: 1240 mm. Weight: 0.8 kg.

**► Ref. 178 040 3H £ 76.00**

**MAUL**

## LED floor lamps, dimmable

- Infinitely adjustable dimmer on the column according to activity and individual requirements
- Radiates approx. 50% upwards and approx. 50% downwards
- Double benefits: direct light for the work surface and indirect light for room lighting

Lamp base: with pedestal base. Energy consumption: 80 kWh/1000h. Bulb: LED. Power: 80 watt. Luminous colour: neutral white. Colour temperature: 4000 K. Colour reproduction index: 80. Max. brightness: 1800 lux. Luminous flux: 7100 lumen. Mains voltage: 200 – 240 V. Mains cable: 2.5 m. Service life: 20000 hrs. Protection type: I safety plug. Feature: dimmable. Light head: fixed. Material: metal / plastic. Overall height: 1960 mm. Overall width: 280 mm. Overall length: 610 mm. Weight: 11.8 kg. Lamp head dimensions: 280 x 610 mm. Base dimensions: 450 x 300 mm.

Colour: white aluminium RAL 9006.

**Ref. 540 137 3H £ 485.00**

Colour: signal white RAL 9003.

**Ref. 587 929 3H £ 485.00**



With sensor

## Sensor operated LED floor lamps, dimmable

- The motion sensor automatically dims the light after 30 minutes without detecting any motions. Shuts down after another 30 minutes when no motion is detected
- The daylight sensor regulates the light output by the lamp, and changes according to the level of light indoors
- Infinitely adjustable dimmer on the column according to activity and individual requirements

Energy consumption: 80 kWh/1000h. Bulb: LED. Power: 80 watt. Luminous colour: neutral white. Colour temperature: 4000 K. Colour reproduction index: 81. Max. brightness: 1920 lux. Luminous flux: 7200 lumen. Mains voltage: 200 – 240 V. Mains cable: 2.5 m. Service life: 20000 hrs. Protection type: I safety plug. Feature: dimmable. Light head: fixed. Material: aluminium / steel. Overall width: 280 mm. Overall length: 610 mm. Lamp head dimensions: 280 x 610 mm.

Lamp base: pedestal base. Overall height: 1960 mm. Weight: 11.8 kg. Base dimensions: 300 x 450 mm.

Colour: white aluminium RAL 9006.

**Ref. 540 129 3H £ 649.00**

Lamp base: clamp base. Colour: white aluminium RAL 9006. Overall height: 1200 mm. Clamp width: 15 – 95 mm. Weight: 5.94 kg.

**Ref. 540 133 3H £ 575.00**



**More Information**  
**kaiserkraft.co.uk**

Free delivery to UK mainland for over 80,000 products.

**UK**  
**Ireland**

**01442 238 000**  
**1 800 677 300**

**KAISER+KRAFT**

957

**OFFICE**