

Pallet trucks

- Distance across forks suitable for EURO pallets
- Precise, infinite lowering
- Low maintenance compact hydraulics with overload valve

Max. load: 2300 kg. Height: 1200 mm. Fork width: 160 mm. Steering radius: 210 °. Steering wheel material: polyurethane. Fork roller material: polyurethane. Fork roller version: tandem. Material: steel. Colour: signal blue RAL 5005. Finish: powder coated. Drawbar height: 1200 mm. Fittings: entry rollers / exit rollers. Feature: manual / mobile.



NEW

Lifting range		mm		55 – 195	85 – 195
Distance across forks		mm		540	520
Steering wheel diameter		mm		150	200
Fork roller diameter		mm		50	82
Length	Fork length	From			
1535 mm	1150 mm	1 pcs.	Ref.	► 659 200 3H	
			£	909.00	
1535 mm	1150 mm	3 pcs.	Ref.	► 659 211 3H	
			£	869.00	
1885 mm	1500 mm	1 pcs.	Ref.		► 659 197 3H
			£		839.00
1885 mm	1500 mm	3 pcs.	Ref.		► 659 208 3H
			£		799.00
2185 mm	1800 mm	1 pcs.	Ref.		► 659 198 3H
			£		949.00
2185 mm	1800 mm	3 pcs.	Ref.		► 659 209 3H
			£		899.00
2385 mm	2000 mm	1 pcs.	Ref.		► 659 199 3H
			£		1020.00
2385 mm	2000 mm	3 pcs.	Ref.		► 659 210 3H
			£		989.00



QUIPO
★★★

5
Year
Guarantee

Pallet trucks

- With extra long forks: 2500 mm
- For simultaneous transport of two Euro pallets

Max. load: 2000 kg. Lifting range: 80 – 200 mm. Length: 2900 mm. Fork length: 2500 mm. Fork width: 153 mm. Distance across forks: 540 mm. Steering radius: 210 °. Weight: 110 kg. Steering wheel material: polyurethane. Fork roller material: polyurethane. Steering wheel diameter: 180 mm. Fork roller version: tandem. Fork roller diameter: 80 mm. Material: steel. Colour: melon yellow RAL 1028. Finish: powder coated. Drawbar height: 1240 mm. Wheel bearing: ball bearing. Feature: extra long / manual / mobile.

► Ref. 484 026 3H £ 989.00