

5 – 10 | Material lifter

- Exchangeable load support
- Optionally available with fixed castors or 4-way chassis
- Swivel castors with wheel stops

Overall length: 970 mm. Overall width: 506 mm. Overall height: 1265 mm. Clearance height: 75 mm. Material: steel. Feature: manual. Finish: powder coated. Colour: signal blue RAL 5005. Steering wheel diameter: 125 mm. Support leg length: 610 mm. Conforms to: DIN EN ISO 3691-5:2014. Lift per crank rotation: 130 mm.



Video
Online!



Available in most
RAL colours.
Only 10% extra.

	5	6	7	8	9	10
Type	platform / fixed castors	platform / 4-way chassis	spike / fixed castors	spike / 4-way chassis	adjustable box fork / fixed castors	adjustable box fork / 4-way chassis
Load suspension device LxW/Ø	mm 600 x 430	600 x 430	600 x 42	600 x 42	450 x 140 - 330	450 x 140 - 330
Max. load	kg 120	120	120	120	100	100
Load centre	mm 300	300	300	300	270	270
Lifting range	mm 80 – 945	80 – 945	120 – 985	120 – 985	110 – 970	110 – 970
Distance across forks	430	430				
Wheel fittings	2 swivel castors with wheel stops, 2 fork rollers	2 steering wheels with wheel stops, 2 swivel castors	2 swivel castors with wheel stops, 2 fork rollers	2 steering wheels with wheel stops, 2 swivel castors	2 swivel castors with wheel stops, 2 fork rollers	2 steering wheels with wheel stops, 2 swivel castors
Castor diameter front / rear	mm 70 / 125	35 / 125	70 / 125	35 / 125	70 / 125	70 / 125
Fork roller material	nylon	polyurethane	nylon	polyurethane	nylon	nylon
Ref.	522 654 6H	522 655 6H	522 656 6H	522 657 6H	569 591 6H	569 592 6H
€	689.00	699.00	689.00	699.00	729.00	759.00

14 – 16 | Lift trucks

- Can be moved as a truck for long routes
- Exact positioning on 4 wheels
- Exchangeable load supports

Overall length: 925 mm. Overall width: 575 mm. Overall height: 1265 mm. Clearance height: 75 mm. Material: steel. Feature: manual. Finish: powder coated. Colour: signal blue RAL 5005. Wheel fittings: 2 wheels, 2 swivel castors. Castor diameter front / rear: 35 / 200 mm. Fork roller diameter: 35 mm. Support leg length: 610 mm. Conforms to: DIN EN ISO 3691-5:2014. Lift per crank rotation: 130 mm. Wheel Ø: 200 mm.



11 | Box forks for material lifter and lift truck

Adjustment range: 140 – 330 mm.
Length: 450 mm.

11 | Ref. 569 590 6H € 125.00

12 | Platform for material lifter and lift truck

Length: 600 mm. Width: 430 mm. Max. load: 120 kg.

12 | Ref. 522 663 6H € 82.90

13 | Spike for material lifter and lift truck

Length: 600 mm. Max. load: 120 kg.
Diameter: 42 mm.

13 | Ref. 522 664 6H € 69.90



Video
Online!

	14	15	16
Type	with adjustable box fork	with platform	with spike
Load suspension device LxW/Ø	mm 450 x 140-330	600 x 430	600 x 42
Max. load	kg 100	120	120
Load centre	mm 270	300	300
Lifting range	mm 110 – 970	80 – 945	120 – 985
Fork roller material	nylon	polyurethane	polyurethane
Weight	kg 43.5	45.8	37.3
Ref.	569 593 6H	522 660 6H	522 661 6H
€	869.00	799.00	799.00



Available in most
RAL colours.
Only 10% extra.