

## 11 – 12 | ERGOBJÖRN TT-05 electric tow trucks

- Driver attendance check
- Comfort support rail
- Powerful 800 W motor

Weight: 160 kg. Tensile force: 500 kg. Overall length: 1425 mm. Overall width: 693 mm. Trailer load: 500 kg. Frame material: sheet steel. Climbing capability: 7 %. Voltage: 24 V. Pulling/pushing speed under load: 10,5 km/h. Wheel fittings: pneumatic tyres. Steering wheel diameter: 260 mm. Steering wheel width: 85 mm. Fixed wheel diameter: 320 mm.

- 11 | Frame colour: red.  
**Ref. 499 163 6H € 8000.00**
- 12 | Frame colour: white.  
**Ref. 499 164 6H € 8000.00**

 **More products online!**



Complete with coupling and 24 V, 14 A battery charger.

### 13 | Puncture proof tyres, extra cost

Wheel Ø: 320 mm. Material: solid rubber, non-marking. Roller Ø: 260 mm.

13 | **Ref. 499 167 6H € 255.00**

### 14 – 15 | TT-05 trailer

Frame material: sheet metal / steel. Overall length: 1352 mm. Loading height: 360 mm. Platform length: 845 mm. Platform width: 643 mm. Platform material: sheet metal. Max. load: 200 kg. Wheel type: pneumatic tyres. Wheel Ø: 260 mm. Wheel bearing: ball bearing. Wheel width: 85 mm.

15 | Colour: red.  
**Ref. 499 126 6H € 829.00**

14 | Colour: white.  
**Ref. 499 127 6H € 829.00**



### 16 – 17 | High performance charging devices

16 | Strength of current: 16.5 A.  
**Ref. 499 171 6H € 999.00**

17 | Strength of current: 20 A.  
**Ref. 499 173 6H € 999.00**

## 18 | TAKKTOR electric tow trucks

- Secured against unauthorised start-up
- Emergency off switch on the drawbar arm joint
- Coupling height 85 – 380 mm

Weight: 315 kg. Overall length: 740 mm. Overall width: 590 mm. Overall max. load: 2000 kg. Frame material: steel. Frame colour: charcoal RAL 7016 / lemon yellow RAL 1012. Wheel fittings: 2 drive wheels, 2 swivel castors. Steering wheel material: polyurethane. Steering wheel diameter: 100 mm. Steering wheel width: 32 mm. Running

wheel material: elastic. Fixed wheel diameter: 260 mm. Type of brakes.

18 | **Ref. 494 416 6H € 5300.00**



### 19 – 20 | Clip-on coupling system

Material: steel. Finish: zinc plated by galvanization. Length: 1450 mm. Width: 190 mm. Height: 680 mm.

19 | **Ref. 499 524 6H € 349.00**

20 | Minimum order quantity: 2 pcs.  
**Ref. 499 527 6H € 319.00**

**EUROKRAFT**  
 by KAISER+KRAFT *pro*




## 21 – 22 | Mobile Kanban shelf units

- Complete with 2 mesh shelves
- Non-slip articulated feet, height adjustable
- Platform tilts 0°, 8° and 16°

Max. load: 500 kg. Platform length: 1208 mm. Platform width: 808 mm. Length: 1280 mm. Width: 810 mm. Height: 1705 mm. Number of levels: 2. Max. load per platform: 200 kg. Material: steel. Colour: charcoal RAL 7016. Adjustment pattern for internal shelves: 150 mm. Loading height: 125 mm. Weight: 77 kg. Platform material: steel.

22 | **Ref. 499 523 6H € 969.00**

21 | Minimum order quantity: 2 pcs.  
**Ref. 499 526 6H € 889.00**

 Available in most RAL colours. Only 10% extra.

**EUROKRAFT**  
 by KAISER+KRAFT *pro*



### 23 – 24 | Wire mesh shelves

Width: 808 mm. Length: 1208 mm. Max. load: 200 kg. Material: steel. Colour: charcoal RAL 7016. Finish: powder coated. Thickness: 50 mm.

23 | **Ref. 499 525 6H € 175.00**

24 | Minimum order quantity: 5 pcs.  
**Ref. 499 528 6H € 159.00**



Forklift pockets 240 x 80 mm, fork entry clearance 350 mm.