



QUIPO

★★★

1–3 | Cable reels

- Complete with cable and safety plug
- Dust and splash water protection to IP42

Housing material: impact resistant plastic. Length: 350 mm. Width: 180 mm. Height: 325 mm. Protection type: IP42. Cable type: H07RN-F3G. Cable cross section: 1.5 mm².

1 | Cable length: 10 m.

Ref. 176 341 6H € 199.00

2 | Cable length: 15 m.

Ref. 176 342 6H € 239.00

3 | Cable length: 20 m.

Ref. 176 343 6H € 259.00



QUIPO

★★★



Tripping hazards are one of the most frequent causes of accidents in workshops! Cable reels help to eliminate them.

4–7 | Hose reels

- For compressed air and water – max. 20 bar / 60 °C
- Suitable for indoor and outdoor use
- Inexpensive model for medium duty applications

Area of application: for compressed air and water. Max. pressure up to: 20 bar. Housing material: impact resistant plastic. Manual arresting mechanism.

4 | Nominal hose diameter: DN 9. External connection: G 3/8 inch. Hose length: 9 m. Length: 383 mm. Width: 163 mm. Height: 309 mm.

Ref. 176 333 6H € 139.00

5 | Nominal hose diameter: DN 12. External connection: G 1/2 inch. Hose length: 15 m. Length: 487 mm. Width: 199 mm. Height: 411 mm.

Ref. 176 335 6H € 199.00

6 | Nominal hose diameter: DN 9. External connection: G 3/8 inch. Hose length: 20 m. Length: 487 mm. Width: 199 mm. Height: 411 mm.

Ref. 176 336 6H € 215.00

7 | Nominal hose diameter: DN 6. External connection: G 1/4 inch. Hose length: 20 m. Length: 422 mm. Width: 191 mm. Height: 368 mm.

Ref. 176 334 6H € 169.00



8 | Hose reels

- Includes a 20 m hose and multifunction nozzle
- Roll up mechanism for automatic, uniform retraction
- Connections compatible with water operated tools made by other manufacturers

Area of application: for water. Max. pressure up to: 10 bar.

Nominal hose diameter: DN 12. External connection: G 1/2 inch. Hose length: 20 m.

Housing material: impact resistant plastic. Length: 610 mm. Width: 247 mm.

Height: 430 mm.

8 | Ref. 176 337 6H € 215.00



9–12 | Stainless steel hose reels

- Ideal for hygienically sensitive areas, wet environments, etc.
- Made of V2A stainless steel with multiple latches for optimum use at work
- Optionally available with dairy steam hose suitable for foodstuffs

Nominal hose diameter: DN 12.

External connection: G 1/2 inch.

Housing material: stainless steel V2A.

Width: 200 mm.



	9	10	11	12
Area of application	for water	for water	for water and steam	for water and steam
Max. pressure up to	bar	60	60	10
Hose length	m	10	15	8
Length	mm	460	490	460
Height	mm	460	490	490
Ref.	979 510 6H	979 513 6H	114 893 6H	114 894 6H
€	729.00	959.00	959.00	1225.00