

1–3 | SEALKID film sealing devices

- Easy to use and cost effective
- Easy sealing and cutting of film pouches and sleeves
- With time limit switch and cutter

Film thickness max.: 2 x 0.2 mm.
Voltage: 230 V.



		1	2	3
Welding seam max.	mm	236 x 3	321 x 3	421 x 3
Height	mm	186	202	202
Width	mm	90	100	100
Length	mm	450	535	635
Power	watt	300	700	550
	Ref.	523 980 6H	523 981 6H	523 982 6H
	€	419.00	449.00	499.00

4 | FUTURA PORTABLE hand sealing tongs

- For quick sealing of films

Welding seam max.: 150 x 2 mm. Film thickness max.: 2 x 0.15 mm. Height: 95 mm.
Width: 180 mm. Length: 170 mm. Power: 35 watt.

4 | Ref. 979 904 6H € 219.00



5–6 | MAGNETA film sealing devices

- High-performance industrial device, adjustable sealing and cooling times
- Particularly easy to operate and ergonomically shaped cutting unit, incl. magnetic latch
- Ideal for serial production – very easy to use

Film thickness max.: 2 x 0.15 mm. Height: 250 mm. Width: 190 mm.

		5	6
Welding seam max.	mm	420	620
Length	mm	560	760
Power	watt	450	575
	Ref.	615 688 6H	615 689 6H
	€	799.00	1375.00

7–9 | ECO impulse sealing devices

- Practical basic sealing device – easy operation
- The cutter allows bags of differing lengths to be manufactured from a tubular film
- With time switch

Film thickness max.: 2 x 0.15 mm. Width: 110 mm.

		7	8	9
Welding seam max.	mm	200 x 2	300 x 2	400 x 2
Height	mm	220	230	220
Length	mm	410	510	620
Power	watt	350	500	750
	Ref.	113 537 6H	113 541 6H	113 545 6H
	€	155.00	219.00	255.00



10–18 | PE shrink films

- For sealing individual parts with different lengths

Material: polyethylene. Colour: transparent.

		10	11	12	13	14	15	16	17	18
Width	mm	80	100	200	200	300	300	400	500	600
Length	m	250	250	200	250	200	250	250	250	250
Material thickness	µm	100	100	200	100	200	100	100	100	100
Pack of	pcs.	2	2	1	1	1	1	1	1	1
	Ref.	730 897 6H	722 520 6H	730 900 6H	722 521 6H	730 901 6H	722 522 6H	722 523 6H	730 898 6H	730 899 6H
	€ / pack	84.90	109.00	109.00	99.90	139.00	139.00	165.00	155.00	189.00