



Video
Online!



EUROKRAFT pro

by KAISER+KRAFT

1–7 | Tubular steel steps

- Robust construction in lightweight design
- Optionally powder coated or zinc plated
- Anti-slip steps

Step depth: 220 mm. Step width: 400 mm.
Access: single sided. Platform depth: 220 mm. Material of treads: aluminium, ribbed. Max. load: 150 kg.

Supplied flat pack – easy self-assembly.



EUROKRAFT basic

by KAISER+KRAFT

8–9 | Tubular steel steps

- Suitable for universal use in the warehouse, office and administration
- Robust, powder coated tubular steel frame
- Stability due to large, anti-slip steps

Access: single sided. Frame material: steel. Max. load: 150 kg.

	1	2	3	4	5	6	7
Steps incl. platform pcs.	1	2	3	2	3	2	3
Feature						mobile	mobile
Platform height mm	200	400	600	400	600		600
Overall height mm	260	465	665	1100	1300	1100	1300
Overall depth mm	335	420	575	420	575	495	645
Overall width mm	460	460	460	512	512	530	530
Wheel Ø						75	75
Safety grip	without	without	without	with	with	with	with
Frame colour							
light blue Ref.	499 571 6H	499 572 6H	499 573 6H	499 577 6H	499 578 6H	499 581 6H	499 582 6H
RAL 5012 €	89.90	149.00	219.00	189.00	259.00	215.00	289.00
zinc plated Ref.	499 574 6H	499 575 6H	499 576 6H	499 579 6H	499 580 6H	499 583 6H	499 584 6H
by galvanization €	109.00	179.00	265.00	219.00	309.00	249.00	329.00

	8	9
Steps incl. platform pcs.	1	2
Platform height mm	265	375
Overall depth mm	440	645
Overall width mm	380	440
Ref.	499 088 6H	499 089 6H
€	54.90	77.90



11



11–16 | Tubular steel steps

- Anti-slip beech wood steps
- Rails with rounded edges
- Large upper step with hand slot

Step depth: 150 mm. Access: double

sided. Platform width: 320 mm. Platform depth: 250 mm. Frame material: steel, powder coated. Material of treads: beechwood. Frame colour: concrete grey RAL 7023.

Supplied flat pack – easy self-assembly.

	11	12	13	14	15	16
Steps incl. platform pcs.	2 x 2	2 x 3	2 x 4	2 x 2	2 x 3	2 x 4
Feature				mobile	mobile	mobile
Platform height mm	490	730	970	490	730	970
Overall depth mm	620	820	1000	620	820	1000
Overall width mm	460	500	540	460	500	540
Ref.	155 900 6H	156 060 6H	156 230 6H	236 292 6H	236 306 6H	236 314 6H
€	82.90	109.00	155.00	199.00	245.00	275.00



17



17–19 | Work platforms

- Sturdy tubular steel rails, powder coated grey
- Steps made of ribbed aluminium profiles
- Top step 400 x 300 mm

Step depth: 200 mm. Access: single sided. Platform width: 400 mm. Platform depth: 300 mm. Frame material: steel, powder coated. Material



of treads: aluminium with non-slip ribbed surface. Frame colour: grey.

Supplied flat pack – easy self-assembly.

10 | Wheel sets

Wheel fittings: 4 sprung castors with wheel stops. Pack of: 4.

10 | Ref. 945 283 6H € / pack 125.00

	17	18	19
Steps incl. platform pcs.	2	3	4
Platform height mm	480	710	960
Overall depth mm	530	800	1000
Overall width mm	540	570	620
Ref.	945 280 6H	945 281 6H	945 282 6H
€	219.00	275.00	329.00