



1–3 | Mobile step stairs

- Stable tubular steel construction
- Particularly easy to move using mounting bracket
- Sturdy with a low empty weight

Step depth: 162 mm. Step width: 408 mm. Feature: mobile. Access: single sided. Platform width: 408 mm. Platform depth: 228 mm. Frame material: steel, powder coated. Frame colour: light blue RAL 5012. Wheel fittings: thermoplastic rubber tyres. Max. load: 150 kg. Wheel Ø: 75 mm.

Supplied flat pack – easy self-assembly.

		1	2	3
Steps incl. platform	pcs.	2	3	4
Platform height	mm	470	705	940
Overall height	mm	1094	1434	1660
Overall depth	mm	530	720	915
Overall width	mm	490	520	540
Material of treads				
diamond lattice	Ref.	476 271 6H	476 274 6H	476 277 6H
	€	329.00	549.00	799.00
phenolic plywood	Ref.	476 272 6H	476 275 6H	476 278 6H
	€	285.00	499.00	699.00
ribbed rubber	Ref.	476 273 6H	476 276 6H	476 279 6H
	€	299.00	539.00	749.00



EUROKRAFT
by KAISER+KRAFT *pro*



Video
Online!



Available in most
RAL colours.
Only 10% extra.



4–7 | Mobile safety steps

- Ideal for removing goods from shelves
- The ladder is lowered by the gas spring when stepped on
- The ladder is light and manoeuvrable to move when not under load

Frame material: steel, powder coated. Frame colour: white aluminium RAL 9006. Access: single sided. Access type: steps. Ladder type: step ladder. Wheel Ø: 100 mm. Step spacing: 229 mm. Feature: mobile. Wheel fittings: 4 swivel castors. Max. load: 150 kg.

Supplied flat pack – easy self-assembly.

		4	5	6	7
Steps incl. platform	pcs.	3	4	5	6
Platform height	mm	700	930	1165	1390
Overall depth	mm	765	935	1205	1345
Overall width	mm	685	685	900	900
Material of treads					
diamond lattice	Ref.	476 304 6H	476 307 6H	476 310 6H	476 313 6H
	€	1195.00	1325.00	1545.00	1695.00
phenolic plywood	Ref.	476 305 6H	476 308 6H	476 311 6H	476 314 6H
	€	1095.00	1145.00	1345.00	1595.00
ribbed rubber	Ref.	476 306 6H	476 309 6H	476 312 6H	476 315 6H
	€	1095.00	1225.00	1425.00	1495.00