





Video
Online!



Steps with aluminium profile



Steps with grate



14 | Installation sets for door hinges
14 | Ref. 499 897 6H € 84.90



15 – 20 | Mobile safety steps

- Comfortable ascent – by means of 48° angle of inclination
- Flexible configuration – 2 different treads
- Mobile – due to non-marking swivel castors and fixed castors

Frame colour: light blue RAL 5012 / light grey RAL 7035.

Platform width: 510 mm. Platform depth: 810 mm. Access: single sided. Access type: single sided. Overall width: 1150 mm. Ladder type: mobile safety steps. Wheel Ø: 125 mm. Feature: mobile. Wheel fittings: 2 swivel castors with wheel stop, 2 fixed castors. Max. load: 150 kg.
Supplied flat pack – easy self-assembly.

Ideal for use in warehouses and production. Without a door as standard. Can be fitted with one self-closing hinged door (see accessories).

Produced and tested in accordance with EN 14122.

		15	16	17	18	19	20
Steps incl. platform	pcs.	3	4	5	6	7	8
Platform height	mm	609	809	1009	1209	1409	1609
Overall depth	mm	1089	1413	1413	1592	1772	1952
Material of treads							
aluminium	Ref.	499 921 6H	499 920 6H	499 919 6H	499 918 6H	499 917 6H	499 916 6H
	€	1925.00	2090.00	2290.00	2890.00	3450.00	3950.00
mesh grid	Ref.	499 915 6H	499 914 6H	499 913 6H	499 912 6H	499 911 6H	499 910 6H
	€	1695.00	1825.00	2050.00	2590.00	3190.00	3590.00

21 – 26 | XXL platform steps

- Comfortable – due an extra large platform
- Comfortable ascent – due to 48° slope
- Flexible configuration – 2 different step inserts

Frame colour: light blue RAL 5012 / light grey RAL 7035.
Platform width: 1250 mm. Platform depth: 810 mm.
Access: single sided. Access type: single sided. Overall

width: 1150 mm. Ladder type: mobile safety steps. Wheel Ø: 125 mm. Feature: mobile. Wheel fittings: 2 swivel castors with wheel stop, 2 fixed castors. Max. load: 150 kg.
Supplied flat pack – easy self-assembly.

Ideal for use in warehouses and production. With one self-closing door as standard. Can be fitted with up to three hinged doors (see accessories).

Produced and tested in accordance with EN 14122.

		21	22	23	24	25	26
Steps incl. platform	pcs.	3	4	5	6	7	8
Platform height	mm	609	809	1009	1209	1409	1609
Overall depth	mm	1790	2113	2113	2291	2471	2651
Material of treads							
aluminium	Ref.	499 909 6H	499 908 6H	499 907 6H	499 906 6H	499 905 6H	499 904 6H
	€	2290.00	2490.00	2890.00	3290.00	3850.00	4290.00
mesh grid	Ref.	499 903 6H	499 902 6H	499 901 6H	499 900 6H	499 899 6H	499 898 6H
	€	2050.00	2150.00	2650.00	3050.00	3490.00	3950.00

