

16–21 | Mobile safety steps

- Practical for mobile use
- Rails made of sturdy aluminium profiles
- Non-slip steps made of ribbed aluminium

Frame material: aluminium. Platform width: 600 mm.
Platform depth: 800 mm. Step width: 800 mm. Step
depth: 200 mm. Access: single sided. Access type: steps.
Material of treads: aluminium, ribbed. Ladder
type: mobile safety steps. Wheel Ø: 125 mm. Slope: 60°.

Feature: mobile. Wheel fittings: 2 swivel castors, 2 fixed
castors, all with wheel stops.

Delivered partially assembled – easy final assembly.

One hand rail 1100 mm in height included, can be mounted on
left or right.

Second hand rail as an accessory.

Custom designs and other platform and step coverings are
available on request.

		16	17	18	19	20	21
Steps incl. platform	pcs.	5	7	9	11	13	15
Platform height	mm	1210	1690	2180	2660	3150	3640
Overall depth	mm	1360	1630	1920	2170	2460	2740
Overall width	mm	1000	1000	1400	1400	1400	1800
	Ref.	570 753 6H	570 754 6H	570 755 6H	570 756 6H	570 757 6H	570 758 6H
	€	1745.00	1945.00	2150.00	2390.00	2590.00	2890.00



16

22–27 | Bridges

- For bridging machines, conveyor belts or pits
- Safe, fatigue-free working – even over longer periods
- Comfortable ascent – 60° slope

Ladder type: bridges. Frame material: aluminium extruded
profile. Material of treads: aluminium, ribbed. Step

depth: 200 mm. Slope: 60°. Overall max. load: 300 kg.
Platform width: 600 mm. Step width: 600 mm.

Delivered partially assembled – easy final assembly.

		22	23	24	25	26	27
Number of steps	pcs.	5	5	7	7	9	9
Platform length	mm	800	1200	800	1200	800	1200
Clear height	mm	1174	1174	1658	1658	2120	2120
Reach	mm	2142	2560	2912	3120	3442	3680
	Ref.	570 798 6H	570 805 6H	570 799 6H	570 806 6H	570 801 6H	570 807 6H
	€	1195.00	1325.00	1425.00	1595.00	1645.00	1925.00
Accessories							
Second railing	Ref.	570 802 6H	570 808 6H	570 803 6H	570 809 6H	570 804 6H	570 810 6H
	€	289.00	289.00	295.00	295.00	299.00	299.00



22

15
Year
Guarantee

Additional sizes, mobile
version, 45° angle
of inclination as well
as alternative designs available
on request.

altrex



**More products
online!**

28–30 | Aluminium folding scaffolding

- Inexpensive, robust basic scaffolding
- Quick and easy assembly due to practical claw mechanism on the struts
- Compact size when folded up – thus easy to transport and store

Platform width: 0,6 m. Platform length: 1.55 m. Material: aluminium. Max.
load: 150 kg/m². Wheel Ø: 100 mm. Scaffolding width: 0.7 m. Scaffolding
length: 1.65 m. Feature: folding. Conforms to: EN 1004.

Wheel fittings: 4 castors with wheel stops.

28 | Platform height: 0,95 m. Working height: 3 m. Tower height: 1.75 m.
Weight: 27.5 kg.


Ref. 727 739 6H € 519.00

29 | Platform height: 1,8 m. Working height: 3,8 m. Tower height: 2.8 m.
Weight: 46 kg.

Ref. 727 742 6H € 939.00

30 | Platform height: 3,8 m. Working height: 5,8 m. Tower height: 4.8 m.
Weight: 84.4 kg.

Ref. 727 743 6H € 1695.00



30



29



28

5
Year
Guarantee



Video
Online!

All articles ex works
plus charges.

Phone +49 711 3465 6999

KAISER+KRAFT

755

WORKSHOP