

## Lifting equipment

### Pallet trucks

from page 104

### Stackers and mini-lifters

Pages 113 – 121

### Stacker accessories

Page 122

### Working platforms

Page 123

### Lifting platform trolleys

from page 124

### Lifting tables

from page 133

### Bridge plates

Page 138

### Strip curtains

Page 139

## Maintenance

Technical equipment requires regular maintenance.

You'll always be on the safe side with a **maintenance contract**.

You can count on us for competent advice.

As an authorised partner we are able to offer **routine safety inspections**.

## Customer service

Our **mobile** service technicians are prompt and reliable. Therefore many repairs can be made on-site, including after warranty repair work as well.

## Spare parts

We keep wear parts in stock and we can obtain other replacement parts on short notice.


**We make daily shipments via the shortest routes.**

## Pallet trucks

### Choose the right pallet truck for individual applications

All pallet trucks have a solid frame made of torsion resistant steel, heavy duty forks reinforced at the shaft, as well as a durable, low maintenance compact hydraulic unit.

Ideal for use with EURO pallets.



## QUIPO

★ ★ ★


- ★ **Quality products – 5 year guarantee**
- ★ **Reliability – From selected suppliers**
- ★ **Value for money – Low cost**

### Select the wheels you require

**Solid rubber steering wheels**  
Fork rollers made of **nylon**.  
Lowest rolling resistance under high loads.

**Solid rubber steering wheels**  
Fork rollers made of **polyurethane**.  
Quiet running, particularly when not loaded, slightly higher rolling resistance than nylon.

**Polyurethane steering wheels**  
Fork rollers made of **polyurethane**.  
Best compromise between low noise and rolling resistance.



### 1 Standard pallet truck

With entry rollers for entering pallets from the side. Powder coated in pure orange RAL 2004. Polyurethane steering wheels, nylon fork rollers.

#### Application guide

Single fork rollers ensure a smooth run and increased manoeuvrability. Tandem fork rollers for uneven flooring.

Technical details	
Max. load	2500 kg
Fork length x width	1150 x 155 mm
Distance across forks	540 mm
Lifting range	85 – 200 mm
Steering wheel diameter	180 mm
Fork roller diameter	80 mm

Fork roller version		single	tandem
1 – 2 items	Ref.	176 289-2G	176 288-2G
	€ / each	309,-	275,-
3+ items	Ref.	290 466-2G	290 465-2G
	€ / each	295,-	259,-

### 2 QUIPO pallet truck

#### For heavy duty use.

With entry rollers for entering pallets from the side. Drawbar handle with convenient rubber coating – ideal for working in cold conditions. Powder coated in melon yellow RAL 1028.

Tandem fork rollers for uneven floors.

Technical details	
Max. load	2500 kg
Fork length x width	1150 x 160 mm
Distance across forks	540 mm
Lifting range	85 – 200 mm
Steering wheel diameter	200 mm
Fork roller diameter	80 mm

Steering wheel material	solid rubber	solid rubber	polyurethane
Fork roller version	tandem	tandem	tandem
Fork roller material	nylon	polyurethane	polyurethane
Ref.	520 028-2G	520 029-2G	520 030-2G
€	409,-	399,-	389,-

BLUE =  
14 working days