



Ref. 968 823-2G  
**€ 599,-**



Low maintenance QuickLift hydraulic unit – overload valve as standard



Pump only twice and the pallet is off the ground \*

\* QuickLift is active for loads up to 200 kg.

**QUICKLIFT**  
 quick lift – save effort and time!

Arched drawbar provides more foot clearance for the user

## Pallet trucks with QuickLift


Max. load 2300 kg

- Pump twice – pallet is off the ground \*
- Pump 5 times – maximum lifting height is attained \*
- Maintenance-free, compact hydraulics

- High quality powder coating
- With entry/exit rollers

### Complete synergy of functionality and design

Designed in Germany – manufactured in Europe. Extremely durable.



Suitable for EURO pallets

Distance across forks 520 mm  
 Fork length 1150 mm

Technical details	
Max. load	2300 kg
Distance across forks	520 mm
Fork width	160 mm
Lifting range	85 – 195 mm
Steering wheel diameter	200 mm
Fork roller diameter	82 mm

Fork length	mm	810	910	1150
Overall length	mm	1195	1295	1535
Steering wheel material	Fork roller material			
solid rubber	nylon	Ref. 968 817-2G	968 818-2G	968 819-2G
		€ 559,-	559,-	529,-
polyurethane		Ref. 968 821-2G	968 822-2G	968 823-2G
		€ 589,-	589,-	599,-
polyurethane	polyurethane	Ref. 968 824-2G	968 825-2G	968 826-2G
		€ 589,-	589,-	569,-

Video ONLINE!



Extra large handle with soft covering, comfortable to touch even when cold

BLUE = 14 working days