



QUICKLIFT

Lifts faster – saves effort and time!



Additional supports



Comfortable handle



2

In raised position



1

In half raised position

QUIPO

★ ★ ★

1 – 4 | High-lift pallet trucks

- Lift, move and deploy loads
- Work at an ideal height
- QuickLift

Mobile up to lifting height: 400 mm. Steering wheel material: polyurethane. Fork roller material: polyurethane. Fork roller version: single. Fork roller diameter: 75 mm. Finish: powder coated. Feature: manual / mobile. Fittings: QuickLift.

€ **629.00**

Ref. 480 552 6G



In lowered position

4

		1	2	3	4
Max. load	kg	1000	1000	1000	1500
Lifting range	mm	85 – 800	85 – 800	85 – 810	85 – 810
Lift drive		electro-hydraulic	manual hydraulics	manual hydraulics	manual hydraulics
Fork length	mm	1190	1140	1190	1170
Length	mm	1676	1475	1660	1640
Height	mm	1286	1260	1275	1275
Steering radius	°	210	180	180	180
Lift per pump stroke with QuickLift	mm	19	25	30	28
Lift per pump stroke	mm	11	10	14	14
Steering wheel diameter	mm	180	150	180	180
Steering wheel width	mm	55	40	50	50
Colour		melon yellow RAL 1028	signal red RAL 3001	melon yellow RAL 1028	melon yellow RAL 1028
Battery		12 V / 70 Ah			
Battery charger		6 A impulse charger			
Lifting time without load	sec	13			
Lifting time with full load	sec	22			
Ref.		968 750 6G	480 552 6G	968 747 6G	968 748 6G
€		2590.00	629.00	969.00	1075.00